

## E-Maxx Brushless (Model 39086-4) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

		E40E	Tires, subbar (2) (fits Trayvas urbaslis har urbasla)
	Bearings & Bushings	<b>5185</b> 4974	Tires, rubber (2) (fits Traxxas wheelie bar wheels) Wheelie bar arm (1)/ connector (1)/ 3x12 SS (hex drive) (4)
4612	Ball bearings (10x15x4mm) (2)	4977	Wheelie bar mount (1)
4611	Ball bearings (5x11x4mm) (2)	4975	Wheelie bar, assembled (fits all Maxx trucks)
4608	Ball Bearings (5x11x4mm) (6)/ 5x8x2.5mm (8)	4976	Wheels (4)/ axles (2), for Maxx wheelie bar
2728	Ball bearings (5x8x2.5mm) (2)	5186A	Wheels, aluminum (blue-anodized) (2)/ 5x8mm ball bearings (4)/
4614	Ball bearings (6x12x4mm) (2)		axles (2)/ rubber tires (2)
5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)	5186	Wheels, aluminum (red-anodized) (2)/ 5x8mm ball bearings (4)/
5120 5116	Ball bearings, blue rubber sealed (12x18x4mm) (2)		axles (2)/ rubber tires (2)
5116 5114	Ball bearings, blue rubber sealed (5x11x4mm) (2)  Ball bearings, blue rubber sealed (5x8x2.5mm) (2)		Differential Components
5117	Ball bearings, blue rubber sealed (5x6x2.5mm) (2)	5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)
5180	Ball bearings, blue rubber sealed (6x13x5mm) (2)	5117	Ball bearings, blue rubber sealed (6x12x4mm) (2)
5118	Ball bearings, blue rubber sealed (8x16x5mm) (2)	5118	Ball bearings, blue rubber sealed (8x16x5mm) (2)
2545	Bellcrank bushings (plastic) (5x8x2.5mm) (4)	3978	Carrier, differential (heavy duty)/ x-ring gaskets (2)/ ring gear gasket/
	Body & Accessories		bushings (2)/ 6x10x0.5 TW
4000		5614	Differential kit, center (complete for E-Revo & E-Maxx (model
1926	Antenna caps, vinyl (2)/ antenna spool		3905 & 3908)) (assembled with 500K oil) (use only with single
5526 <b>5526R</b>	Antenna crimp nut, aluminum (blue-anodized)/ antenna nut tools  Antenna crimp nut, aluminum (red-anodized)/ antenna nut tools	5382X	speed transmission) Gear set, differential (output gears (2)/ spider gears (2)/ spider gear
1726	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)	330ZA	shaft/ diff carrier support)
3934	Body clips, heavy duty (12)	3979	Housings, differential (left & right)/ pinion collar (1)
4914R	Body mount posts, front (2)/ body mount, rear/ body mount screw	5379X	Ring gear, differential/ pinion gear, differential
101111	pins (4)	5379R	Ring gear, differential/ pinion gear, differential (machined, spiral
1815	Body washers (8)		cut) (front)
4915	Body washers, foam adhesive (10)	3236	Screws, 2.5x12mm cap-head machine (6)
6716	Body washers, foam, 2mm (2)/ 3mm (2)/ 4mm (4)	2577	Screws, 3x10mm button-head machine (hex drive) (6)
3915	Body, E-Maxx Brushless (clear, requires painting)/ decal sheet	1647	Silicone grease
3915X	Body, E-Maxx Brushless, ProGraphix (replacement for painted body.	5381X	Spool, differential (eliminates differential. Use off-road only)
	Graphics are printed, requires paint & final color application)/decal		(requires #5379X ring gear)
00407	sheet		Driveline Components
3913X	Decal sheet, Flames	5334	Axle carriers, left & right (1 each)
<b>2514</b>	Decal sheet, racing sponsors	5334R	Axle carriers, left & right (1 each) (use with larger 6x13mm ball
3916 <b>9950</b>	Decal sheets, E-Maxx Brushless (model 3908)  Official Team Traxxas racing decal set (flag logo/ 6-color)		bearings)/ bearing adapters (for 6x12mm ball bearings) (2)/ dust
5185	Tires, rubber (2) (fits Traxxas wheelie bar wheels)		boot retainers (4)
4974	Wheelie bar arm (1)/ connector (1)/ 3x12 SS (hex drive) (4)	4928X	Differential output yokes (heavy duty) (2)/ set screw yoke pins, M4/10
4977	Wheelie bar mount (1)		(2)
4975	Wheelie bar, assembled (fits all Maxx trucks)	5153	Drive cups, inner (2) Revo/Maxx (steel constant-velocity
4976	Wheels (4)/ axles (2), for Maxx wheelie bar	5451X	driveshafts)/screw pin, M4/15(2)  Driveshaft assembly (1), left or right (fully assembled, ready to install)/
5186A	Wheels, aluminum (blue-anodized) (2)/ 5x8mm ball bearings (4)/	0 <del>4</del> 01/	4x15mm screw pin (1)
	axles (2)/ rubber tires (2)	5188	Driveshaft, steel constant-velocity (shaft only, 112mm)/ drive cup
5186	Wheels, aluminum (red-anodized) (2)/ 5x8mm ball bearings (4)/		pin (1) (fits rear center shaft on 3905 E-Maxx)
	axles (2)/ rubber tires (2)	5187	Driveshaft, steel constant-velocity (shaft only, 55mm)/ drive cup
	Bumpers & Skidplates		pin (1) (fits front center shaft on 3905 E-Maxx)
4936	Bumper mounts, front (l&r)/ bumper mounts, rear (l&r)/ 3x12mm RHM	5154	Driveshaft, steel constant-velocity, Revo/Maxx (shaft only,
	screws (8)	5454B	128.5mm)/ drive cup pin (1)
4935X	Bumpers, 6061-T6, brushed aluminum (f&r)	5151R	Driveshafts, center E-Maxx (steel constant-velocity) front (1)/ rear (1) (assembled with inner and outer dust boots, for 3905 E-
3926	Bumpers, black chrome (f&r)		Maxx)
4935	Bumpers, satin finished (f&r)	5451R	Driveshafts, Revo/Maxx (steel constant-velocity)(assembled
4937	Skidplate, front plastic (black)/ stainless steel plate	• .•	w/inner & outer dust boots) (for models w/sealed pivot ball
4937A	Skidplate, front plastic (grey)/ stainless steel plate		suspension & 3.8" wheels)(4)
4938	Skidplate, rear plastic (black)/ stainless steel plate	5150	E-clips, 1.5mm (24)
4938A	Skidplate, rear plastic (grey)/ stainless steel plate	5450	Half shaft set, left or right (plastic parts only) (internal splined half
3920 4974	Skidplate, transmission, nylon (grey)		shaft/ external splined half shaft/ rubber boot) (assembled with glued
4974 4977	Wheelie bar arm (1)/ connector (1)/ 3x12 SS (hex drive) (4) Wheelie bar mount (1)	5050	boot) (2 assemblies)
4977	Wheelie bar mount (1) Wheelie bar, assembled (fits all Maxx trucks)	5650	Half shafts, center (internal splined (3)/ external splined (2)) (plastic
4976	Wheels (4)/ axles (2), for Maxx wheelie bar	4955	parts only) Pins, axle (2.5x12mm) (4)
5186A	Wheels, aluminum (blue-anodized) (2)/ 5x8mm ball bearings (4)/	5129	Rebuild kit (for Revo/Maxx steel constant-velocity driveshafts)
010071	axles (2)/ rubber tires (2)	0123	(includes pins, dustboots, & lube for 2 driveshafts assemblies)
5186	Wheels, aluminum (red-anodized) (2)/ 5x8mm ball bearings (4)/	5145	Screw pin, 4x15mm (6)
	axles (2)/ rubber tires (2)	5189	Screw pins, 4x13mm (with threadlock) (4)
	Chassis & Attachments	5454	Stub axle (steel) (2)
2024		5166	Stub axle, (1)/ axle sleeve (1) Revo/Maxx (steel constant-velocity
3924	Box, receiver (sealed)/ foam pad/ silicone grease/2.5x8mm BCS (2)/ 3x10mm CCS (2)/ 3x15mm CCS (2)		driveshaft)
3930	Bulkhead cross braces (2)/ 3x25mm CS screws (8)	5452	U-joints, driveshaft (carrier (4)/ 4.5mm cross pin (4)/ 3mm cross pin
3921	Chassis braces, lower (black) (2)	40=	(4)/ e-clips (20)) (metal parts for 2 driveshafts)
3922A	Chassis, E-Maxx (long wheelbase)	4954R	Wheel hubs, hex (steel)
3927	Hold downs, battery, left & right (2)/ foam spacers (2) (fits standard	4954X	Wheel hubs, hex, 6061-T6 aluminum (blue) (4)/ axle pins
	battery packs)	5353X	(2.5x10mm) (4) Wheel hubs, splined, 17mm (blue-anodized) (4)/ wheel nuts, splined,
3927X	Hold downs, battery, left & right (2)/ foam spacers (4) (allows for	0000A	17mm (blue-anodized) (4)/ screw pins, 4x13mm (with threadlock) (4)
	installation of taller, multi-cell batteries)	5353G	Wheel hubs, splined, 17mm (green-anodized) (4)/ wheel nuts,
3928	Retainer, battery hold-down, front (2)/ rear (2)/ CCS 3x12 (4)		splined, 17mm (blue-anodized) (4)/ screw pins, 4x13mm (with
3925	Seal kit, receiver box (includes o-ring, seals, and silicone grease)		threadlock) (4)
3920	Skidplate, transmission, nylon (grey)		

Page 2	E-Maxx Brushless: TQi Traxxas Link Enabled 2.40	Hz Radi	o & TSM (Model 39086-4) Parts List
5353R	Wheel hubs, splined, 17mm (red-anodized) (4)/ wheel nuts,	2575	Screws, 3x6mm button-head machine (hex drive) (6)
	splined, 17mm (red-anodized) (4)/ screw pins, 4x13mm (with threadlock) (4)	2550	Screws, 3x8mm countersunk machine (6) (hex drive)
5353	Wheel nuts, splined, 17mm (blue-anodized) (4)	3642X 2537	Shoulder screws, Ultra Shocks (3x12 hex drive) (6) Threaded rods (20/25/44mm 1 ea.)/ (1) 12mm set screw
5353A	Wheel nuts, splined, 17mm (green-anodized) (4)	2001	Motors & Electronics
5458X	Yokes, differential and transmission (2)/ 4x15mm screw pins (2)	3977R	Cover, gear (upper & lower) (1)/ dust plug (1)/ 3x6mm CS (3) (for
5453	Yokes, stub axle (2)/ pins (2)	337710	single motor installation, use with motor plate #3997X)
	Front Suspension & Steering	2064	Gear set (for 2065 waterproof sub-micro servo)
<b>4934X</b> 5334	Aluminum caps, pivot ball (blue-anodized) (4)	2072	Gear set (for 2070, 2075 servos)
5334R	Axle carriers, left & right (1 each)  Axle carriers, left & right (1 each) (use with larger 6x13mm ball	3376	Motor, 2200Kv 75mm, brushless (with 6.5mm gold-plated connectors & high-efficiency heatsink)
	bearings)/ bearing adapters (for 6x12mm ball bearings) (2)/ dust	3378	MXL-6s Brushless Power System, waterproof (includes MXL-6s
0700	boot retainers (4)		waterproof ESC, 2200Kv, 75mm motor)
<b>2728</b> 2545	Ball bearings (5x8x2.5mm) (2) Bellcrank bushings (plastic) (5x8x2.5mm) (4)	3377	MXL-6s Electronic Speed Control, waterproof (brushless) (fwd/rev/brake)
4944	Bellcrank posts, aluminum (2)/ steering link threaded rod (3x25mm)/	3997X	Plate, motor (for single motor installation, use gear cover #3977R)
	long rod ends (2)	3159	Screws, 3x10mm caphead machine (hex drive) (6)/ lockwashers (6)/
4914R	Body mount posts, front (2)/ body mount, rear/ body mount screw pins (4)	2565	hex wrench Screws, 3x18mm roundhead machine (6)
3930	Bulkhead cross braces (2)/ 3x25mm CS screws (8)	2554	Screws, 3x6mm cap-head machine (by drive) (6)
4930R	Bulkheads (I & r) (front) (grey)	2074	Servo case/gaskets (for 2056 and 2075 waterproof servos)
4930X	Bulkheads, front (machined 6061-T6 aluminum) (blue) (l&r)	2063	Servo case/gaskets (for 2065 waterproof sub-micro servo)
5134	(requires use of 4939X suspension pins) Caster spacers (4)/ shims (4)	2075 <b>2065</b>	Servo, digital high-torque (ball bearing), waterproof Servo, sub-micro, waterproof
5355	Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer	2003	
=0=0\/	adjustment shims; 3.5mm (2), 1.17mm (2)	2072V	Radio System, Batteries & Chargers
5378X	Pivot ball caps (4)/ dust boots, rubber (4)/ dust plugs, rubber (4)/ dust boot retainers, black (4), blue (4) (2 pkgs. req. to complete truck)	2872X 2843X	5000mAh 11.1v 3-Cell 25C LiPo Battery 5800mAh 7.4v 2-Cell 25C LiPo Battery
4933	Pivot balls (4)/ pivot ball cap bushings (4)	2869X	7600mAh 7.4v 2-Cell 25C LiPo Battery
4933X	Pivot balls, hard-anodized 7075-T6 aluminum (4)/ pivot ball cap	2976	AC to DC converter, 40W
E247	bushings (4)	2938X	Adapter, Traxxas iD LiPo battery (adapts Traxxas iD batteries to separate balance ports)
5347 5349	Rod ends, Revo (large) with hollow balls (12) Rod ends, small, with hollow balls (6) (for Revo steering linkage)	1726	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)
3968	Servo horns, steering (2)/ steering link (3x12mm threaded rod (1)/ rod	6546	Battery door, TQi transmitter (replacement for #6528, 6529, 6530
2075	ends (2)/ hollow balls (2) Servo, digital high-torque (ball bearing), waterproof	2914	transmitters) Battery, Power Cell AA Alkaline (4)
4917R	Shock tower (for rectangular body posts)	2923X	Battery, Power Cell, 3000mAh (NiMH, 7-C flat, 8.4V)
4945	Steering bellcranks/ servo saver/ servo saver spring/ servo spring	2942X	Battery, Series 3 Power Cell, 3300mAh (NiMH, 6-C flat, 7.2V)
2044	retainer (requires 5x11mm BB (2))	2940X 2952X	Battery, Series 3 Power Cell, 3300mAh (NiMH, 7-C flat, 8.4V)
3941	Steering drag link (4x72mm turnbuckle) (1)/ rod ends (2)/ hollow balls (2)	2952X 2950X	Battery, Series 4 Power Cell, 4200mAh (NiMH, 6-C flat, 7.2V) Battery, Series 4 Power Cell, 4200mAh (NiMH, 7-C flat, 8.4V)
3941R	Steering drag link (Tubes red-anodized, 7075-T6 aluminum,	2960X	Battery, Series 5 Power Cell, 5000mAh (NiMH, 7-C flat, 8.4V)
5400D	stronger than titanium) (72mm) (1)/ rod ends (2)/ aluminum 7mm wrench	2991	Battery/charger completer pack (includes #2972 Dual iD charger (1), #2869X 7600mAh 7.4V 2-cell 25C LiPo battery (2))
5132R 5131R	Suspension arms (lower) (2) (fits all Maxx series) Suspension arms (upper) (2) (fits all Maxx series)	2975 2972	Charger, DC, 4 amp (6 - 7 cell, 7.2 - 8.4 volt, NiMH) Charger, EZ-Peak Dual, 100W, NiMH/LiPo with iD Auto Battery
5161	Suspension screw pin set, hardened steel (hex drive)	2312	Identification
5141A	Toe links, Maxx (Tubes black-anodized, 7075-T6 aluminum, stronger than titanium) (112mm, front) (2)/ rod ends (4)/	2971	Charger, EZ-Peak Live, 100W, NiMH/LiPo with iD Auto Battery
	aluminum wrench (1) (For Maxx models w/sealed pivot ball	2970	Identification Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with iD Auto Battery
5141R	suspension & 3.8' wheels) Toe links, Maxx (Tubes red-anodized, 7075-T6 aluminum,	CEOE	Identification
J14110	stronger than titanium) (112mm, front) (2)/ rod ends (4)/	6525 2978	Communication link, telemetry expander Fuse, charger, 5A (2) (for #2974, 2975, 2977)
	aluminum wrench (1) (For Maxx models w/sealed pivot ball	2064	Gear set (for 2065 waterproof sub-micro servo)
5141	suspension & 3.8" wheels) Turnbuckles, toe links (5.0mm steel) (front) (2)	2072	Gear set (for 2070, 2075 servos)
5141	Hardware	6556	Mount, telemetry expander (fits XO-1, E-Revo*, Summit*, all Maxx trucks, Revo 3.3, Slayer Pro 4X4) (*requires rear chassis brace
5526	Antenna crimp nut, aluminum (blue-anodized)/ antenna nut tools		#5632)
5526R	Antenna crimp nut, aluminum (blue-anodized)/ antenna nut tools  Antenna crimp nut, aluminum (red-anodized)/ antenna nut tools	6535	Mount, temperature sensor (electric motors)/ wire tie/ thermal
3934	Body clips, heavy duty (12)	6533	pad Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel)
5150	E-clips, 1.5mm (24)	<b>6552</b>	Seal kit, expander box (includes o-ring, seals, and silicone
5477 5478	Flat wrench, 5mm (blue-anodized aluminum) Flat wrench, 8mm (blue-anodized aluminum)		grease)
2586	Head screws, 3x15mm cap-head machine (hex drive) (6) (TRX 2.5)	6526	Sensor, auto-detectable, temperature
5476X	Hex wrenches; 1.5mm, 2mm, 2.5mm, 3mm, 2.5mm ball	6527 6522	Sensor, auto-detectable, voltage Sensor, RPM (short)/ 3x4mm BCS (2)
5355	Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer	6521	Sensor, temperature and voltage (long)
5475	adjustment shims; 3.5mm (2), 1.17mm (2)  Multi-tool (plastic)	2074	Servo case/gaskets (for 2056 and 2075 waterproof servos)
4147X	Nuts, 5mm flanged nylon locking (aluminum, blue-anodized) (4)	2063	Servo case/gaskets (for 2065 waterproof sub-micro servo)
5147X	Nuts, 5mm flanged nylon locking (steel, serrated) (8)	2075 <b>2065</b>	Servo, digital high-torque (ball bearing), waterproof Servo, sub-micro, waterproof
5347 5340	Rod ends, Revo (large) with hollow balls (12)	6550	Telemetry expander, TQi radio system
5349 3215	Rod ends, small, with hollow balls (6) (for Revo steering linkage) Screws, 2.5x6mm cap-head machine (hex drive) (6)	6551	Telemetry GPS module, TQi radio system
3965	Screws, 2.5x8mm cap-head machine (6)	6538	Telemetry trigger magnet holders, spur gear/ magnet, 5x2mm (1)/
2577	Screws, 3x10mm button-head machine (hex drive) (6)	6540	3x8mm CCS (3)/ 3x10mm CCS (3) Telemetry trigger magnet, 5X2mm (1)
4859 2579	Screws, 3x10mm flat-head machine (hex drive) (4)	2928	Temperature sensor, EZ-Peak Plus
2578 2552	Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x12mm countersunk machine (6) (hex drive)	6509R	TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link
2579	Screws, 3x15mm button-head machine (hex drive) (6)	6507R	enabled, TSM (2-ch transmitter, 5-ch micro receiver)  TQi 2.4 GHz High Output radio system, 4-channel with Traxxas
2553 2583	Screws, 3x15mm countersunk machine (6) (hex drive) Screws, 3x18mm button-head machine (hex drive) (6)	0007TC	Link Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver)
	, , , , ,		100011017

Transmitter, TQi Traxxas Link enabled, 2.4GHz high output,	3767P	Shock caps, aluminum (pink-anodized) (4) (fits all Ultra Shocks)
		Shock caps, aluminum (red-anodized) (4) (fits all Ultra Shocks)
3-channel (transmitter only)	20301	Shock shafts, hardened steel, titanium nitride coated (xx-long) (2)
Transmitter, TQi Traxxas Link enabled, 2.4GHz high output,	2656	Shock shafts, steel, chrome finish (xx-long) (2)
• • • • • • • • • • • • • • • • • • • •		Shoulder screws, Ultra Shocks (3x12 hex drive) (6)
		Silicone diaphragms (4)
		Silicone shock oil (30 wt)  Spring pre-load spacers: 1mm (4)/ 2mm (2)/ 4mm (2)/ 8mm (2)
₹	3768	Spring retainers, upper & lower (2)/ piston head set (2-hole (2)/ 3-ho
		(2))
Stability Management (TSM)	4957R	Springs, progressive rate (for Ultra-Shocks only) (progressive rate)
Rear Suspension	1057	(f/r) (4) Springs, red (for Ultra Shocks only) (2.5 rate) (f/r) (2)
	3762	Ultra Shocks (black) (xx-long) (complete w/ spring pre-load
Axle carriers, left & right (1 each)		spacers & springs) (rear) (2)
Axle carriers, left & right (1 each) (use with larger 6x13mm ball	3762A	Ultra Shocks (grey) (xx-long) (complete w/ spring pre-load spacers &
		springs) (rear) (2)
		Slipper Clutch Components
		Ball bearings, blue rubber sealed (5x11x4mm) (2)
Body mount posts, front (2)/ body mount, rear/ body mount screw		Flat wrench, 8mm (blue-anodized aluminum)
pins (4)		Universal wrench (glow plug wrench) Nuts, 4mm nylon locking (10)
		Rebuild kit (heavy duty), slipper clutch (steel disc/ aluminum friction
( ) ( ) (0 ))	0002.1	pads (3)/ spring, Revo (1)/ spring, Maxx (1)/ 2x9.8mm pin/ 5x8mm
		MW/ 5.0mm NL (1)/ 4.0mm NL (1))
Caster spacers (4)/ shims (4)	5352X	Rebuild kit, slipper clutch (steel disc/ friction pads (3)/ spring (2
Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer	2554	2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1)) Screws, 3x6mm cap-head machine (hex drive) (6)
		Slipper pressure plate and hub (alloy)
		Spur Gears & Pinion Gears
	E640	Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fi
Pivot balls, hard-anodized 7075-T6 aluminum (4)/ pivot ball cap	3040	5mm shaft)/ set screw
bushings (4)	5643	Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits
Rod ends, Revo (large) with hollow balls (12)		5mm shaft)/ set screw
	5644	Gear, 18-T pinion (0.8 metric pitch, compatible with 32-pitch)
	5646	(hardened steel) (fits 5mm shaft)/ set screw  Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (fit
· · · · · · · · · · · · · · · · · · ·	3040	5mm shaft)/ set screw
Suspension arms (upper) (2) (fits all Maxx series)	3960	Spur gear, 65-tooth (0.8 metric pitch, compatible with 32-pitch)
Tie bar, rear (1) /3x18mm BCS (2) (fits all Maxx trucks)	3961	Spur gear, 68-tooth (0.8 metric pitch, compatible with 32-pitch)
		Steering Components
	2728	Ball bearings (5x8x2.5mm) (2)
3.8' wheels)	5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)
Toe links, Maxx (Tubes red-anodized, 7075-T6 aluminum,	5114	Ball bearings, blue rubber sealed (5x8x2.5mm) (2)
		Bellcrank bushings (plastic) (5x8x2.5mm) (4)
	4944	Bellcrank posts, aluminum (2)/ steering link threaded rod (3x25mm)/ long rod ends (2)
·	5347	Rod ends, Revo (large) with hollow balls (12)
	5349	Rod ends, small, with hollow balls (6) (for Revo steering linkage)
,	3968	Servo horns, steering (2)/ steering link (3x12mm threaded rod (1)/ ro
Big Bore shocks (XX-long) (hard-anodized & PTFE-coated T6		ends (2)/ hollow balls (2)
	2075	Servo, digital high-torque (ball bearing), waterproof
	1015	Stooring holloropka/ convo cover/ convo cover coring/ convo coring
aluminum) (assembled with TiN shafts) w/o springs (rear) (2) Big Bore shocks (xx-long) (hard-anodized & PTFE-coated T6	4945	Steering bellcranks/ servo saver/ servo saver spring/ servo spring retainer (requires 5x11mm BB (2))
aluminum) (assembled with TiN shafts) w/o springs (rear) (2) Big Bore shocks (xx-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled) w/ red springs, TiN shafts (8 pack)	4945 3941	retainer (requires 5x11mm BB (2))
aluminum) (assembled with TiN shafts) w/o springs (rear) (2) Big Bore shocks (xx-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled) w/ red springs, TiN shafts (8 pack) Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushings	3941	retainer (requires 5x11mm BB (2)) Steering drag link (4x72mm turnbuckle) (1)/ rod ends (2)/ hollow ball (2)
aluminum) (assembled with TiN shafts) w/o springs (rear) (2) Big Bore shocks (xx-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled) w/ red springs, TiN shafts (8 pack) Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushings & washers (2) (Big Bore Shocks)		retainer (requires 5x11mm BB (2)) Steering drag link (4x72mm turnbuckle) (1)/ rod ends (2)/ hollow ball (2) Steering drag link (Tubes red-anodized, 7075-T6 aluminum,
aluminum) (assembled with TiN shafts) w/o springs (rear) (2) Big Bore shocks (xx-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled) w/ red springs, TiN shafts (8 pack) Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushings	3941	retainer (requires 5x11mm BB (2)) Steering drag link (4x72mm turnbuckle) (1)/ rod ends (2)/ hollow ball (2) Steering drag link (Tubes red-anodized, 7075-T6 aluminum, stronger than titanium) (72mm) (1)/ rod ends (2)/ aluminum 7mm
aluminum) (assembled with TiN shafts) w/o springs (rear) (2) Big Bore shocks (xx-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled) w/ red springs, TiN shafts (8 pack) Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushings & washers (2) (Big Bore Shocks) Rebuild kit, Ultra shocks (for 2 shocks) Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2)	3941 <b>3941</b> R	retainer (requires 5x11mm BB (2)) Steering drag link (4x72mm turnbuckle) (1)/ rod ends (2)/ hollow ball (2) Steering drag link (Tubes red-anodized, 7075-T6 aluminum, stronger than titanium) (72mm) (1)/ rod ends (2)/ aluminum 7mm wrench
aluminum) (assembled with TiN shafts) w/o springs (rear) (2) Big Bore shocks (xx-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled) w/ red springs, TiN shafts (8 pack) Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushings & washers (2) (Big Bore Shocks) Rebuild kit, Ultra shocks (for 2 shocks) Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) Set (grub) screws, 3x25mm (8)/ 3mm nylon locknuts (8)	3941	retainer (requires 5x11mm BB (2)) Steering drag link (4x72mm turnbuckle) (1)/ rod ends (2)/ hollow ball (2) Steering drag link (Tubes red-anodized, 7075-T6 aluminum, stronger than titanium) (72mm) (1)/ rod ends (2)/ aluminum 7mm wrench Threaded rods (20/25/44mm 1 ea.)/ (1) 12mm set screw
aluminum) (assembled with TiN shafts) w/o springs (rear) (2) Big Bore shocks (xx-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled) w/ red springs, TiN shafts (8 pack) Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushings & washers (2) (Big Bore Shocks) Rebuild kit, Ultra shocks (for 2 shocks) Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) Set (grub) screws, 3x25mm (8)/ 3mm nylon locknuts (8) Shock caps, aluminum (Big Bore Shocks) (2)	3941 <b>3941R</b> 2537	retainer (requires 5x11mm BB (2)) Steering drag link (4x72mm turnbuckle) (1)/ rod ends (2)/ hollow ball (2) Steering drag link (Tubes red-anodized, 7075-T6 aluminum, stronger than titanium) (72mm) (1)/ rod ends (2)/ aluminum 7mm wrench Threaded rods (20/25/44mm 1 ea.)/ (1) 12mm set screw  Suspension Linkage
aluminum) (assembled with TiN shafts) w/o springs (rear) (2) Big Bore shocks (xx-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled) w/ red springs, TiN shafts (8 pack) Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushings & washers (2) (Big Bore Shocks) Rebuild kit, Ultra shocks (for 2 shocks) Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) Set (grub) screws, 3x25mm (8)/ 3mm nylon locknuts (8) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long)	3941 3941R 2537 5134	retainer (requires 5x11mm BB (2)) Steering drag link (4x72mm turnbuckle) (1)/ rod ends (2)/ hollow ball (2) Steering drag link (Tubes red-anodized, 7075-T6 aluminum, stronger than titanium) (72mm) (1)/ rod ends (2)/ aluminum 7mm wrench Threaded rods (20/25/44mm 1 ea.)/ (1) 12mm set screw  Suspension Linkage Caster spacers (4)/ shims (4)
aluminum) (assembled with TiN shafts) w/o springs (rear) (2) Big Bore shocks (xx-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled) w/ red springs, TiN shafts (8 pack) Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushings & washers (2) (Big Bore Shocks) Rebuild kit, Ultra shocks (for 2 shocks) Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) Set (grub) screws, 3x25mm (8)/ 3mm nylon locknuts (8) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2)	3941 <b>3941R</b> 2537	retainer (requires 5x11mm BB (2)) Steering drag link (4x72mm turnbuckle) (1)/ rod ends (2)/ hollow bal (2) Steering drag link (Tubes red-anodized, 7075-T6 aluminum, stronger than titanium) (72mm) (1)/ rod ends (2)/ aluminum 7mr wrench Threaded rods (20/25/44mm 1 ea.)/ (1) 12mm set screw  Suspension Linkage
aluminum) (assembled with TiN shafts) w/o springs (rear) (2) Big Bore shocks (xx-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled) w/ red springs, TiN shafts (8 pack) Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushings & washers (2) (Big Bore Shocks) Rebuild kit, Ultra shocks (for 2 shocks) Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) Set (grub) screws, 3x25mm (8)/ 3mm nylon locknuts (8) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long)	3941 3941R 2537 5134	retainer (requires 5x11mm BB (2)) Steering drag link (4x72mm turnbuckle) (1)/ rod ends (2)/ hollow ball (2) Steering drag link (Tubes red-anodized, 7075-T6 aluminum, stronger than titanium) (72mm) (1)/ rod ends (2)/ aluminum 7mr wrench Threaded rods (20/25/44mm 1 ea.)/ (1) 12mm set screw  Suspension Linkage Caster spacers (4)/ shims (4) Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer adjustment shims; 3.5mm (2), 1.17mm (2) Rod ends, Revo (large) with hollow balls (12)
aluminum) (assembled with TiN shafts) w/o springs (rear) (2) Big Bore shocks (xx-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled) w/ red springs, TiN shafts (8 pack) Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushings & washers (2) (Big Bore Shocks) Rebuild kit, Ultra shocks (for 2 shocks) Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) Set (grub) screws, 3x25mm (8)/ 3mm nylon locknuts (8) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Silicone shock oil (30 wt)	3941 3941R 2537 5134 5355 5347 5349	retainer (requires 5x11mm BB (2)) Steering drag link (4x72mm turnbuckle) (1)/ rod ends (2)/ hollow ball (2) Steering drag link (Tubes red-anodized, 7075-T6 aluminum, stronger than titanium) (72mm) (1)/ rod ends (2)/ aluminum 7mm wrench Threaded rods (20/25/44mm 1 ea.)/ (1) 12mm set screw  Suspension Linkage Caster spacers (4)/ shims (4) Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer adjustment shims; 3.5mm (2), 1.17mm (2) Rod ends, Revo (large) with hollow balls (12) Rod ends, small, with hollow balls (6) (for Revo steering linkage)
aluminum) (assembled with TiN shafts) w/o springs (rear) (2) Big Bore shocks (xx-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled) w/ red springs, TiN shafts (8 pack) Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushings & washers (2) (Big Bore Shocks) Rebuild kit, Ultra shocks (for 2 shocks) Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) Set (grub) screws, 3x25mm (8)/ 3mm nylon locknuts (8) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Silicone shock oil (30 wt) Spring retainers, upper & lower (2)/ spring pre-load spacers:	3941 3941R 2537 5134 5355 5347 5349 2553	retainer (requires 5x11mm BB (2)) Steering drag link (4x72mm turnbuckle) (1)/ rod ends (2)/ hollow ball (2) Steering drag link (Tubes red-anodized, 7075-T6 aluminum, stronger than titanium) (72mm) (1)/ rod ends (2)/ aluminum 7mr wrench Threaded rods (20/25/44mm 1 ea.)/ (1) 12mm set screw  Suspension Linkage  Caster spacers (4)/ shims (4) Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer adjustment shims; 3.5mm (2), 1.17mm (2) Rod ends, Revo (large) with hollow balls (12) Rod ends, small, with hollow balls (6) (for Revo steering linkage) Screws, 3x15mm countersunk machine (6) (hex drive)
aluminum) (assembled with TiN shafts) w/o springs (rear) (2) Big Bore shocks (xx-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled) w/ red springs, TiN shafts (8 pack) Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushings & washers (2) (Big Bore Shocks) Rebuild kit, Ultra shocks (for 2 shocks) Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) Set (grub) screws, 3x25mm (8)/ 3mm nylon locknuts (8) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Silicone shock oil (30 wt) Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore	3941 3941R 2537 5134 5355 5347 5349 2553 3642X	retainer (requires 5x11mm BB (2)) Steering drag link (4x72mm turnbuckle) (1)/ rod ends (2)/ hollow ball (2) Steering drag link (Tubes red-anodized, 7075-T6 aluminum, stronger than titanium) (72mm) (1)/ rod ends (2)/ aluminum 7mm wrench Threaded rods (20/25/44mm 1 ea.)/ (1) 12mm set screw  Suspension Linkage  Caster spacers (4)/ shims (4) Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer adjustment shims; 3.5mm (2), 1.17mm (2) Rod ends, Revo (large) with hollow balls (12) Rod ends, small, with hollow balls (6) (for Revo steering linkage) Screws, 3x15mm countersunk machine (6) (hex drive) Shoulder screws, Ultra Shocks (3x12 hex drive) (6)
aluminum) (assembled with TiN shafts) w/o springs (rear) (2) Big Bore shocks (xx-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled) w/ red springs, TiN shafts (8 pack) Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushings & washers (2) (Big Bore Shocks) Rebuild kit, Ultra shocks (for 2 shocks) Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) Set (grub) screws, 3x25mm (8)/ 3mm nylon locknuts (8) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Silicone shock oil (30 wt) Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks)	3941 3941R 2537 5134 5355 5347 5349 2553 3642X 5161	retainer (requires 5x11mm BB (2)) Steering drag link (4x72mm turnbuckle) (1)/ rod ends (2)/ hollow ball (2) Steering drag link (Tubes red-anodized, 7075-T6 aluminum, stronger than titanium) (72mm) (1)/ rod ends (2)/ aluminum 7mm wrench Threaded rods (20/25/44mm 1 ea.)/ (1) 12mm set screw  Suspension Linkage  Caster spacers (4)/ shims (4) Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer adjustment shims; 3.5mm (2), 1.17mm (2) Rod ends, Revo (large) with hollow balls (12) Rod ends, small, with hollow balls (6) (for Revo steering linkage) Screws, 3x15mm countersunk machine (6) (hex drive) Shoulder screws, Ultra Shocks (3x12 hex drive) (6) Suspension screw pin set, hardened steel (hex drive)
aluminum) (assembled with TiN shafts) w/o springs (rear) (2) Big Bore shocks (xx-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled) w/ red springs, TiN shafts (8 pack) Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushings & washers (2) (Big Bore Shocks) Rebuild kit, Ultra shocks (for 2 shocks) Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) Set (grub) screws, 3x25mm (8)/ 3mm nylon locknuts (8) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Silicone shock oil (30 wt) Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, red (for big bore shocks) (2.5 rate) (2)	3941 3941R 2537 5134 5355 5347 5349 2553 3642X	retainer (requires 5x11mm BB (2)) Steering drag link (4x72mm turnbuckle) (1)/ rod ends (2)/ hollow ball (2) Steering drag link (Tubes red-anodized, 7075-T6 aluminum, stronger than titanium) (72mm) (1)/ rod ends (2)/ aluminum 7mm wrench Threaded rods (20/25/44mm 1 ea.)/ (1) 12mm set screw  Suspension Linkage  Caster spacers (4)/ shims (4) Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer adjustment shims; 3.5mm (2), 1.17mm (2) Rod ends, Revo (large) with hollow balls (12) Rod ends, small, with hollow balls (6) (for Revo steering linkage) Screws, 3x15mm countersunk machine (6) (hex drive) Shoulder screws, Ultra Shocks (3x12 hex drive) (6) Suspension screw pin set, hardened steel (hex drive) Toe links, Maxx (Tubes black-anodized, 7075-T6 aluminum,
aluminum) (assembled with TiN shafts) w/o springs (rear) (2) Big Bore shocks (xx-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled) w/ red springs, TiN shafts (8 pack) Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushings & washers (2) (Big Bore Shocks) Rebuild kit, Ultra shocks (for 2 shocks) Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) Set (grub) screws, 3x25mm (8)/ 3mm nylon locknuts (8) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Silicone shock oil (30 wt) Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, red (for big bore shocks) (2.5 rate) (2)	3941 3941R 2537 5134 5355 5347 5349 2553 3642X 5161	retainer (requires 5x11mm BB (2)) Steering drag link (4x72mm turnbuckle) (1)/ rod ends (2)/ hollow ball (2) Steering drag link (Tubes red-anodized, 7075-T6 aluminum, stronger than titanium) (72mm) (1)/ rod ends (2)/ aluminum 7mm wrench Threaded rods (20/25/44mm 1 ea.)/ (1) 12mm set screw  Suspension Linkage  Caster spacers (4)/ shims (4) Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer adjustment shims; 3.5mm (2), 1.17mm (2) Rod ends, Revo (large) with hollow balls (12) Rod ends, small, with hollow balls (6) (for Revo steering linkage) Screws, 3x15mm countersunk machine (6) (hex drive) Shoulder screws, Ultra Shocks (3x12 hex drive) (6) Suspension screw pin set, hardened steel (hex drive)
aluminum) (assembled with TiN shafts) w/o springs (rear) (2) Big Bore shocks (xx-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled) w/ red springs, TiN shafts (8 pack) Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushings & washers (2) (Big Bore Shocks) Rebuild kit, Ultra shocks (for 2 shocks) Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) Set (grub) screws, 3x25mm (8)/ 3mm nylon locknuts (8) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Silicone shock oil (30 wt) Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, red (for big bore shocks) (2.5 rate) (2)  Shocks (Ultra Shocks) Body, Ultra Shock(s) (XXL) (grey) (2)	3941 3941R 2537 5134 5355 5347 5349 2553 3642X 5161 5141A	retainer (requires 5x11mm BB (2)) Steering drag link (4x72mm turnbuckle) (1)/ rod ends (2)/ hollow ball (2) Steering drag link (Tubes red-anodized, 7075-T6 aluminum, stronger than titanium) (72mm) (1)/ rod ends (2)/ aluminum 7mm wrench Threaded rods (20/25/44mm 1 ea.)/ (1) 12mm set screw  Suspension Linkage  Caster spacers (4)/ shims (4) Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer adjustment shims; 3.5mm (2), 1.17mm (2) Rod ends, Revo (large) with hollow balls (12) Rod ends, small, with hollow balls (6) (for Revo steering linkage) Screws, 3x15mm countersunk machine (6) (hex drive) Shoulder screws, Ultra Shocks (3x12 hex drive) (6) Suspension screw pin set, hardened steel (hex drive) Toe links, Maxx (Tubes black-anodized, 7075-T6 aluminum, stronger than titanium) (112mm, front) (2)/ rod ends (4)/ aluminum wrench (1) (For Maxx models w/sealed pivot ball suspension & 3.8' wheels)
aluminum) (assembled with TiN shafts) w/o springs (rear) (2) Big Bore shocks (xx-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled) w/ red springs, TiN shafts (8 pack) Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushings & washers (2) (Big Bore Shocks) Rebuild kit, Ultra shocks (for 2 shocks) Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) Set (grub) screws, 3x25mm (8)/ 3mm nylon locknuts (8) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Silicone shock oil (30 wt) Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, red (for big bore shocks) (2.5 rate) (2)  Shocks (Ultra Shocks) Body, Ultra Shock(s) (XXL) (grey) (2) Rebuild kit, Ultra shocks (for 2 shocks)	3941 3941R 2537 5134 5355 5347 5349 2553 3642X 5161	retainer (requires 5x11mm BB (2)) Steering drag link (4x72mm turnbuckle) (1)/ rod ends (2)/ hollow ball (2) Steering drag link (Tubes red-anodized, 7075-T6 aluminum, stronger than titanium) (72mm) (1)/ rod ends (2)/ aluminum 7mm wrench Threaded rods (20/25/44mm 1 ea.)/ (1) 12mm set screw  Suspension Linkage  Caster spacers (4)/ shims (4) Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer adjustment shims; 3.5mm (2), 1.17mm (2) Rod ends, Revo (large) with hollow balls (12) Rod ends, small, with hollow balls (6) (for Revo steering linkage) Screws, 3x15mm countersunk machine (6) (hex drive) Shoulder screws, Ultra Shocks (3x12 hex drive) (6) Suspension screw pin set, hardened steel (hex drive) Toe links, Maxx (Tubes black-anodized, 7075-T6 aluminum, stronger than titanium) (112mm, front) (2)/ rod ends (4)/ aluminum wrench (1) (For Maxx models w/sealed pivot ball suspension & 3.8¹ wheels) Toe links, Maxx (Tubes black-anodized, 7075-T6 aluminum,
aluminum) (assembled with TiN shafts) w/o springs (rear) (2) Big Bore shocks (xx-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled) w/ red springs, TiN shafts (8 pack) Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushings & washers (2) (Big Bore Shocks) Rebuild kit, Ultra shocks (for 2 shocks) Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) Set (grub) screws, 3x25mm (8)/ 3mm nylon locknuts (8) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Silicone shock oil (30 wt) Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, red (for big bore shocks) (2.5 rate) (2)  Shocks (Ultra Shocks) Body, Ultra Shock(s) (XXL) (grey) (2)	3941 3941R 2537 5134 5355 5347 5349 2553 3642X 5161 5141A	retainer (requires 5x11mm BB (2)) Steering drag link (4x72mm turnbuckle) (1)/ rod ends (2)/ hollow ball (2) Steering drag link (Tubes red-anodized, 7075-T6 aluminum, stronger than titanium) (72mm) (1)/ rod ends (2)/ aluminum 7mr wrench Threaded rods (20/25/44mm 1 ea.)/ (1) 12mm set screw  Suspension Linkage  Caster spacers (4)/ shims (4) Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer adjustment shims; 3.5mm (2), 1.17mm (2) Rod ends, Revo (large) with hollow balls (12) Rod ends, small, with hollow balls (6) (for Revo steering linkage) Screws, 3x15mm countersunk machine (6) (hex drive) Shoulder screws, Ultra Shocks (3x12 hex drive) (6) Suspension screw pin set, hardened steel (hex drive) Toe links, Maxx (Tubes black-anodized, 7075-T6 aluminum, stronger than titanium) (112mm, front) (2)/ rod ends (4)/ aluminum wrench (1) (For Maxx models w/sealed pivot ball suspension & 3.8' wheels)
	Transmitter, TQi Traxxas Link enabled, 2.4GHz high output, 4-channel (transmitter only) Traxxas Link Wireless Module Wire retainers, gear cover/ 3x4mm BCS (2)  Ready-To-Race Model  E-Maxx Brushless: 1/10 Scale Brushless Electric Monster Truck with TQi 2.4GHz Traxxas Link Enabled Radio System and Traxxas Stability Management (TSM)  Rear Suspension  Aluminum caps, pivot ball (blue-anodized) (4) Axle carriers, left & right (1 each) (use with larger 6x13mm ball bearings) bearing adapters (for 6x12mm ball bearings) (2)/ dust boot retainers (4)  Ball bearings, blue rubber sealed (12x18x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) Bulkhead cross braces (2)/ 3x25mm CS screws (8) Bulkhead (ross braces (2)/ 3x25mm CS screws (8) Bulkheads (l & r) (rear) (grey) Bulkheads, rear (machined 6061-T6 aluminum) (blue)(l&r) (requires use of 4939X suspension pins) Caster spacers (4)/ shims (4) Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer adjustment shims; 3.5mm (2), 1.17mm (2) Pivot ball caps (4)/ dust boots, rubber (4)/ dust plugs, rubber (4)/ dust boot retainers, black (4), blue (4) (2 pkgs. req. to complete truck) Pivot balls (4)/ pivot ball cap bushings (4) Pivot balls, hard-anodized 7075-T6 aluminum (4)/ pivot ball cap bushings (4) Rod ends, Revo (large) with hollow balls (12) Rod ends, Revo (large) with hollow balls (12) Rod ends, Revo (large) with hollow balls (12) Screws, 3x15mm countersunk machine (6) (hex drive) Shock tower (for rectangular body posts) Suspension arms (upper) (2) (fits all Maxx series) Tie bar, rear (1) /3x18mm BCS (2) (fits all Maxx trucks) Toe links, Maxx (Tubes black-anodized, 7075-T6 aluminum, stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum wrench (1) (For Maxx models w/sealed pivot ball suspension & 3.8" wheels) Turnbuckles, toe links (5.0mm steel) (rear) (2)  Shocks (Pro-level Aluminum) Big Bore shock cylinder (XX-long) (1)	Transmitter, TQi Traxxas Link enabled, 2.4GHz high output, 3-channel (transmitter only)  Transmitter, TQi Traxxas Link enabled, 2.4GHz high output, 4-channel (transmitter only)  Traxxas Link Wireless Module  Wire retainers, gear cover/ 3x4mm BCS (2)  Fedaxy Brushless: 1/10 Scale Brushless Electric Monster Truck with TQi 2.4GHz Traxxas Link Enabled Radio System and Traxxas  Stability Management (TSM)  Rear Suspension  Aluminum caps, pivot ball (blue-anodized) (4)  Axle carriers, left & right (1 each) (use with larger 6x13mm ball bearings) (2)/ dust boot retainers, left & right (1 each) (use with larger 6x13mm ball bearings) bearing adapters (for 6x12mm ball bearings) (2)/ dust boot retainers, left & right (1 each) (use with larger 6x13mm ball bearings), blue rubber sealed (6x12x4mm) (2)  Ball bearings, blue rubber sealed (12x18x4mm) (2)  Ball bearings, blue rubber sealed (6x12x4mm) (2)  Ball bearings, blue rubber sealed (6x12x4mm) (2)  Ball bearings, blue rubber sealed (12x18x4mm) (2)  Sa52x  S

Page 4	E-Maxx Brushless: TQi Traxxas Link Enabled 2.40	Hz Rad	lio & TSM (Model 39086-4) Parts List
5141R	Toe links, Maxx (Tubes red-anodized, 7075-T6 aluminum, stronger than titanium) (112mm, front) (2)/ rod ends (4)/	5371	Wheels, dished 3.8" (white) (2) (use with 17mm splined wheel hubs and wheel nuts, part #5353X)
	aluminum wrench (1) (For Maxx models w/sealed pivot ball suspension & 3.8" wheels)	5372X	Wheels, Gemini 3.8" (black chrome) (2) (use with 17mm splined wheel hubs & nuts, part #5353X)
5143R	Toe links, Maxx (Tubes red-anodized, 7075-T6 aluminum,	5372	Wheels, Gemini 3.8" (chrome) (2) (also fits Maxx series)
	stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum wrench (1) (For Maxx models w/sealed pivot ball suspension & 2 ** whose)	5671	Wheels, Geode 3.8" (chrome) (2) (use with 17mm splined wheel hubs & nuts, part #5353X & beadlock-style sidewall protectors,
5141	3.8" wheels) Turnbuckles, toe links (5.0mm steel) (front) (2)	5373	part #5665, 5666, 5667) Wheels, Hurricane 3.8" (chrome) (2) (also fits Maxx series)
5143	Turnbuckles, toe links (5.0mm steel) (rear) (2)	5172A	Wheels, SS (split spoke) 3.8" (black chrome) (2) (use with 17mm
	Team Traxxas Items		splined wheel hubs & nuts, part #5353X) (fits Revo/Maxx series)
2514	Decal sheet, racing sponsors	5172X	Wheels, SS (split spoke) 3.8" (chrome) (2) (fits Revo/Maxx series)
6160X	DVD, Maxx Power! Full Throttle Action (sleeve)	5172R	Wheels, SS (split spoke) 3.8" (chrome) (2) (use with 17mm
9950	Official Team Traxxas racing decal set (flag logo/ 6-color)		splined wheel hubs & nuts, part #5353X) (fits Revo/Maxx series)
9909	Traxxas racing banner, red & black (3x7 feet)	5172	Wheels, SS (split spoke) 3.8" (satin) (2) (fits Revo/Maxx series)
E447	Tires & Wheels		Transmission Components
5117 <b>4147X</b>	Ball bearings, blue rubber sealed (6x12x4mm) (2)  Nuts, 5mm flanged nylon locking (aluminum, blue-anodized) (4)	5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)
5147X	Nuts, 5mm flanged nylon locking (steel, serrated) (8)	5117 5157	Ball bearings, blue rubber sealed (6x12x4mm) (2) Cover plates and seals, forward only conversion (Revo) (Optidrive
4955	Pins, axle (2.5x12mm) (4)	3137	blank-out plate, Optidrive sensor cover, shift fork cover)
5666	Sidewall protector, beadlock style (blue) (2)/ 2.5x8mm CS (24) (for use with Geode wheels)	3977R	Cover, gear (upper & lower) (1)/ dust plug (1)/ 3x6mm CS (3) (for
5664	Sidewall protector, beadlock style (green) (2)/ 2.5x8mm CS (24)	3973	single motor installation, use with motor plate #3997X)  Gear set, close ratio (1st speed gear 21T, 18T input gear)
	(for use with Geode wheels)	3974	Gear set, vide ratio (1st speed gear 26T, 13T input gear)
5667	Sidewall protector, beadlock style (red) (2)/ 2.5x8mm CS (24) (for use with Geode wheels)	3991X	Gearbox halves (front & rear)/ shift detent ball/ spring/ 4mm GS/ shift
5665	Sidewall protector, beadlock style (yellow) (2)/ 2.5x8mm CS (24)	2070	shaft seal, glued/ 2.5x8mm CS (2)
	(for use with Geode wheels)	<b>3976</b> 3996X	Idler gear, 13T (1st speed gear) Idler gear, 20-tooth/ idler gear shaft
5374X	Tires & wheels, assembled, glued (Gemini black chrome wheels,	3992	Input shaft/ drive gear assembly (18-tooth steel top gear)
	Talon tires, foam inserts) (2) (use with 17mm splined wheel hubs & nuts, part #5353X) (TSM rated)	3988X	Linkage, shift (includes: ball cup, servo horn with built-in spring,
5374	Tires & wheels, assembled, glued (Gemini chrome wheels, Talon	3984X	linkage wire, and hardware) Output gear, 33-tooth (1)/ spacers (2)
F074	tires, foam inserts) (2) (also fits Maxx series)	3985X	Output gears, 33T (2)/ drive dog carrier/ output shaft spacer
5674	Tires & wheels, assembled, glued (Geode chrome wheels, Maxx tires (6.3" outer diameter), foam inserts) (2) (use with 17mm	3969	Output shaft, transmission
	splined wheel hubs & nuts, part #5353X & beadlock-style	3965	Screws, 2.5x8mm cap-head machine (6)
EC70	sidewall protectors, part #5665, 5666, 5667)	2552 <b>3989X</b>	Screws, 3x12mm countersunk machine (6) (hex drive) Shift fork/ shaft
5672	Tires & wheels, assembled, glued (Geode chrome wheels, paddle tires, foam inserts) (2) (use with 17mm splined wheel	1647	Silicone grease
	hubs & nuts, part # 5353X) (TSM rated)	3998	Two Speed Conversion Kit (E-Maxx) (includes wide and close
4973R	Tires & wheels, assembled, glued (Hurricane chrome wheels, Maxx tires (6.3" outer diameter), foam inserts) (2) (fits Revo/Maxx		ratio first gear sets, sub-micro servo, and linkage)
	series)	50.45	Turnbuckles & Threaded Rods
5174A	Tires & wheels, assembled, glued (Split-Spoke satin-finish	5347 5349	Rod ends, Revo (large) with hollow balls (12) Rod ends, small, with hollow balls (6) (for Revo steering linkage)
	wheels, Talon tires, foam inserts) (2) (fits Maxx w/sealed pivot ball suspension & Revo)	3941	Steering drag link (4x72mm turnbuckle) (1)/ rod ends (2)/ hollow balls
4983A	Tires & wheels, assembled, glued (SS (Split Spoke) black chrome		(2)
	wheels, Maxx tires (6.3" outer diameter), foam inserts) (2) (fits	3941R	Steering drag link (Tubes red-anodized, 7075-T6 aluminum, stronger than titanium) (72mm) (1)/ rod ends (2)/ aluminum 7mm
5173	Maxx/Revo series) (TSM rated)  Tires & wheels, assembled, glued (SS (Split Spoke) chrome		wrench
••	wheels, Maxx tires, foam inserts) (2) (fits Maxx/Revo series)	2537	Threaded rods (20/25/44mm 1 ea.)/ (1) 12mm set screw
5174	Tires & wheels, assembled, glued (SS (Split Spoke) chrome	5141A	Toe links, Maxx (Tubes black-anodized, 7075-T6 aluminum, stronger than titanium) (112mm, front) (2)/ rod ends (4)/
5174R	wheels, Talon tires, foam inserts) (2) (fits Maxx/Revo series) Tires & wheels, assembled, glued (SS (Split Spoke) chrome		aluminum wrench (1) (For Maxx models w/sealed pivot ball
011-110	wheels, Talon tires, foam inserts) (2) (use w/17mm splined wheel		suspension & 3.8' wheels)
5075D	hubs & nuts, part #5353X)	5143A	Toe links, Maxx (Tubes black-anodized, 7075-T6 aluminum, stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum
5375R	Tires & wheels, assembled, glued (white dished 3.8" wheels, Response Pro tires, foam inserts) (2) (use with 17mm splined		wrench (1) (For Maxx models w/sealed pivot ball suspension &
	wheel hubs and wheel nuts, part #5353X)	E4.44 D	3.8' wheels)
5670	Tires, Canyon AT 3.8" (2)/ foam inserts (2)	5141R	Toe links, Maxx (Tubes red-anodized, 7075-T6 aluminum, stronger than titanium) (112mm, front) (2)/ rod ends (4)/
4973	Tires, Maxx 3.8" (6.3" outer diameter (160mm)) (2) (fits Revo/Maxx series)		aluminum wrench (1) (For Maxx models w/sealed pivot ball
5171	Tires, Maxx Chevron 3.8" (2) (fits Revo/Maxx series)	E1.12D	suspension & 3.8" wheels)
5375	Tires, Response Pro 3.8" (soft-compound, narrow profile, short	5143R	Toe links, Maxx (Tubes red-anodized, 7075-T6 aluminum, stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum
5471	knobby design)/ foam inserts (2) Tires, Response racing 3.8" (soft-compound, narrow profile,		wrench (1) (For Maxx models w/sealed pivot ball suspension &
	short knobby design)/ foam inserts (2)	5141	3.8" wheels) Turnbuckles, toe links (5.0mm steel) (front) (2)
5470	Tires, SportTraxx racing 3.8" (soft compound, directional and	5143	Turnbuckles, toe links (5.0mm steel) (rear) (2)
5370	asymmetrical tread design)/ foam inserts (2) Tires, Talon 3.8" (2)/ foam inserts (2)		
4954R	Wheel hubs, hex (steel)		
4954X	Wheel hubs, hex, 6061-T6 aluminum (blue) (4)/ axle pins		
5353X	(2.5x10mm) (4) Wheel hubs, splined, 17mm (blue-anodized) (4)/ wheel nuts, splined,		If you have questions or need technical assistance, call Traxxas at:
3333X	17mm (blue-anodized) (4)/ screw pins, 4x13mm (with threadlock) (4)		1-888-TRAXXAS
5353G	Wheel hubs, splined, 17mm (green-anodized) (4)/ wheel nuts,		(1-888-872-9927) (U.S. residents only)
	splined, 17mm (blue-anodized) (4)/ screw pins, 4x13mm (with threadlock) (4)		For orders, calls outside the U.S., and other information, call 972-549-3000,
5353R	Wheel hubs, splined, 17mm (red-anodized) (4)/ wheel nuts,		or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com
	splined, 17mm (red-anodized) (4)/ screw pins, 4x13mm (with		TRAXXAS.COM
5353	threadlock) (4) Wheel nuts, splined, 17mm (blue-anodized) (4)		
5353A	Wheel nuts, splined, 17mm (green-anodized) (4)		
	-		