

Slash 4X4 Platinum (Model 6804R) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

	Bearings & Bushings	3932 1647	Screws, 3x6mm flat-head machine (hex drive) (6)
4607	Ball bearings (5x11x4mm) (8)	1647 6878	Silicone grease Slipper clutch, complete
4612	Ball bearings (10x15x4mm) (2)	5556	Slipper crutori, complete Slipper pressure plate & hub (aluminum alloy)
2728	Ball bearings (5x8x2.5mm) (2)	5351	Slipper pressure plate and hub (alloy)
5119A	Ball bearings, black rubber sealed (10x15x4mm) (2)		Chassis & Attachments
5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)		
5120	Ball bearings, blue rubber sealed (12x18x4mm) (2)	7426	Battery hold-down (1)/ hold-down retainer, front & rear (1 each)
5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)	7426X	Battery hold-downs, tall (2) (allows for installation of taller, multi
5114	Ball bearings, blue rubber sealed (5x8x2.5mm) (2)	601ED	cell batteries)
5117 5118	Ball bearings, blue rubber sealed (6x12x4mm) (2) Ball bearings, blue rubber sealed (8x16x5mm) (2)	6815R	Body mount (1)/ body mount post (2)/ body post extensions (2) (front or rear)
1985	PTFE-coated washers, 5x8x0.5mm (20) (use with ball bearings)	7424	Box, receiver (sealed)/ foam pads/ 2.5x12mm CS (2)/ 3x6mm CS (2)/
1905			3x12mm BCS (2)
	Body & Accessories	6835	Bumper, front/ bumper mount, front (black)
1926	Antenna caps, vinyl (2)/ antenna spool	6836	Bumper, rear/ bumper mount, rear (black)
1726	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)	7422	Chassis
3935	Body clip (mounting clip), angled, 90-degrees (10)	6730X	Chassis brace kit, blue (fits Rustler® 4X4 or Slash 4X4 models
3935A	Body clip (mounting clip), angled, 90-degrees (black) (10)	67000	equipped with Low-CG chassis)
3934 6815R	Body clips, heavy duty (12) Body mount (1)/ body mount post (2)/ body post extensions (2) (front	6730G	Chassis brace kit, green (fits Rustler® 4X4 or Slash 4X4 models equipped with Low-CG chassis)
1815	or rear) Body washers (8)	6730A	Chassis brace kit, orange (fits Rustler® 4X4 or Slash 4X4 models equipped with Low-CG chassis)
6716	Body washers, foam, 2mm (2)/ 3mm (2)/ 4mm (4)	6730R	Chassis brace kit, red (fits Rustler® 4X4 or Slash 4X4 models
6811	Body, Slash 4X4 (clear, requires painting)/ window masks/ decal	7400	equipped with Low-CG chassis)
E040	sheet	7423	Nerf bars, chassis (2)
5849	Body, Slash 4X4, Hawaiian graphics (painted, decals applied)	7425	Seal kit, receiver box (includes o-ring, seals, and silicone grease)
6811R	Body, Slash 4X4, heavy duty (clear, untrimmed, requires painting)/ window masks/ decal sheet	7437	Skidplate, front
5824	Body, Slash 4X4, Keegan Kincaid (painted, decals applied)		Differential Components
5850	Body, Slash 4X4, orange (painted, decals applied)	5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)
5812	Body, Slash 4X4, ProGraphix® (Graphics are printed, requires	5117	Ball bearings, blue rubber sealed (6x12x4mm) (2)
	paint & final color application)/ decal sheet	5118	Ball bearings, blue rubber sealed (8x16x5mm) (2)
5824R	Body, Slash 4X4, red (painted, decals applied)	5381	Carrier, differential/x-ring gaskets (2)/ ring gear gasket/ 6x10x0.5 TW
5848	Body, Slash 4X4, Rock n' Roll (painted, decals applied)	6780	Differential kit, center (complete)
6849	Body, Slash 4X4/Slash, Fox Edition (painted, decals applied)	6814	Differential kit, center (complete)
2514	Decal sheet, racing sponsors	5136X	Differential oil kit (1 each: 10K, 30K, 50K weights)
6813	Decal sheet, Slash 4X4	6783	Gear set, center differential (output gears (2)/ spider gears (4)/ spider gear shaft (2))
9950	Official Team Traxxas® racing decal set (flag logo/ 6-color)	6882X	Gear set, differential (output gears (2)/ spider gears (2)/ spider gear
	Center Driveline	0002X	shaft, carrier support)
5119A	Ball bearings, black rubber sealed (10x15x4mm) (2)	6781	Housing, center differential (aluminum)/ x-ring gaskets (2)/ ring
5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)		gear gasket/ bushings (2)/ 5x10x0.5mm PTFE-coated washers
5120	Ball bearings, blue rubber sealed (12x18x4mm) (2)		(2)/ 2.5x8 CCS (4)
5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)	6881	Housings, differential, front
5117	Ball bearings, blue rubber sealed (6x12x4mm) (2)	6880	Housings, differential, rear
6893G	Bearing adapter, 6061-T6 aluminum (green-anodized) (1)/	6782	Output gears, center differential, hardened steel (2)
	10x15x4mm ball bearing (black rubber sealed) (1) (for slipper	5379X	Ring gear, differential/ pinion gear, differential
6893X	shaft)	5379R	Ring gear, differential/ pinion gear, differential (machined, spiral cut) (front)
00337	Bearing adapter, 6160-T6 aluminum (blue-anodized) (1)/10x15x4mm ball bearing (blue rubber sealed) (1) (for slipper	6879R	Ring gear, differential/ pinion gear, differential (machined, spiral
7477	shaft)	6870	cut) (rear) Ring gear, differential/ pinion gear, differential (rear)
6814	Cover, gear/ wire retainer Differential kit, center (complete)	6879 3965	Screws, 2.5x8mm cap-head machine (6)
6888	Drive hub, center, rear (1)/ 4x3 GS (1)	1647	Silicone grease
6888X	Drive hub, front, hardened steel (1)/ screw pin (1)		ů
6883	Gear set, center differential (output gears (2)/ spider gears (2)/		Driveline Components
	spider gear shaft)	6455	Axle carriers, rear, 6061-T6 aluminum, left & right (blue-
5148	Grease, white lithium		anodized) (compatible only when installing #6451 & #6452 steel constant-velocity driveshafts)
	Housing, center differential/ x-ring gaskets (2)/ ring gear gasket/	51104	•
6884		5119A	Ball bearings, black rubber sealed (10x15x4mm) (2)
6884 6893	Housing, center differential/ x-ring gaskets (2)/ ring gear gasket/ bushings (2)/ 5x10x0.5 TW (2)/ CCS 2.5x8 (4) Input shaft (slipper shaft)/ bearing adapter (1)/pin (1)	5119	Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2)
6884 6893	Housing, center differential/ x-ring gaskets (2)/ ring gear gasket/ bushings (2)/ 5x10x0.5 TW (2)/ CCS 2.5x8 (4) Input shaft (slipper shaft)/ bearing adapter (1)/pin (1) Motor mount (assembled with 3x6 flat-head machine screw)/	5119 5116	Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2)
6884 6893 7460A	Housing, center differential/ x-ring gaskets (2)/ ring gear gasket/ bushings (2)/ 5x10x0.5 TW (2)/ CCS 2.5x8 (4) Input shaft (slipper shaft)/ bearing adapter (1)/pin (1) Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1)	5119	Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) (compatible
6884 6893 7460A 7460R	Housing, center differential/ x-ring gaskets (2)/ ring gear gasket/ bushings (2)/ 5x10x0.5 TW (2)/ CCS 2.5x8 (4) Input shaft (slipper shaft)/ bearing adapter (1)/pin (1) Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1) Motor mount, 6061-T6 aluminum (blue-anodized)	5119 5116	Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2)
6884 6893 7460A 7460R 7490	Housing, center differential/ x-ring gaskets (2)/ ring gear gasket/ bushings (2)/ 5x10x0.5 TW (2)/ CCS 2.5x8 (4) Input shaft (slipper shaft)/ bearing adapter (1)/pin (1) Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1) Motor mount, 6061-T6 aluminum (blue-anodized) Plate, motor	5119 5116	Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) (compatible only when installing #6451 & #6452 steel constant-velocity
6884 6893 7460A 7460R 7490 7490G	Housing, center differential/ x-ring gaskets (2)/ ring gear gasket/ bushings (2)/ 5x10x0.5 TW (2)/ CCS 2.5x8 (4) Input shaft (slipper shaft)/ bearing adapter (1)/pin (1) Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1) Motor mount, 6061-T6 aluminum (blue-anodized) Plate, motor Plate, motor, green	5119 5116 5117 6758	Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) (compatible only when installing #6451 & #6452 steel constant-velocity driveshafts) Differential output shaft (for steel constant-velocity driveshafts) (2)
6884 6893 7460A 7460R 7490 7490G 7490A	Housing, center differential/ x-ring gaskets (2)/ ring gear gasket/ bushings (2)/ 5x10x0.5 TW (2)/ CCS 2.5x8 (4) Input shaft (slipper shaft)/ bearing adapter (1)/pin (1) Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1) Motor mount, 6061-T6 aluminum (blue-anodized) Plate, motor Plate, motor, green Plate, motor, orange	5119 5116 5117	Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) (compatible only when installing #6451 & #6452 steel constant-velocity driveshafts) Differential output shaft (for steel constant-velocity driveshafts) (2) Differential output yoke assembly, extreme heavy duty (2) (left or
6884 6893 7460A 7460R 7490 7490G 7490A 7490R	Housing, center differential/ x-ring gaskets (2)/ ring gear gasket/ bushings (2)/ 5x10x0.5 TW (2)/ CCS 2.5x8 (4) Input shaft (slipper shaft)/ bearing adapter (1)/pin (1) Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1) Motor mount, 6061-T6 aluminum (blue-anodized) Plate, motor Plate, motor, green Plate, motor, orange Plate, motor, red	5119 5116 5117 6758 6828A	Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) (compatible only when installing #6451 & #6452 steel constant-velocity driveshafts) Differential output shaft (for steel constant-velocity driveshafts) (2) Differential output yoke assembly, extreme heavy duty (2) (left or right, front or rear) (assembled with external-splined half shaft)
6884 6893 7460A 7460R 7490 7490G 7490A	Housing, center differential/ x-ring gaskets (2)/ ring gear gasket/ bushings (2)/ 5x10x0.5 TW (2)/ CCS 2.5x8 (4) Input shaft (slipper shaft)/ bearing adapter (1)/pin (1) Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1) Motor mount, 6061-T6 aluminum (blue-anodized) Plate, motor Plate, motor, green Plate, motor, orange	5119 5116 5117 6758 6828A 6828X	Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) (compatible only when installing #6451 & #6452 steel constant-velocity driveshafts) Differential output shaft (for steel constant-velocity driveshafts) (2) Differential output yoke assembly, extreme heavy duty (2) (left or right, front or rear) (assembled with external-splined half shaft) Differential output yokes, heavy duty (2)/ screw pin (2)
6884 6893 7460A 7460R 7490 7490G 7490A 7490R	Housing, center differential/ x-ring gaskets (2)/ ring gear gasket/ bushings (2)/ 5x10x0.5 TW (2)/ CCS 2.5x8 (4) Input shaft (slipper shaft)/ bearing adapter (1)/pin (1) Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1) Motor mount, 6061-T6 aluminum (blue-anodized) Plate, motor Plate, motor, green Plate, motor, orange Plate, motor, red Rebuild kit (heavy duty), slipper clutch (steel disc/ aluminum	5119 5116 5117 6758 6828A	Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) (compatible only when installing #6451 & #6452 steel constant-velocity driveshafts) Differential output shaft (for steel constant-velocity driveshafts) (2) Differential output yoke assembly, extreme heavy duty (2) (left or right, front or rear) (assembled with external-splined half shaft) Differential output yokes, heavy duty (2)/ screw pin (2) Driveshaft assembly, front, heavy duty (1) (left or right) (fully
6884 6893 7460A 7460R 7490 7490G 7490A 7490R	Housing, center differential/ x-ring gaskets (2)/ ring gear gasket/ bushings (2)/ 5x10x0.5 TW (2)/ CCS 2.5x8 (4) Input shaft (slipper shaft)/ bearing adapter (1)/pin (1) Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1) Motor mount, 6061-T6 aluminum (blue-anodized) Plate, motor Plate, motor, green Plate, motor, orange Plate, motor, red Rebuild kit (heavy duty), slipper clutch (steel disc/ aluminum friction pads (3)/ spring (1)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL	5119 5116 5117 6758 6828A 6828X 6851X	Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) (compatible only when installing #6451 & #6452 steel constant-velocity driveshafts) Differential output shaft (for steel constant-velocity driveshafts) (2) Differential output yoke assembly, extreme heavy duty (2) (left or right, front or rear) (assembled with external-splined half shaft) Differential output yokes, heavy duty (2)/ screw pin (2) Driveshaft assembly, front, heavy duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1)
6884 6893 7460A 7460R 7490 7490G 7490A 7490R 5352R	Housing, center differential/ x-ring gaskets (2)/ ring gear gasket/ bushings (2)/ 5x10x0.5 TW (2)/ CCS 2.5x8 (4) Input shaft (slipper shaft)/ bearing adapter (1)/pin (1) Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1) Motor mount, 6061-T6 aluminum (blue-anodized) Plate, motor Plate, motor, green Plate, motor, orange Plate, motor, red Rebuild kit (heavy duty), slipper clutch (steel disc/ aluminum friction pads (3)/ spring (1)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1)) Rebuild kit, slipper clutch (steel disc/ friction pads (3)/ spring (2)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1))	5119 5116 5117 6758 6828A 6828X	Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) (compatible only when installing #6451 & #6452 steel constant-velocity driveshafts) Differential output shaft (for steel constant-velocity driveshafts) (2) Differential output yoke assembly, extreme heavy duty (2) (left or right, front or rear) (assembled with external-splined half shaft) Differential output yokes, heavy duty (2)/ screw pin (2) Driveshaft assembly, front, heavy duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft assembly, rear, heavy duty (1) (left or right) (fully
6884 6893 7460A 7460R 7490 7490G 7490A 7490R 5352R	Housing, center differential/ x-ring gaskets (2)/ ring gear gasket/ bushings (2)/ 5x10x0.5 TW (2)/ CCS 2.5x8 (4) Input shaft (slipper shaft)/ bearing adapter (1)/pin (1) Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1) Motor mount, 6061-T6 aluminum (blue-anodized) Plate, motor Plate, motor, green Plate, motor, orange Plate, motor, red Rebuild kit (heavy duty), slipper clutch (steel disc/ aluminum friction pads (3)/ spring (1)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1)) Rebuild kit, slipper clutch (steel disc/ friction pads (3)/ spring (2)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1)) Rebuild kit, slipper clutch (steel disc/ friction pads (3)/ spring (2)/ pin/	5119 5116 5117 6758 6828A 6828X 6851X 6852X	Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) (compatible only when installing #6451 & #6452 steel constant-velocity driveshafts) Differential output shaft (for steel constant-velocity driveshafts) (2) Differential output yoke assembly, extreme heavy duty (2) (left or right, front or rear) (assembled with external-splined half shaft) Differential output yokes, heavy duty (2)/ screw pin (2) Driveshaft assembly, front, heavy duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft assembly, rear, heavy duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1)
6884 6893 7460A 7460R 7490 7490G 7490A 7490R 5352R	Housing, center differential/ x-ring gaskets (2)/ ring gear gasket/ bushings (2)/ 5x10x0.5 TW (2)/ CCS 2.5x8 (4) Input shaft (slipper shaft)/ bearing adapter (1)/pin (1) Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm NL (1) Motor mount, 6061-T6 aluminum (blue-anodized) Plate, motor Plate, motor, green Plate, motor, orange Plate, motor, red Rebuild kit (heavy duty), slipper clutch (steel disc/ aluminum friction pads (3)/ spring (1)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1)) Rebuild kit, slipper clutch (steel disc/ friction pads (3)/ spring (2)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1))	5119 5116 5117 6758 6828A 6828X 6851X	Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2) (compatible only when installing #6451 & #6452 steel constant-velocity driveshafts) Differential output shaft (for steel constant-velocity driveshafts) (2) Differential output yoke assembly, extreme heavy duty (2) (left or right, front or rear) (assembled with external-splined half shaft) Differential output yokes, heavy duty (2)/ screw pin (2) Driveshaft assembly, front, heavy duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) Driveshaft assembly, rear, heavy duty (1) (left or right) (fully

Page 2 Slash 4X4 Platinum: Low CG-Chassis (Model 6804R) Parts List

Page 2	Slash 4X4 Platinum: Low CG-Chassis (Model 6804	R) Parts	List
6451	Driveshaft, front (6mm axle) (steel-spline constant-velocity) (complete assembly) (1) (also required for installation #6869,	3655R 3655G	Suspension arms, front/rear (left & right), heavy duty (2) Suspension arms, green, front/rear (left & right), heavy duty (2)
6452	#6452 (x2), #6439, #6455, #5117 (x3)) Driveshaft, rear (6mm axle) (steel-spline constant-velocity)	3655X	Suspension arms, left & right
0432	(complete assembly) (1) (also required for installation #6869, #6451 (x2), #6439, #6455, #5117 (x3))	3655T 3655L 3655A	Suspension arms, orange, front/rear (left & right), heavy duty (2) Suspension arms, red, front/rear (left & right), heavy duty (2)
6851R	Driveshafts, front, steel-spline constant-velocity (complete	6834	Suspension arms, white, front/rear (left & right), heavy duty (2) Suspension pin set, complete (front and rear)
6852R	assembly) (2) Driveshafts, rear, steel-spline constant-velocity (complete	6898	Sway bar kit (front and rear) (includes front and rear sway bars and adjustable linkage)
6750	assembly) (2)	6742X	Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger
6750 6751	Half shaft, external splined (steel-spline constant-velocity) (1) Half shaft, internal splined (steel-spline constant-velocity) (1)	67400	than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1)
6850X	Half shafts, heavy duty (external splined (2)/ internal splined (2))/	6742G	Toe links (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1)
6757	metal u-joints (4)	6742R	Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger
6757	Rebuild kit, steel-splined constant-velocity driveshafts (includes pins, dustboots, lube, and hardware)	2642	than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1)
6439	Steering blocks, 6061-T6 aluminum, left & right (blue-anodized) (compatible only when installing #6451 & #6452 steel constant-	3643 5539	Turnbuckles, camber link, 49mm (82mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) Turnbuckles, camber links, 58mm (assembled with rod ends and
6854A	velocity driveshafts) Stub axle assembly, front, outer, extreme heavy duty (1) (left or	6896	hollow balls) (2) Wires, sway bar (front & rear, hard & soft) / 3x6 FCS (4)
6853A	right) (assembled with internal-splined half shaft) Stub axle assembly, rear, outer, extreme heavy duty (1) (left or		Hardware
	right) (assembled with internal-splined half shaft)	1926	Antenna caps, vinyl (2)/ antenna spool
6754	Stub axle, front, 5mm (steel-splined constant-velocity	1726	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)
6753	driveshaft) (1) Stub axle, rear, 5mm (steel-splined constant-velocity driveshaft)	1552	Screws, 3x8mm cap-head machine (hex drive) (6)/washers (6)/ wrench
6854X	(1) Stub axion front hoovy duty (2)/ volces (2)/ pine (4)	3935	Body clip (mounting clip), angled, 90-degrees (10)
6853X	Stub axles, front, heavy duty (2)/ yokes (2)/ pins (4) Stub axles, rear, heavy duty (2)/pins (2)	3935A 3934	Body clip (mounting clip), angled, 90-degrees (black) (10) Body clips, heavy duty (12)
6869	Wheel adaptors, 12mm hex, 6061-T6 aluminum (blue-anodized)	1589	Double-sided adhesive tape (25mm x 25mm) (2)
	(4)/ screw pins (4)/ drill bit, 0.25 inch (for 6mm shafts) (requires #6451 (x2), #6452 (x2), #6439, #6455, #5117 (x3))	2586	Screws, 3x15mm cap-head machine (hex drive) (6)
	Front Suspension & Steering	2745 3647	Nuts, 3mm nylon locking (12) Nuts, 4mm flanged nylon locking (steel, serrated) (8)
2728	Ball bearings (5x8x2.5mm) (2)	1747	Nuts, 4mm nylon locking (10)
5114	Ball bearings, blue rubber sealed (5x8x2.5mm) (2)	1747A	Nuts, aluminum, flanged, serrated (4mm) (red-anodized) (4)
6823	Bulkhead tie bars, front & rear, aluminum (blue-anodized)	1985 5525	PTFE-coated washers, 5x8x0.5mm (20) (use with ball bearings) Rod ends (12)/ hollow balls (12)
6823G 6823R	Bulkhead tie bars, front & rear, aluminum (green-anodized) Bulkhead tie bars, front & rear, aluminum (red-anodized)	2742X	Rod ends, short (6)/ hollow balls (6)
7430X	Bulkhead, front	3347	Screws, 2.5x5mm button-head machine (hex drive) (6)
3643X	Camber links, front (TUBES blue-anodized, 7075-T6 aluminum,	3215 3965	Screws, 2.5x6mm cap-head machine (hex drive) (6) Screws, 2.5x8mm cap-head machine (6)
	stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)	2577	Screws, 3x10mm button-head machine (b)
3643G	Camber links, front (TUBES green-anodized, 7075-T6 aluminum,	2578	Screws, 3x12mm button-head machine (hex drive) (6)
	stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)	2552 2579	Screws, 3x12mm countersunk machine (6) (hex drive) Screws, 3x15mm button-head machine (hex drive) (6)
3643R	Camber links, front (TUBES red-anodized, 7075-T6 aluminum,	3646	Screws, 3x15mm flat-head machine (hex drive) (6)
	stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)	2583	Screws, 3x18mm button-head machine (hex drive) (6)
6832X	Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left &	2580 2591	Screws, 3x20mm button-head machine (hex drive) (6) Screws, 3x23mm button-head machine (hex drive) (6)
	right	2582	Screws, 3x30mm button-head machine (hex drive) (6)
6832G	Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right	2592	Screws, 3x40mm button-head machine (hex drive) (6)
6832A	Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized),	2575 2534	Screws, 3x6mm button-head machine (hex drive) (6) Screws, 3x6mm countersunk machine (6) (hex drive)
6832R	left & right Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left &	3932	Screws, 3x6mm flat-head machine (hex drive) (6)
000211	right	2576 3931	Screws, 3x8mm button-head machine (hex drive) (6)
6832	Caster blocks (c-hubs), left & right	3936	Screws, 3x8mm flat-head machine (hex drive) (6) Screws, 4x10mm button-head machine (hex drive) (6)
6845A 6845G	Drag link, machined 6061-T6 aluminum (blue-anodized) Drag link, machined 6061-T6 aluminum (green-anodized)	3937	Screws, 4x12mm button-head machine (hex drive) (6)
6845T	Drag link, machined 6061-T6 aluminum (groon anodized)	2542	Screws, 4x12mm countersunk machine (hex drive) (6)
6845R	Drag link, machined 6061-T6 aluminum (red-anodized)	3938 2546	Screws, 4x14mm button-head machine (hex drive) (6) Screws, 4x15mm countersunk machine (hex drive) (6)
6895	Linkage, front sway bar (2) (assembled with rod ends, hollow balls and ball studs)	2743	Set (grub) screws, 3mm hardened (12)
6897	Linkage, rear sway bar (2) (assembled with rod ends, hollow balls	3642X 2754	Shoulder screws, Ultra Shocks (3x12 hex drive) (6) Stub axle pins (4)
7438	and ball studs) Linkage, steering	2748X	Tool Set (1.5mm &2.5mm allens/ 4-way lug, 8mm &4mm wrench & U-
3646	Screws, 3x15mm flat-head machine (hex drive) (6)	2746	joint wrenches) Washers, 3x6mm metal (12)
6839 6839X	Shock tower, front Shock tower, front, 7075-T6 aluminum (blue-anodized)	27 10	Motors & Electronics
6845X	Steering bellcranks/ servo saver/ servo saver spring/ servo spring	1726	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)
000714	retainer/servo horn, steering	2260	BEC assembly (complete)
6837X 6837G	Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right	3340	Cooling fan, Velineon® VXL-3s ESC
6837A	Steering blocks, 6061-T6 aluminum (green-unodized), left & Hght	2072A 2252	Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos)
60075	right	7460A	Motor mount (assembled with 3x6 flat-head machine screw)/
6837R 6837	Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right	74600	3.0mm NL (1) Motor mount, 6061 T6 aluminum (blue anodized)
6854A	Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft)	7460R 3351R	Motor mount, 6061-T6 aluminum (blue-anodized) Motor, Velineon® 3500, brushless (assembled with 12-gauge wire
6754	Stub axle, front, 5mm (steel-splined constant-velocity driveshaft) (1)	7490	and gold-plated bullet connectors) Plate, motor
6854X	Stub axles, front, heavy duty (2)/ yokes (2)/ pins (4)	7490G 7490A	Plate, motor, green
3655P	Suspension arms, blue, front/rear (left & right), heavy duty (2)	149UA	Plate, motor, orange

Page 3	Slash 4X4 Platinum: Low CG-Chassis (Model 6804	R) Parts	List
7490R 3352R	Plate, motor, red Rebuild kit, Velineon® 3500 (includes plastic endbell, 5x11x4mm ball	6553X 6550X	Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (for use only with
3347	bearings (2), 2.5x5mm BCS (with threadlock) (4), rear bushing) Screws, 2.5x5mm button-head machine (hex drive) (6)	6551X	#6551X GPS module) Telemetry GPS module 2.0, TQi radio system (for use only with
3932 2254	Screws, 3x6mm flat-head machine (hex drive) (6) Servo case, aluminum (blue-anodized) (middle) (for 2250 servo)	6539	#6550X telemetry expander) Telemetry trigger magnet holder, center differential/ magnet,
2253	Servo case, aluminum (red-anodized) (middle) (for 2255 servo)		5x2mm (1)/ 3x8mm BCS (3)
2251	Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for	6540	Telemetry trigger magnet, 5X2mm (1)
0074	2250, 2255 servos)	6509R	TQi 2.4 GHz High Output radio system, 2-channel, Traxxas
2074 2075R	Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo, digital high-speed, metal gear (ball bearing), waterproof	6507R	Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas
2075K	Servo, digital high-torque (ball bearing), waterproof	000711	Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro
2250	Servo, digital high-torque 330 coreless, metal gear (ball bearing), waterproof	6528	receiver) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2-
2255	Servo, digital high-torque 400 brushless, metal gear (ball bearing), waterproof	6529	channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3-
2075X	Servo, digital high-torque, metal gear (ball bearing), waterproof	CESO	channel (transmitter only)
3350R	Velineon® VXL-3s Brushless Power System, waterproof (includes	6530	Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4- channel (transmitter only)
	VXL-3s waterproof ESC, Velineon 3500 motor, and speed control mounting plate (part #3725R))	3355R	Velineon® VXL-3s Electronic Speed Control, waterproof (brushless)
3355R	Velineon® VXL-3s Electronic Speed Control, waterproof (brushless)		(fwd/rev/brake)
	(fwd/rev/brake)		Ready-To-Race Model
2872X	Radio System, Batteries & Chargers 5000mAh 11.1v 3-Cell 25C LiPo Battery	6804R	Slash 4X4 Platinum: 1/10 Scale 4WD Electric Short Course Truck with Low CG chassis
2857X	6400mAh 11.1v 3-Cell 25C LiPo Battery		Rear Suspension
2869X	7600mAh 7.4v 2-Cell 25C LiPo Battery	6823	Bulkhead tie bars, front & rear, aluminum (blue-anodized)
2976	AC to DC converter, 40W	6823G	Bulkhead tie bars, front & rear, aluminum (green-anodized)
2938X	Adapter, Traxxas® iD® LiPo battery (adapts Traxxas iD batteries to separate balance ports)	6823R	Bulkhead tie bars, front & rear, aluminum (red-anodized)
2943	Battery charge indicators (green (4), blue (4), grey (4))	7429	Bulkhead, rear
6548	Battery door, transmitter (replacement for #6516, 6517, 6528, 6529, 6530 transmitters)	3644X	Camber links, rear (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
2914	Battery, Power Cell AA Alkaline (4)	3644G	Camber links, rear (TUBES green-anodized 7075-T6 aluminum,
2922X	Battery, Power Cell, 3000mAh (NiMH, 6-C flat, 7.2V)		stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum
2923X	Battery, Power Cell, 3000mAh (NiMH, 7-C flat, 8.4V)		wrench (1) (#2579 3x15 BCS (4) required for installation)
2942X 2940X	Battery, Series 3 Power Cell, 3300mAh (NiMH, 6-C flat, 7.2V) Battery, Series 3 Power Cell, 3300mAh (NiMH, 7-C flat, 8.4V)	3644R	Camber links, rear (TUBES red-anodized, 7075-T6 aluminum,
2952X	Battery, Series 4 Power Cell, 4200mAh (NiMH, 6-C flat, 7.2V)		stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
2950X	Battery, Series 4 Power Cell, 4200mAh (NiMH, 7-C flat, 8.4V)	1952X	Carriers, stub axle (blue-anodized 6061-T6 aluminum) (rear) (2)
2960X	Battery, Series 5 Power Cell, 5000mAh (NiMH, 7-C flat, 8.4V)	1952G	Carriers, stub axle (green-anodized 6061-T6 aluminum) (rear) (2)
2260	BEC assembly (complete)	1952	Carriers, stub axle (rear) (2)
2972	Charger, EZ-Peak® Dual, 100W, NiMH/LiPo with iD® Auto Battery Identification	1952A 6895	Carriers, stub axle (red-anodized 6061-T6 aluminum) (rear) (2) Linkage, front sway bar (2) (assembled with rod ends, hollow balls
2973	Charger, EZ-Peak® Live Dual, 200W, NiMH/LiPo with iD® Auto Battery Identification	6897	and ball studs) Linkage, rear sway bar (2) (assembled with rod ends, hollow balls
2971	Charger, EZ-Peak® Live, 100W, NiMH/LiPo with iD® Auto Battery Identification	6838	and ball studs) Shock tower, rear
2970	Charger, EZ-Peak® Plus, 4 amp, NiMH/LiPo with iD® Auto	6838X	Shock tower, rear, 7075-T6 aluminum (blue-anodized)
6525	Battery Identification Communication link, telemetry expander	6853A	Stub axle assembly, rear, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft)
6541	Connector, power tap (with cable) (long)/ wire tie	6853X	Stub axles, rear, heavy duty (2)/pins (2)
2072A 2252	Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos)	3655P 3655R	Suspension arms, blue, front/rear (left & right), heavy duty (2) Suspension arms, front/rear (left & right), heavy duty (2)
2968X	LiPo cell voltage checker/balancer (includes #2938X adapter for	3655G	Suspension arms, green, front/rear (left & right), heavy duty (2)
	Traxxas® iD® batteries)	3655X	Suspension arms, left & right
2968	LiPo cell voltage checker/balancer (requires #2938X adapter for	3655T	Suspension arms, orange, front/rear (left & right), heavy duty (2)
6555	Traxxas® iD® batteries) Mount, telemetry expander (fits Slash 4X4, Stampede® 4X4,	3655L 3655A	Suspension arms, red, front/rear (left & right), heavy duty (2) Suspension arms, white, front/rear (left & right), heavy duty (2)
6535	Rally, Jato®) Mount, temperature sensor (electric motors)/ wire tie/ thermal	6834 6898	Suspension pin set, complete (front and rear) Sway bar kit (front and rear) (includes front and rear sway bars and
6533	pad Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel)	2644	adjustable linkage)
6518	Receiver, micro, TQi 2.4GHz with telemetry (5-channel)	3644	Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on
3932	Screws, 3x6mm flat-head machine (hex drive) (6)		Slash, rear on Slash 4X4)
6552	Seal kit, expander box (includes o-ring, seals, and silicone	6896	Wires, sway bar (front & rear, hard & soft) / 3x6 FCS (4)
GEOG	grease)		Shocks (GTR)
6526 6527	Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage	7466X	Body, GTR long (hard-anodized, PTFE-coated aluminum) (1)
6520	Sensor, RPM (long)/ 3x4mm BCS (2)/ 3x4 GS (1)	7466G	Body, GTR long shock, aluminum (green-anodized) (PTFE-
6521	Sensor, temperature and voltage (long)		coated bodies) (1)
2254	Servo case, aluminum (blue-anodized) (middle) (for 2250 servo)	7466A	Body, GTR long shock, aluminum (orange-anodized) (PTFE-
2253	Servo case, aluminum (red-anodized) (middle) (for 2255 servo)	7467X	coated bodies) (1) Body, GTR xx-long (hard-anodized, PTFE-coated aluminum) (1)
2251	Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos)	7467G	Body, GTR xx-long (hard-anodized, FTT E-coated aidminidin) (T) Body, GTR xx-long shock, aluminum (green-anodized) (PTFE-
2074	Servo case/gaskets (for 2056 and 2075 waterproof servos)		coated bodies) (1)
2075R	Servo, digital high-speed, metal gear (ball bearing), waterproof	7467A	Body, GTR xx-long shock, aluminum (orange-anodized) (PTFE-
2075	Company digital binds to make the latest and the control of the co		coated bodies) (1)

coated bodies) (1)

Multi-tool (plastic)

Nuts, 2.5mm nylon locking (12)

7468

5475

5158

Caps and spring retainers, GTR long/xx-long shock (upper cap (2)/ hollow balls (4)/ bottom cap (2)/ upper retainer (2)/ lower retainer (2))

Servo, digital high-torque (ball bearing), waterproof

Servo, digital high-torque 400 brushless, metal gear (ball

Servo, digital high-torque 330 coreless, metal gear (ball bearing),

Servo, digital high-torque, metal gear (ball bearing), waterproof

2075

2250

2255

2075X

waterproof

bearing), waterproof

Page 4 Slash 4X4 Platinum: Low CG-Chassis (Model 6804R) Parts List

piston mits, abock note onts, hollow balls) (renews 2 shocks) Rod ends (GTR shocks) (6) Rod ends (GTR shocks) (7) Rod (GTR shocks) (8) Shaft, GTR xxiong, (The coated bodies with TN shaft (GTR xxiong), (The coated bodies with TN shaft (fully assembled, Visituot springs) (2) Shocks, GTR (John hard-anodized, PTFE-coated bodies with TN shaft (fully assembled, Visituot springs) (2) Shocks, GTR (Visituot) (Visituot) (2) Shocks, GTR (Visituot) (2) Shocks,	
piston nuts, shock rold ends, heliow balls) (increws 2 shocks) 74697	on head set (2-hole (2)/ 3-
7461 Shaft, GTR (ang, Thi-coated (2) 7461 Shocks, GTR Long green-anodized, PTFE-coated bodies with TIN 8 shafts (fully assembled, without springs) (2) 7462 Shocks, GTR Long green-anodized, PTFE-coated bodies with TIN 7462 Shocks, GTR Long green-anodized, PTFE-coated bodies with TIN 7462 Shocks, GTR Long green-anodized, PTFE-coated bodies with TIN 7462 Shocks, GTR Long green-anodized, PTFE-coated bodies with TIN 7462 Shocks, GTR Long green-anodized, PTFE-coated bodies with TIN 7463 Shocks, GTR Long green-anodized, PTFE-coated bodies with TIN 7464 Shocks, GTR Long green-anodized, PTFE-coated bodies with TIN 7465 Shocks, GTR Long green-anodized, PTFE-coated bodies with TIN 7466 Shocks, GTR Long green-anodized, PTFE-coated bodies with TIN 7467 Spring, shock, white (GTR long) (0.92 are to bried) (1 pair) 7468 Spring, shock, white (GTR long) (0.92 are to bried) (1 pair) 7469 Spring, shock, white (GTR Long) (0.72 are bried) (1 pair) 7460 Spring, shock, white (GTR Long) (0.72 are bried) (1 pair) 7461 Spring, shock, white (GTR Long) (0.72 are bried) (1 pair) 7462 Spring, shock, white (GTR Long) (0.72 are bried) (1 pair) 7463 Spring, shock, white (GTR Long) (0.72 are bried) (1 pair) 7464 Spring, shock, white (GTR Long) (0.72 are bried) (1 pair) 7465 Spring, shock, white (GTR Long) (0.72 are bried) (1 pair) 7466 Spring, shock, white (GTR Long) (1 pair) 7467 Spring, shock, white (GTR Long) (1 pair) 7468 Ping, shock white (GTR Long) (1 pair) 7469 Spring, shock, white (GTR Long) (1 pair) 7460 Spring, shock, white (GTR Long) (1 pair) 7461 Spring, shock, white (GTR Long) (1 pair) 7462 Spring, shock, white (GTR Long) (1 pair) 7463 Spring, shock, white (GTR Long) (1 pair) 7464 Spring, shock, white (GTR Long) (1 pair) 7465 Spring, shock white (1 pair) 7466 Ping, shock white (1 pair) 7466 Ping, shock white (1 pair) 7467 Spring, shock white (1 pair) 7468 Ping, shock white (1 pair) 7469 Spring, shock white (1 pair) 7460 Spring, shock white (1 pair) 7460 Spring, shock white (1 pair) 7460 Ping, shock white (1 pair) 7460 Ping, shock wh	, , ,
74610 Shock, GTR long green-anodized, PTFE-coated bodies with TIN shafts (fully assembled, without springs) (2) 74610 Shock, GTR long green-anodized, PTFE-coated bodies with TIN shafts (tassembled) (2) (without springs) (2) 74610 Shock, GTR long part-anodized, PTFE-coated bodies with TIN shafts (tassembled) (2) (without springs) (2) 74610 Shock, GTR long part-anodized, PTFE-coated bodies with TIN shafts (tassembled) (2) (without springs) (2) 74610 Shock, GTR try-long hard-anodized, PTFE-coated bodies with TIN shafts (tassembled) (2) (without springs) (2) 74620 Shock, GTR try-long) hard-anodized, PTFE-coated bodies with TIN shafts (tassembled) (2) (without springs) (3) 74621 Shock, with (GTR long) (0.523 rate orrange) (1 pair) shafts (assembled) (2) (without springs) (3) 7463 Spring, shock, white (GTR long) (0.523 rate green) (1 pair) spring, shock, white (GTR long) (0.527 rate parent) (1 pair) spring, shock, white (GTR try-long) (0.752 rate green) (1 pair) spring, shock, white (GTR xx-long) (0.752 rate green) (1 pair) spring, shock, white (GTR xx-long) (0.752 rate green) (1 pair) spring, shock, white (GTR xx-long) (0.752 rate green) (1 pair) spring, shock, white (GTR xx-long) (0.752 rate green) (1 pair) spring, shock, white (GTR xx-long) (0.752 rate green) (1 pair) spring, shock, white (GTR xx-long) (0.752 rate green) (1 pair) spring, shock, white (GTR xx-long) (0.752 rate green) (1 pair) spring, shock, white (GTR xx-long) (0.752 rate green) (1 pair) spring, shock, white (GTR xx-long) (0.752 rate green) (1 pair) spring, shock, white (GTR xx-long) (0.752 rate green) (1 pair) spring, shock, white (GTR xx-long) (0.752 rate green) (1 pair) spring, shock, white (GTR xx-long) (0.752 rate green) (1 pair) spring, shock, white (GTR xx-long) (0.752 rate green) (1 pair) spring, shock, white (GTR xx-long) (0.752 rate green) (1 pair) spring, shock, white (GTR xx-long) (0.752 rate green) (1 pair) spring, shock, white (GTR xx-long) (0.752 rate green) (1 pair) spring, shock, white (GTR xx-long) (1 pair) spring, shock, white (1	pink) (2)
Shocks, GTR long prem-anodized, PTE-coated bodies with TIN Shocks, GTR long hard-anodized, PTE-coated bodies with TIN Shocks, GTR long hard-anodized, PTE-coated bodies with TIN Shaffat (saesmbied) (2) (without springs) (2) Shocks, GTR xx-long green-anodized, PTE-coated bodies with TIN shaffat (saesmbied) (2) (without springs) (2) Shocks, GTR xx-long green-anodized, PTE-coated bodies with TIN shaffat (saesmbied) (2) (without springs) (2) Shocks, GTR xx-long) (0.632 rate orange) (1 pair) shaffat (saesmbied) (2) (without springs) (3) Shock, With (GTR long) (0.632 rate orange) (1 pair) shaffat (saesmbied) (2) (without springs) (3) Shock, with (GTR long) (0.632 rate orange) (1 pair) shaffat (saesmbied) (2) (without springs) (3) Shock, with (GTR long) (0.673 rate black) (1 pair) shaffat (saesmbied) (2) (xithout springs) (2) Shock, with (GTR long) (0.673 rate black) (1 pair) shaffat (saesmbied) (2) (xithout springs) (2) Shock, with (GTR long) (0.673 rate black) (1 pair) shaffat (3) Shock, white (GTR long) (0.673 rate black) (1 pair) shaffat (3) Shock, white (GTR xx-long) (0.711 rate orange) (1 pair) shock, withe (GTR xx-long) (0.711 rate orange) (1 pair) shock, white (GTR xx-long) (0.714 rate black) (1 pair) shock, white (GTR xx-long) (0.714 rate black) (1 pair) shock, white (GTR xx-long) (0.714 rate black) (1 pair) shock, white (GTR xx-long) (0.714 rate black) (1 pair) shock, white (GTR xx-long) (0.714 rate black) (1 pair) shock, white (GTR xx-long) (0.714 rate black) (1 pair) shock, white (GTR xx-long) (0.714 rate black) (1 pair) shock, white (GTR xx-long) (0.714 rate black) (1 pair) shock, white (GTR xx-long) (0.714 rate black) (1 pair) shock, white (GTR xx-long) (0.714 rate black) (1 pair) shock, white (GTR xx-long) (0.714 rate black) (1 pair) shock, white (GTR xx-long) (0.714 rate black) (1 pair) shock, white (GTR xx-long) (1 pair) shock, white (GTR xx-long) (1 pair) shock, white (GTR xx-long) (1 pair) shock, white (1 xx-long) (1 pair) shock, white (1 xx-long) (1 pair) shock, white (1 xx-long) (1 pair) shock, whi	blue) (2)
shafts (fully assembled, without springs) [2) 7461X Shocks, GTR xx-dnq-anolazed, PTFE-coated bodies with TIN shafts (assembled) [2] (without springs) [3] 7462G Shocks, GTR xx-dng green-anolazed, PTFE-coated bodies with TIN shafts (fully assembled, without springs) [2] 7462C Shocks, GTR xx-dng green-anolazed, PTFE-coated bodies with TIN shafts (fully assembled, without springs) [2] 7462C Shocks, GTR xx-dng green-anolazed, PTFE-coated bodies with TIN shafts (fully assembled, without springs) [2] 7462C Shocks, GTR xx-dng green-anolazed, PTFE-coated bodies with TIN shafts (fully assembled, without springs) [2] 7463 Spring, shock, white (GTR long) (0.52 rate prene) [4] pair) 7464 Spring, shock, white (GTR long) (0.51 rate black) [1] pair) 7465 Spring, shock, white (GTR tong) (0.767 rate black) [1] pair) 7466 Spring, shock, white (GTR xx-dng) (0.762 rate prene) [4] pair) 7467 Spring, shock, white (GTR xx-dng) (0.762 rate prene) [4] pair) 7468 Spring, shock, white (GTR xx-dng) (0.762 rate black) [1] pair) 7469 Spring, shock, white (GTR xx-dng) (0.762 rate black) [1] pair) 7460 Spring, shock, white (GTR xx-dng) (0.762 rate black) [1] pair) 7461 Spring, shock, white (GTR xx-dng) (0.762 rate black) [1] pair) 7462 Spring, shock, white (GTR xx-dng) (0.762 rate black) [1] pair) 7463 Spring, shock white (GTR xx-dng) (0.762 rate black) [1] pair) 7464 Spring, shock, white (GTR xx-dng) (0.762 rate black) [1] pair) 7465 Shlock shafts, steel (GTR xx-dng) (0.762 rate black) [1] pair) 7466 Spring, shock white (GTR xx-dng) (1.002 rate black) [1] pair) 7467 Shlock shafts, steel pair (1) pair) 7468 Spring, shock white (GTR xx-dng) (1.002 rate black) [1] pair) 7469 Spring, shock white (GTR xx-dng) (1.002 rate black) [1] pair) 7460 Spring, shock white (GTR xx-dng) (1.002 rate black) [1] pair) 7461 Spring, shock white (GTR xx-dng) (1.002 rate black) [1] pair) 7462 Spring, shock white (GTR xx-dng) (1.002 rate black) [1] pair) 7463 Spring, shock white (GTR xx-dng) [1] pair) 7464 Spring, shock white (GTR xx-dng) [green) (2)
Shocks, GTR long hard-anodized, PTFE-coated bodies with TIN shafts (fully assembled) ((without springs) (2) Shocks, GTR xx-long green-anodized, PTFE-coated bodies with TIN Thatfar (fully assembled) (without springs) (2) Shocks, GTR xx-long green-anodized, PTFE-coated bodies with TIN Shafts (fully assembled) (GTR long) (0.852 rate green) (1 pair) Shocks, GTR xx-long pard-anodized, PTFE-coated bodies with TIN Shafts (fully assembled) (GTR long) (0.852 rate green) (1 pair) Spring, shock, white (GTR long) (0.852 rate brue) (1 pair) Spring, shock, white (GTR long) (0.852 rate brue) (1 pair) Spring, shock, white (GTR long) (0.852 rate brue) (1 pair) Spring, shock, white (GTR long) (0.872 rate brue) (1 pair) Spring, shock, white (GTR xx-long) (0.711 rate orange) (1 pair) Spring, shock, white (GTR xx-long) (0.727 rate brue) (1 pair) Spring, shock, white (GTR xx-long) (0.787 rate brue) (1 pair) Spring, shock, white (GTR xx-long) (0.787 rate brue) (1 pair) Spring, shock, white (GTR xx-long) (0.787 rate brue) (1 pair) Spring, shock, white (GTR xx-long) (0.787 rate brue) (1 pair) Spring, shock, white (GTR xx-long) (0.787 rate brue) (1 pair) Spring, shock, white (GTR xx-long) (0.787 rate brue) (1 pair) Spring, shock, white (GTR xx-long) (0.787 rate brue) (1 pair) Spring, shock, white (GTR xx-long) (0.787 rate brue) (1 pair) Spring, shock, white (GTR xx-long) (0.787 rate brue) (1 pair) Spring, shock, white (GTR xx-long) (0.787 rate brue) (1 pair) Spring, shock, white (GTR xx-long) (0.787 rate brue) (1 pair) Spring, shock, white (GTR xx-long) (0.787 rate brue) (1 pair) Spring, shock, white (GTR xx-long) (0.787 rate brue) (1 pair) Spring, shock, white (GTR xx-long) (0.787 rate brue) (1 pair) Spring, shock, white (GTR xx-long) (0.787 rate brue) (1 pair) Spring, shock, white (GTR xx-long) (0.787 rate brue) (1 pair) Spring, shock, white (GTR xx-long) (0.787 rate brue) (1 pair) Spring, shock, white (GTR xx-long) (0.787 rate brue) (1 pair) Spring, shock, white (1 pair) Spring, shock, white (1 pair) Spring, shock, white (1 pair) Spr	orange) (2)
shafts (assembled) (2) (without springs) 74620 Shocks, GTR xx-long green-anodized, PTFE-coated bodies with TIN shafts (fully assembled, without springs) (2) 74621 Shocks, GTR xx-long) (and the coated) (1 pair) 74622 Shocks, GTR xx-long) (br. TFE-coated bodies with TIN shafts (assembled) (2) (without springs) 7463 Spring, shock, with (GTR long) (0.80 art are cange) (1 pair) 7464 Spring, shock, with (GTR long) (0.82 rate bullo (1 pair) 7465 Spring, shock, with (GTR long) (0.82 rate bullo (1 pair) 7465 Spring, shock, with (GTR xx-long) (0.711 rate orange) (1 pair) 7465 Spring, shock, with (GTR xx-long) (0.711 rate orange) (1 pair) 7466 Spring, shock, with (GTR xx-long) (0.711 rate orange) (1 pair) 7467 Spring, shock, with (GTR xx-long) (0.782 rate black) (1 pair) 7468 Spring, shock, with (GTR xx-long) (0.782 rate preen) (1 pair) 7469 Spring, shock, with (GTR xx-long) (0.782 rate preen) (1 pair) 7460 Spring, shock, with (GTR xx-long) (0.782 rate preen) (1 pair) 7461 Spring, shock, with (GTR xx-long) (0.782 rate preen) (1 pair) 7462 Spring, shock, with (GTR xx-long) (0.782 rate preen) (1 pair) 7463 Spring, shock, with (GTR xx-long) (0.782 rate preen) (1 pair) 7464 Spring, shock, with (GTR xx-long) (0.782 rate preen) (1 pair) 7465 Spring, shock, with (GTR xx-long) (0.782 rate preen) (1 pair) 7466 Spring, shock, with (GTR xx-long) (0.782 rate preen) (1 pair) 7467 Spring, shock, with (GTR xx-long) (0.782 rate preen) (1 pair) 7468 Spring, shock, with (GTR xx-long) (0.782 rate preen) (1 pair) 7469 Spring, shock, with (GTR xx-long) (0.782 rate preen) (1 pair) 7460 Spring, shock, with (GTR xx-long) (0.782 rate preen) (1 pair) 7461 Spring, shock, with (GTR xx-long) (0.782 rate preen) (1 pair) 7462 Spring, shock, with (GTR xx-long) (2.782 rate preen) (2.782	(2)
shafts (assembled) (2) (without springs) 74620 Shocks, GTR xx-long) green-anodized, PTFE-coated bodies with TIN shafts (fully assembled, without springs) (2) 74620 Shocks, GTR xx-long) gand-anodized, PTFE-coated bodies with TIN shafts (fully assembled with CITR long) (0.823 rate orange) (1 pair) 74620 Shocks, GTR xx-long) gand-anodized, PTFE-coated bodies with TIN Spring, shock, white (GTR long) (0.823 rate orange) (1 pair) 74641 Spring, shock, white (GTR long) (0.823 rate black) (1 pair) 74652 Shock, white (GTR long) (0.823 rate black) (1 pair) 74653 Spring, shock, white (GTR long) (0.824 rate black) (1 pair) 74654 Spring, shock, white (GTR xx-long) (0.714 rate brang) (1 pair) 74654 Spring, shock, white (GTR xx-long) (0.747 rate black) (1 pair) 74655 Shock short (6) (GTR xx-long) (0.747 rate black) (1 pair) 7466 Spring, shock, white (GTR xx-long) (0.747 rate black) (1 pair) 7467 Spring, shock, white (GTR xx-long) (0.747 rate black) (1 pair) 7468 Spring, shock, white (GTR xx-long) (0.747 rate black) (1 pair) 7469 Spring, shock, white (GTR xx-long) (0.747 rate black) (1 pair) 7460 Spring, shock, white (GTR xx-long) (0.747 rate black) (1 pair) 7461 Spring, shock, white (GTR xx-long) (0.747 rate black) (1 pair) 7462 Spring, shock, white (GTR xx-long) (0.747 rate black) (1 pair) 7463 Spring, shock, white (GTR xx-long) (0.747 rate black) (1 pair) 7464 Spring, shock, white (GTR xx-long) (0.747 rate black) (1 pair) 7465 Spring, shock, white (GTR xx-long) (0.747 rate black) (1 pair) 7466 Spring, shock, white (GTR xx-long) (0.747 rate black) (1 pair) 7467 Spring, shock, white (GTR xx-long) (0.747 rate black) (1 pair) 7468 Spring, shock, white (GTR xx-long) (0.747 rate black) (1 pair) 7469 Spring, shock, white (GTR xx-long) (0.747 rate black) (1 pair) 7460 Spring, shock, white (GTR xx-long) (0.747 rate black) (1 pair) 7461 Spring, shock, white (GTR xx-long) (0.747 rate black) (1 pair) 7462 Spring, shock, white (GTR xx-long) (1 pair) 7463 Spring, shock, white (GTR xx-long) (1 pair) 7464 Spring,	oink) (2)
Till shafts (fully assembled, without springs) (2) 462X Shocks, GTR x-kong hard-anodized, PTE-Coated bodies with Till shafts (assembled) (2) (without springs) 7440 Spring, shock, white (GTR long) (0.632 rate orange) (1 pair) 7441 Spring, shock, white (GTR long) (0.637 fare black) (1 pair) 7442 Spring, shock, white (GTR long) (0.637 fare black) (1 pair) 7443 Spring, shock, white (GTR long) (0.767 fare black) (1 pair) 7444 Spring, shock, white (GTR long) (0.767 fare black) (1 pair) 7442 Spring, shock, white (GTR x-long) (0.711 rate orange) (1 pair) 7443 Spring, shock, white (GTR x-long) (0.711 rate orange) (1 pair) 7444 Spring, shock, white (GTR x-long) (0.727 fare black) (1 pair) 7445 Spring, shock, white (GTR x-long) (0.727 fare black) (1 pair) 7446 Spring, shock, white (GTR x-long) (0.847 rate pilk (1) pair) 7447 Spring, shock, white (GTR x-long) (0.847 rate pilk (1) pair) 7449 Spring, shock, white (GTR x-long) (0.847 rate pilk (1) pair) 7440 Spring, shock, white (GTR x-long) (0.854 rate pilk) (1 pair) 7441 Spring, shock, white (GTR x-long) (0.854 rate pilk) (1 pair) 7442 Spring, shock, white (GTR x-long) (0.854 rate pilk) (1 pair) 7443 Spring, shock, white (GTR x-long) (0.854 rate pilk) (1 pair) 7444 Spring, shock, white (GTR x-long) (0.854 rate pilk) (1 pair) 7445 Spring, shock, white (GTR x-long) (0.854 rate pilk) (1 pair) 7446 Spring, shock, white (GTR x-long) (0.854 rate pilk) (1 pair) 7447 Spring, shock, white (GTR x-long) (0.854 rate pilk) (1 pair) 7448 Spring, shock, white (GTR x-long) (0.854 rate pilk) (1 pair) 7449 Spring, shock, white (GTR x-long) (0.854 rate pilk) (1 pair) 7450 Spring, shock, white (GTR x-long) (0.854 rate pilk) (1 pair) 7451 Spring, shock, white (GTR x-long) (0.854 rate pilk) (1 pair) 7452 Spring, shock, white (GTR x-long) (0.854 rate pilk) (1 pair) 7454 Spring, shock, white (GTR x-long) (1 pair) 7455 Spring, shock, white (GTR x-long) (1.954 rate black) (1 pair) 7455 Spring, shock, white (1 pair) 7456 Spring, shock, white (1 pair) 7457 Spring, shock, white (1 pair) 7458 Spring, sh	
Till shafts (fully assembled, without springs) (2) 462X Shock, GTR x-Accing part-Sandzide, PTE-Coaled bodies with Till shafts (assembled) (2) (without springs) 47440 Spring, shock, with (CTR long) (0.623 rate orange) (1 pair) 47441 Spring, shock, with (CTR long) (0.637 rate black) (1 pair) 4744 Spring, shock, with (CTR long) (0.637 rate black) (1 pair) 4744 Spring, shock, with (CTR long) (0.637 rate black) (1 pair) 4744 Spring, shock, with (CTR v. long) (0.711 rate orange) (1 pair) 4744 Spring, shock, white (CTR x-long) (0.724 rate black) (1 pair) 4744 Spring, shock, white (CTR x-long) (0.724 rate black) (1 pair) 4745 Spring, shock, white (CTR x-long) (0.724 rate black) (1 pair) 4746 Spring, shock, white (CTR x-long) (0.724 rate black) (1 pair) 4747 Spring, shock, white (CTR x-long) (0.724 rate black) (1 pair) 4749 Spring, shock, white (CTR x-long) (0.745 rate black) (1 pair) 4749 Spring, shock, white (CTR x-long) (0.745 rate black) (1 pair) 4749 Spring, shock, white (CTR x-long) (0.745 rate black) (1 pair) 4749 Spring, shock, white (CTR x-long) (0.745 rate black) (1 pair) 4749 Spring, shock, white (CTR x-long) (0.745 rate black) (1 pair) 4749 Spring, shock, white (CTR x-long) (1 pair) 4740 Spring, shock, white (CTR x-long) (1 pair) 4741 Spring, shock, white (CTR x-long) (1 pair) 4742 Spring, shock, white (CTR x-long) (1 pair) 4743 Spring, shock, white (CTR x-long) (2) 4744 Spring, shock, white (CTR x-long) (2) 4745 Spring, shock, white (CTR x-long) (2) 4746 Spring, shock, white (CTR x-long) (2) 4747 Spring, shock, white (CTR x-long) (2) 4748 Spring, shock, white (CTR x-long) (2) 4749 Spring, shock, white (CTR x-long) (2) 4740 Spring, shock, white (2) 4740 Spring, shock	reen) (2)
shafts (assembled) (2) (without springs) 7440 Spring, shock, white (GTR long) (0.63 arte orange) (1 pair) 7441 Spring, shock, white (GTR long) (0.67 farb black) (1 pair) 7442 Spring, shock, white (GTR long) (0.67 farb black) (1 pair) 7443 Spring, shock, white (GTR long) (0.67 farb black) (1 pair) 7444 Spring, shock, white (GTR long) (0.67 farb black) (1 pair) 7442 Spring, shock, white (GTR x-long) (0.711 rate orange) (1 pair) 7443 Spring, shock, white (GTR x-long) (0.752 rate green) (1 pair) 7444 Spring, shock, white (GTR x-long) (0.752 rate green) (1 pair) 7445 Spring, shock, white (GTR x-long) (0.752 rate green) (1 pair) 7446 Spring, shock, white (GTR x-long) (0.752 rate green) (1 pair) 7447 Spring, shock, white (GTR x-long) (0.847 rate blue) (1 pair) 7448 Spring, shock, white (GTR x-long) (0.847 rate blue) (1 pair) 7449 Spring, shock, white (GTR x-long) (0.847 rate blue) (1 pair) 7440 Spring, shock, white (GTR x-long) (0.847 rate blue) (1 pair) 7441 Spring, shock, white (GTR x-long) (0.847 rate blue) (1 pair) 7442 Spring, shock, white (GTR x-long) (0.847 rate blue) (1 pair) 7443 Spring, shock, white (GTR x-long) (0.847 rate blue) (1 pair) 7444 Spring, shock, white (GTR x-long) (0.847 rate blue) (1 pair) 7445 Spring, shock, white (GTR x-long) (0.847 rate blue) (1 pair) 7446 Spring, shock, white (GTR x-long) (0.847 rate blue) (1 pair) 7447 Spring, shock, white (GTR x-long) (0.847 rate blue) (1 pair) 7448 Spring, shock, white (GTR x-long) (0.848 rate pink) (1 pair) 7449 Spring, shock, white (GTR x-long) (0.848 rate pink) (1 pair) 7440 Spring, shock, white (GTR x-long) (0.848 rate pink) (1 pair) 7441 Spring, shock, white (GTR x-long) (0.848 rate pink) (1 pair) 7442 Spring, shock, white (GTR x-long) (0.848 rate pink) (1 pair) 7444 Spring, shock, white (GTR x-long) (0.848 rate pink) (1 pair) 7445 Spring, shock, white (GTR x-long) (1.848 rate pink) (1 pair) 7446 Spring, shock, white (GTR x-long) (1.848 rate pink) (1 pair) 7447 Spring, shock, white (STR x-long) (1 pair) 7448 Spring, shock, white (STR x-long) (1 pai	
shafts (assembled) (2) (without springs) 7440 Spring, shock, with (GTR long) (0.683 rate orange) (1 pair) 7441 Spring, shock, with (GTR long) (0.687 rate black) (1 pair) 7442 Spring, shock, with (GTR long) (0.687 rate black) (1 pair) 7443 Spring, shock, with (GTR long) (0.687 rate black) (1 pair) 7444 Spring, shock, with (GTR long) (0.687 rate black) (1 pair) 7445 Spring, shock, with (GTR long) (0.687 rate orange) (1 pair) 7446 Spring, shock, with (GTR long) (0.687 rate orange) (1 pair) 7447 Spring, shock, with (GTR long) (0.687 rate orange) (1 pair) 7446 Spring, shock, with (GTR long) (0.687 rate orange) (1 pair) 7447 Spring, shock, with (GTR long) (0.687 rate orange) (1 pair) 7448 Spring, shock, with (GTR long) (0.687 rate orange) (1 pair) 7449 Spring, shock, with (GTR long) (0.884 rate prink) (1 pair) 7440 Spring, shock, with (GTR long) (0.884 rate prink) (1 pair) 7441 Spring, shock, with (GTR long) (0.884 rate prink) (1 pair) 7442 Spring, shock, with (GTR long) (0.884 rate prink) (1 pair) 7443 Spring, shock, with (GTR long) (0.884 rate prink) (1 pair) 7444 Spring, shock, with (GTR long) (0.884 rate prink) (1 pair) 7445 Spring, shock, with (GTR long) (1 pair) 7446 Spring, shock, with (GTR long) (1 pair) 7447 Spring, shock, with (GTR long) (1 pair) 7449 Spring, shock, with (GTR long) (1 pair) 7449 Spring, shock, with (GTR long) (1 pair) 7450 Spring, shock, with (GTR long) (1 pair) 7460 Spring, shock, with (GTR long) (1 pair) 7460 Spring, shock, with (GTR long) (1 pair) 7470 Spring, shock, with (GTR long) (1 pair) 7480 Spring, shock, with (GTR long) (1 pair) 749 Spring, shock, with (GTR long) (1 pair) 740 Spring, shock, with (1	(2)
Spring, shock, white (GTR long) (0.76 rate black) (1 pair)	spring pre-load spacers
Spring, shock, white (GTR tong) (0.767 rate black) (1 pair)	
Spring, shock, white (GRT Roylo) (a.982 rate blue) (1 pair) Spring, shock, white (GRT Rx-dong) (0.792 rate present) 1 pair) Spring, shock, white (GRT Rx-dong) (0.792 rate present) 1 pair) Spring, shock, white (GRT Rx-dong) (0.874 rate black) (1 pair) Spring, shock, white (GRT Rx-dong) (0.874 rate black) (1 pair) Spring, shock, white (GRT Rx-dong) (0.874 rate black) (1 pair) Spring, shock, white (GRT Rx-dong) (0.874 rate black) (1 pair) Spring, shock, white (GRT Rx-dong) (0.884 rate phink) (1 pair) Spring, shock, white (GRT Rx-dong) (0.884 rate phink) (1 pair) Spring, shock, white (GRT Rx-dong) (1 control rate blue) (1 pair) Spring, shock, white (GRT Rx-dong) (1 control rate blue) (1 pair) Spring, shock, white (GRT Rx-dong) (1 control rate blue) (1 pair) Spring, shock, white (GRT Rx-dong) (1 control rate blue) (1 pair) Spring, shock, white (GRT Rx-dong) (1 control rate blue) (1 pair) Spring, shock, white (GRT Rx-dong) (1 control rate blue) (1 pair) Spring, shock, white (GRT Rx-dong) (1 control rate blue) (1 pair) Spring, shock, white (GRT Rx-dong) (1 control rate blue) (1 pair) Spring, shock, white (GRT Rx-dong) (1 control rate blue) (1 pair) Spring, shock, white (GRT Rx-dong) (2 control rate blue) (1 pair) Spring, shock, white (GRT Rx-dong) (2 control rate blue) (1 pair) Spring, shock white (GRT Rx-dong) (2 control rate blue) (1 pair) Spring, shock shock (SV-dong) (1 control rate blue) (1 pair) Spring, shock shock (SV-dong) (1 control rate blue) (1 pair) Spring, shock s	e w/ spring pre-load
5 pring, shock, white (GTR xx-long) (0.71 rate or cange) (1 pair) 5 pring, shock, white (GTR xx-long) (0.71 rate or cange) (1 pair) 5 pring, shock, white (GTR xx-long) (0.71 rate or cange) (1 pair) 5 pring, shock, white (GTR xx-long) (0.78 rate black) (1 pair) 5 pring, shock, white (GTR xx-long) (0.87 rate black) (1 pair) 5 pring, shock, white (GTR xx-long) (0.884 rate pink) (1 pair) 5 pring, shock, white (GTR xx-long) (0.884 rate pink) (1 pair) 5 pring, shock, white (GTR xx-long) (1.884 rate pink) (1 pair) 5 pring, shock, white (GTR xx-long) (1.884 rate pink) (1 pair) 5 pring, shock, white (GTR xx-long) (1.884 rate pink) (1 pair) 5 pring, shock, white (GTR xx-long) (1.884 rate pink) (1 pair) 5 pring, shock, white (GTR xx-long) (1.884 rate pink) (1 pair) 5 pring, shock, white (GTR xx-long) (1.884 rate pink) (1 pair) 5 pring, shock, white (GTR xx-long) (1.884 rate pink) (1 pair) 5 pring, shock, white (GTR xx-long) (1.884 rate pink) (1 pair) 5 pring, shock, white (GTR xx-long) (1.884 rate pink) (1 pair) 5 pring, shock, white (GTR xx-long) (1.884 rate pink) (1 pair) 5 pring, shock, white (GTR xx-long) (1.884 rate pink) (1 pair) 5 pring, shock (1.884 pring) (1.884 rate pink) (1 pair) 5 pring green (1.884 pring) (1.884 rate pink) (1 pair) 5 pring, shock (1.884 pring) (1.884 rate pink) (1.884 pring) (1.	
5 Spring, shock, white (GTR xx-long) (0.74 rate orange) (1 pair) 5 Spring, shock, white (GTR xx-long) (0.874 rate black) (1 pair) 5 Spring, shock, white (GTR xx-long) (0.874 rate black) (1 pair) 5 Spring, shock, white (GTR xx-long) (1.084 rate blue) (1 pair) 5 Spring, shock, white (GTR xx-long) (1.084 rate blue) (1 pair) 5 Shock Spring, shock, white (GTR xx-long) (1.084 rate blue) (1 pair) 5 Shock Spring, shock, white (GTR xx-long) (1.084 rate blue) (1 pair) 5 Shock Spring, shock, white (GTR xx-long) (1.084 rate blue) (1 pair) 5 Shock Spring, shock, white (GTR xx-long) (1.084 rate blue) (1 pair) 5 Shock Spring, shock, white (GTR xx-long) (1.084 rate blue) (1 pair) 5 Shock Spring, shock, white (GTR xx-long) (1.084 rate blue) (1 pair) 5 Shock Spring, shock, white (GTR xx-long) (1.084 rate blue) (1 pair) 5 Shock Spring, shock, white (GTR xx-long) (1.084 rate blue) (1 pair) 5 Shock Spring, shock, white (GTR xx-long) (1.084 rate blue) (1 pair) 5 Shock Spring, shock, white (GTR xx-long) (1.084 rate blue) (1 pair) 5 Spring shock, white (GTR xx-long) (1.084 rate blue) (1 pair) 5 Spring shock, white (GTR xx-long) (1.084 rate blue) (1 pair) 5 Spring shock, white (GTR xx-long) (1.084 rate blue) (1 pair) 5 Spring shock, white (GTR xx-long) (1.084 rate blue) (1 pair) 6 Spring shock, white (GTR xx-long) (1.084 rate blue) (1 pair) 6 Spring shock, white (GTR xx-long) (1.084 rate blue) (2.085	spring pre-load spacers
Spring, shock, white (GTR xx-long) (0.787 atel bards) (1 pair) Spring, shock, white (GTR xx-long) (0.874 atel bards) (1 pair) Spring, shock, white (GTR xx-long) (0.884 rate plink) (1 pair) Spring, shock, white (GTR xx-long) (0.884 rate plink) (1 pair) Spring, shock, white (GTR xx-long) (1.004 rate blue) (1 pair) SIDGES PTO-GYD	
Spiring, shock, white (GTR xx-long) (0.874 rate black) (1 pair) Spiring, shock, white (GTR xx-long) (0.884 rate plack) (1 pair) Spiring, shock, white (GTR xx-long) (1.004 rate blue) (1 pair) Shock Strock Spiring, shock, white (GTR xx-long) (1.004 rate blue) (1 pair) Shock Strock Spiring, shock, white (GTR xx-long) (1.004 rate blue) (1 pair) Shock Strock Spiring, shock, white (GTR xx-long) (1.004 rate blue) (1 pair) Shock Strock Spiring, shock, white (GTR xx-long) (1.004 rate blue) (1 pair) Shock Strock Spiring, shock, white (GTR xx-long) (1.004 rate blue) (1 pair) Shock Strock Spiring, shock, white (GTR xx-long) (1.004 rate blue) (1 pair) Shock Strock Spiring, shock, white (GTR xx-long) (1.004 rate blue) (1 pair) Shock Spiring, shock, white (GTR xx-long) (1.004 rate blue) (1 pair) Shock Spiring, shock, white (GTR xx-long) (1.004 rate blue) (1 pair) Shock Spiring, shock, white (GTR xx-long) (1.004 rate blue) (1 pair) Shock Spiring, shock, white (GTR xx-long) (1.004 rate blue) (1 pair) Shock Spiring, shock (shord) (1.004 rate blue) (1 pair) Shock Spiring, shock (shord) (1.004 rate blue) (1 pair) Shock Spiring, shock (shord) (1.004 rate blue) (1 pair) Shock Spiring, shock (shord) (1.004 rate blue) (1 pair) Shock Spiring, shock (shord) (1.004 rate blue) (1 pair) Shock Spiring, shord (shord) (1.004 rate blue) (1 pair) Shock Spiring, shord (shord) (1.004 rate blue) (1 pair) Shock Spiring, shord (shord) (1.004 rate blue) (1 pair) Shock Spiring, shord (shord) (1.004 rate blue) (1 pair) Shock Spiring, shord (shord) (1.004 rate blue) (1 pair) Shock Spiring, shord (shord) (1.004 rate blue) (1 pair) Shock Spiring, shord (shord) (1.004 rate blue) (1 pair) Shock Spiring, shord (shord) (1.004 rate blue) (1 pair) Shock Spiring, shord (shord) (1.004 rate blue) (1 pair) Shock Spiring, shord (shord) (1.004 rate blue) (1.004 rat	w/ spring pre-load
Spring, shock, white (GIT x-x-long) (J.084 rate pink) († pair) Spring, shock, white (GIT x-x-long) (1.084 rate pink) († pair) Sillocks (Pro-level Alliminim) Sillocks (Sillock) (spring x-long) (1.09 task of the state of the st	
Spring, shock, white (GTR xx-long) (1.004 rate blue) (1 pair) SiDCIS (FTO-I-BUE Alluminum) SiDCIS (FTO-I-BUE Alluminum) Sig Bore shock cylinder (NX-long) (1) Sig Bore shock cylinder (XX-long) (1) Sig Bore shock cylinder (XX-long) (1) Sig Bore shock cylinder (XX-long) (1) Sig Bore shock (hard-anodized & PTFE-coated T6 aluminum) (assembled with TiN shafts) was springs (front & rear) (4) Big Bore shocks (IxX-long) (Indra-anodized & PTFE-coated T6 aluminum) (assembled with TiN shafts) was springs (front) (2) Big Bore shocks (XX-long) (Indra-anodized & PTFE-coated T6 aluminum) (assembled with TiN shafts) was springs (front) (2) Big Bore shocks (XX-long) (Indra-anodized & PTFE-coated T6 aluminum) (assembled with TiN shafts) was springs (front) (2) Sig Bore shocks (XX-long) (Indra-anodized & PTFE-coated T6 aluminum) (assembled with TiN shafts) was springs (front) (2) Sig Bore shocks (XX-long) (Indra-anodized & PTFE-coated T6 aluminum) (assembled with TiN shafts) was springs (front) (2) Big Bore shocks (XX-long) (Indra-anodized & PTFE-coated T6 aluminum (Ind	ents
Sing Strock, Kimte (Juno) (1) (1) (1) (1) (1) (2) (2) (2) (2) (3) (4) (2) (4) (4) (4) (4) (4) (4) (4) (4) (4) (4	
SIDCAS INTO EIG All IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	
See Big Bore shock cylinder (long) (1)	, , ,
Big Bore shock cylinder (XX-forg) (1) 8819 Bore shocks (hard-anodized & PTFE-coated T6 aluminum) 8820 Big Bore shocks (long) (hard-anodized & PTFE-coated T6 aluminum) 8821 Big Bore shocks (long) (hard-anodized & PTFE-coated T6 aluminum) 8822 Big Bore shocks (XX-long) (hard-anodized & PTFE-coated T6 aluminum) 8822 Big Bore shocks (XX-long) (hard-anodized & PTFE-coated T6 aluminum) 8822 Big Bore shocks (XX-long) (hard-anodized & PTFE-coated T6 aluminum) 8822 Big Bore shocks (XX-long) (hard-anodized & PTFE-coated T6 aluminum) 8822 Big Bore shocks (XX-long) (hard-anodized & PTFE-coated T6 aluminum) 8822 Big Bore shocks (XX-long) (hard-anodized & PTFE-coated T6 aluminum) 8822 Big Bore shocks (XX-long) (hard-anodized & PTFE-coated T6 aluminum) 8822 Big Bore shocks (XX-long) (hard-anodized & PTFE-coated T6 aluminum) 8822 Big Bore shocks (XX-long) (hard-anodized & PTFE-coated T6 aluminum (hue-ano (hard-anodized & PTFE-coated T6 aluminum (hilled bare (2) aluminum) 882 Big Bore shocks (XX-long) (hard-anodized & PTFE-coated T6 aluminum (hue-ano (hard-anodized & PTFE-coated T6 aluminum (blue-ano (hard-anodized & P	sealed) (1) (101 slippel
Big Bore shocks (hard-anodized & PTTE-coated T6 aluminum) (assembled with Tin sharts and springs) (front & rear) (4) Big Bore shocks (long) (hard-anodized & PTTE-coated T6 aluminum) (assembled with Tin sharts) w/o springs (front) (2) Big Bore shocks (XV-long) (And-anodized & PTTE-coated T6 aluminum) (assembled with Tin sharts) w/o springs (front) (2) Big Bore shocks (XV-long) (And-anodized & PTTE-coated T6 aluminum) (assembled with Tin sharts) w/o springs (rear) (2) Big Bore shocks (XV-long) (And-anodized & PTTE-coated T6 aluminum) (assembled with Tin sharts) w/o springs (rear) (2) Big Bore shocks (XV-long) (And-anodized & PTTE-coated T6 aluminum) (assembled with Tin sharts) w/o springs (rear) (2) Big Bore shocks (XV-long) (And-anodized & PTTE-coated T6 aluminum) (assembled with Tin sharts) w/o springs (rear) (2) Big Bore shocks (XV-long) (And-anodized & PTTE-coated T6 aluminum) (assembled with Tin sharts) w/o springs (rear) (2) Big Bore shocks (XV-long) (And-anodized & PTTE-coated T6 aluminum) (assembled with Tin sharts) w/o springs (rear) (2) Big Bore shocks (XV-long) (And-anodized & PTTE-coated T6 aluminum) (assembled with Tin sharts) w/o springs (rear) (2) Big Bore shocks (XV-long) (And-anodized & PTTE-coated T6 aluminum) (assembled with Tin sharts) w/o springs (rear) (2) Big Bore shocks (Stylong) (Anote) (Big Bore Shocks) (2) Book shafts, steel, chrome finish (nong) (2) Book shafts, steel, chrome finish (nong) (2) Book shafts, steel, chrome finish (nong) (2) Book shafts, steel, chrome finish (xx-long) (2) Book shafts, steel, chrome finish (xx-long) (2) Bilicone shock oil (30 wt) Book shafts, steel, chrome finish (xx-long) (2) Boo	(hezanodized)
(assembled with TIN shafts and springs) (front & rear) (4) Big Bore shocks (long) (hard-anodized & PTFE-coated T6 aluminum) (assembled with TIN shafts) w/o springs (front) (2) Big Bore shocks (XX-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled with TIN shafts) w/o springs (front) (2) Big Bore shocks (XX-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled with TIN shafts) w/o springs (front) (2) Big Bore shocks (XX-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled with TIN shafts) w/o springs (front) (2) Big Bore shocks (XX-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled with TIN shafts) w/o springs (front) (2) Big Bore shocks (XX-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled with TIN shafts) w/o springs (front) (2) Big Bore shocks (XX-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled with TIN shafts) w/o springs (front) (2) Big Bore shocks (XX-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled with TIN shafts) w/o springs (front) (2) Big Bore shocks (XX-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled with TIN shafts) w/o springs (rear) (2) Big Bore shocks (XX-long) (hard-anodized & PTFE-coated T6 aluminum, (lassembled with TIN shafts) w/o springs (rear) (2) Big Bore shocks (GX-2 shocks) Bod ear set, center differential (output gears (2)/ spide gear shaft) Bod ear set, center differential (output gears (2)/ spide gear shaft) Bod ear set, center differential (output gears (2)/ spide gear shaft) Bod ear set, center differential (output gears (2)/ spide gear shaft) Bod ear set, center differential (output gears (2)/ spide gear shaft) Bod ear set, center differential (output gears (2)/ spide feat shaft) Bod ear set, center differential (output gears (2)/ spide feat shaft) Bod ear set, center differential (output gears (2)/ spide feat shaft) Bod ear set, center differential (output gears (2)/ spide feat shaft) Bod ear set, center differential (output gears (2)/ spide feat shaft)	
Big Bore shocks (long) (hard-anodized & PTFE-coated T6 aluminum) (assembled with TiN shafts) wo springs (front) (2) 6888 [888 pla Gres shocks (XX-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled with TiN shafts) wo springs (rear) (2) 6888 [888 pla Gres shocks (XX-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled with TiN shafts) wo springs (rear) (2) 6882 [888 plate to the coated (1-10 to the coated (2-10-10 to the coated (2-10	. Janua, (), (ioi siippei
aluminum) (assembled with TiN shafts) w/o springs (front) (2) Big Bore shocks (XX-Jong) (hard-anodized & PTFE-coated To aluminum) (assembled with TiN shafts) w/o springs (rear) (2) Big Bore shocks (XX-Jong) (hard-anodized & PTFE-coated To aluminum) (assembled with TiN shafts) w/o springs (rear) (2) Big Bore shocks (XX-Jong) (hard-anodized & PTFE-coated To aluminum) (assembled with TiN shafts) w/o springs (rear) (2) Big Bore shocks) Piston head set (2-hole (2)/ 3-hole (2)/) shock mounting bushings & washers (2) (Big Bore Shocks) Basel (2) (Big Bore Shocks) Basel (2) (Big Bore Shocks) Bhock caps, aluminum (Big Bore Shocks) (2) Bhock shafts, hardened steel, titanium nitride coated (long) (2) Bhock shafts, steel, chrome finish (long) (2) Bhock shafts, steel, chrome finish (long) (2) Bhock shafts, steel, chrome finish (xx-long) (2) Basel Springs, front (progressive, 40% rate, plule) (2) Basel Springs, front (progressive, +10% rate, pink) (2) Basel Springs, front (progressive, +20% rate, plule) (2) Basel Springs, front (progressive, +20% rate, blue) (2) Basel Springs, front (progressive, +20% rate, blue) (2) Basel Springs, front (progressive, +20% rate, blue) (2) Basel Springs, rear (progressive, +10% rate, pink) (2) Basel Springs, rear (progressive, +10% rate, pink) (2) Basel Springs, rear (progressive, +10% rate, pink) (2) Basel Springs, rear (progressive, -20% rate, blue) (2) Basel Springs, rear	
Big Bore shocks (XX-long) (hard-anod/zed & PTFE-coated To aluminum) (assembled with TiN shafts) w/o springs (rear) (2) piston head set (2-hole (2)) shock mounting bushings & washers (2) (Big Bore Shocks) Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) piston head set (2-hole (2)) shock mounting bushings & washers (2) (Big Bore Shocks) Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) piston head set (2-hole (2)) shock shafts, hardened steel, titanium nitride coated (long) (2) piston kashafts, hardened steel, titanium nitride coated (xx-long) (2) piston kashafts, hardened steel, titanium nitride coated (xx-long) (2) piston kashafts, steel, chrome finish (xx-long) (2) piston kashafts,	
aluminum) (assembled with TiN shafts) w/o springs (rear) (2) 2669 Piston head set (2-hole (2)) -shock mounting bushings & washers (2) (Big Bore Shocks) 2322 Rebuild kit, Ultra shocks (for 2 shocks) 1942 Rod ends (16 long & 4 short) hollow ball connectors (18) ball screws (2) 2742X Rod ends, short (6)/ hollow balls (6) 2742X Shock shafts, shardened steel, titanium nitride coated (long) (2) 2742X Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) 2742X Shock shafts, steel, chrome finish (long) (2) 2742X Shock shafts, steel, chrome finish (long) (2) 2742X Shock shafts, steel, chrome finish (xx-long) (2) 2742X Shock shafts, steel, chrome finish (long) (2) 2742X Rod ends, short (progressive, +10% rate, pink) (2) 2742X Rod ends, short (progressive, -20% rate, orange) (2) 2742X Rod ends, short (bil long & 4 short) hollow balls (6) 2742X Rod ends, short (6)/ hollow balls (6) 2742X Rod ends, short (6)	v pin (1)
Piston head set (2-hole (2)/ 3-hole (2)) shock mounting bushings & washers (2) (Big Bore Shocks) Rebuild kit, Ultra shocks (for 2 shocks) Red ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) Rod ends, short (6)/ hollow balls (6) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Silicone diaphragms (4) Silicone shock oil (30 wt) Spring strainers, upper & lower (2)/ spring pre-load spacers: Imm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, -20% rate, orange) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, -10% rate, green) (2) Springs, rear (progressive, -10% ra	1 ()
& washers (2) (Big Bore Shocks) Rebuild kit, Ultra shocks (for 2 shocks) 1942 Rod ends, (16 long & 4 shortyl hollow ball connectors (18)/ ball screws (2) 2742X Rod ends, short (6)/ hollow balls (6) 2742X Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock shaffs, hardened steel, titanium nitride coated (long) (2) Shock shaffs, hardened steel, titanium nitride coated (xx-long) (2) Shock shaffs, steel, chrome finish (long) (2) Shock shaffs, steel, chrome finish (long) (2) Shock shaffs, steel, chrome finish (xx-long) (2) Shock shaffs, steel, chrome finish (long) (2) Shock shaffs, steel, chrome finish (xx-long) (2) Shock shaffs, steel, chrome finish (long) (2) Shock spage (1) (1) (2) (2) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3	io (2)/ opidor godio (2)/
Rebuild kit, Ultra shocks (for 2 shocks) 1942 Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) 2742X Rod ends, short (6)/ hollow balls (6) 2742K Rod ends, short (6)/ hollow balls (6) 3766A Shock shafts, steel, chrome finish (long) (2) 2755 Shock shafts, steel, chrome finish (long) (2) 2756 Shock shafts, steel, chrome finish (long) (2) 2757 Shock shafts, steel, chrome finish (long) (2) 2758 Shock shafts, steel, chrome finish (long) (2) 2759 Shock shafts, steel, chrome finish (long) (2) 2750 Shock shafts, steel, chrome finish (long) (2) 2750 Shock shafts, steel, chrome finish (long) (2) 2750 Shock shafts, steel, chrome finish (long) (2) 2751 Shock shafts, steel, chrome finish (long) (2) 2752 Shock shafts, steel, chrome finish (xx-long) (2) 2753 Silicone daphragms (4) 2755 Silicone daphragms (4) 2756 Silicone daphragms (4) 2766 Silicone shock oil (30 wt) 2766 Silicone shock oil (30 wt) 2766 Silicone shock oil (30 wt) 2767 Springs, front (progressive, +10% rate, prink) (2) 2768 Springs, front (progressive, +10% rate, prink) (2) 2769 Springs, rear (progressive, +10% rate, prink) (2) 2769 Springs, rear (progressive, +10% rate, prink) (2) 2770 Springs, rear (progressive, +10% rate, prink) (2) 2771 Springs (2) 2772 Springs, rear (progressive, +10% rate, prink)	cets (2)/ ring gear gasket/
Rod ends (16 long & 4 short) hollow ball connectors (18)/ ball screws (2) Rod ends, short (6)/ hollow balls (6) Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (tong) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Shilicone shock oil (30 wt) Spring retainers, upper & lower (2)/ spring pre-load spacers: Imm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, +10% rate, pink) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, +20% rate, orange) (2) Springs, rear (progressive, +0% rate, blue) (2)	
screws (2) Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2) Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (long) (2) Silicone diaphragms (4) Silicone shock oil (30 wt) Spring retainers, upper & lower (2)/ spring pre-load spacers: Imm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, +20% rate, orange) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, -20% rate, blue) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (progressive, -20% rate, blue) (2) Springs, rear (progressive, -20% rate, blue) (2) Springs, rear (progressive, -20% rate, pink) (2) Springs, rear (progressive, -10% rate, pink) (2) Springs, rear (progressive, -20% rate, orange) (2) S	
2742X Rod ends, short (6)/ hollow balls (6) 2667 Shock caps, aluminum (Big Bore Shocks) (2) 26567 Shock shafts, hardened steel, titanium nitride coated (long) (2) 26567 Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) 26568 Shock shafts, steel, chrome finish (long) (2) 2656 Shock shafts, steel, chrome finish (xx-long) (2) 2658 Spice shock oil (30 wt) 2668 Spiring retainers, upper & lower (2)/ spring pre-load spacers: 1 mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore 2 Shocks) 2 Springs, front (progressive, +10% rate, pink) (2) 2 Springs, front (progressive, +10% rate, pink) (2) 2 Springs, rear (progressive, +10% rate, pink) (2) 2 Springs, rear (progressive, +20% rate, blue) (2) 2 Springs, rear (progressive, +20% rate, pink) (2) 2 Springs, rear (progressive, +20% rate, pink) (2) 2 Springs, rear (progressive, -20% rate, orange) (2) 3 Springs, rear (progressive, -20% rate, orange) (2) 3 Springs, rear (progressive, -20% rate, orange) (2) 3 Springs, rear (progressive, orange) (2) 3 Springs, rear (progressive, orange) (2) 3 Springs, rear (progressive, o	
Shock caps, aluminum (Big Bore Shocks) (2) Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone shock oil (30 wt) Spring retainers, upper & lower (2)/ spring pre-load spacers: Imm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, front (progressive, +20% rate, blue) (2) Springs, front (progressive, -20% rate, orange) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, -10% rate, pink) (2) Springs, rear (progressive, -20% rate, blue) (2) Springs, rear (progressive, -10% rate, pink) (2) Springs, rear (progressive, -20% rate, blue) (2) Springs, rear (progressive, -10% rate, pink) (2) Springs, rear (progressive, -20% rate, blue) (2) Springs, rear (progressive, -10% rate, pink) (2) Springs, rear (progressive, -10% rate, pink) (2) Springs, rear (progressive, -10% rate, pink) (2) Springs, rear (progressive, -20% rate, blue) (2) Springs, rear (progressive, -10% rate, pink) (2) Springs, rear (progressive, -20% rate, blue) (2) Springs, rear (progressive, -10% rate, pink) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (progressive, -20% rate, orange)	
Shock shafts, hardened steel, titanium nitride coated (long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Spriing retainers, upper show (2)/ spring pre-load spacers: 15552 Springs prear plate & hub (alluminum alloy) Slipper pressure plate & hub (alluminum alloy) Slipper pluta, complete Slipper clutch, complete Slipper clutch,	
255T Shock shafts, hardened steel, titanium nitride coated (xx-long) (2) 2656 Shock shafts, steel, chrome finish (long) (2) 2656 Shock shafts, steel, chrome finish (xx-long) (2) 2658 Silicone diaphragms (4) 2668 Silicone shock oil (30 wt) 2668 Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore 2664 Springs, front (progressive, +10% rate, pink) (2) 2665 Springs, front (progressive, +20% rate, blue) (2) 2666 Springs, front (progressive, -0% rate, pink) (2) 2667 Springs, front (progressive, -0% rate, pink) (2) 2668 Springs, rear (progressive, +20% rate, pink) (2) 2669 Springs, rear (progressive, +20% rate, pink) (2) 2660 Spr	iction pads (3)/ spring (2)/
Section Springs Foot (progressive 10% rate, pink) (2) Spring	
4. 0mm NL (1) 5.0mm NL (1)) Screws, 3x6mm cap-head machine (hex drive) (6 Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Silicone shock oil (30 wt) Silipor clutch, complete Slipper pressure plate & hub (aluminum alloy) Silipper pressure plate & hub (aluminum alloy) Silipper pressure plate and hub (alloy) Silipper pressure plate and hub (alloy) Silipper pressure plate & hub (aluminum alloy) Silipper pressure plate and hub (alloy) Silipper pressure plate & hub (aluminum alloy) Silipper pressure plate & hub (aluminum (aluminum alloy) Silipper pressure plate & hub (aluminum (balte slipper pressure plate & hub (aluminum (balte slipper pres	
Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4) Silicone shock oil (30 wt) Spring retainers, upper & lower (2)/ spring pre-load spacers: Imm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, +20% rate, blue) (2) Springs, front (progressive, -10% rate, pink) (2) Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, +10% rate, pink) (2) Springs, front (white) (progressive rate) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, -20% rate, pink) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (white) (progressive rate) (2) Springs, rear (wre retainer Spur gear, 52-tooth (0.8 metric pitch, compatible spur gear, 52-tooth (0.8 metric pitch, compatible spur gear, 54-tooth (0.8 metric pitch, compatible spur	
Silicone diaphragms (4) 1666 Silicone shock oil (30 wt) 2668 Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) 6863 Springs, front (progressive, +10% rate, pink) (2) 6864 Springs, front (progressive, +20% rate, blue) (2) 6865 Springs, front (progressive, -20% rate, orange) (2) 6866 Springs, front (progressive, -20% rate, orange) (2) 6867 Springs, front (progressive, -20% rate, orange) (2) 6868 Springs, rear (progressive, +10% rate, pink) (2) 6868 Springs, rear (progressive, +20% rate, blue) (2) 6868 Springs, rear (progressive, +20% rate, blue) (2) 6866 Springs, rear (progressive, +20% rate, pink) (2) 6866 Springs, rear (progressive, -20% rate, orange) (2) 6867 Springs, rear (progressive, -20% rate, pink) (2) 6868 Springs, rear (progressive, -20% rate, pink) (2) 6869 Springs, rear (progressive, -20% rate, pink) (2) 6860 Springs, rear (progressive, -20% rate, pink) (2) 6861 Springs, rear (progressive, -20% rate, pink) (2) 6862 Springs, rear (progressive, -20% rate, pink) (2) 6863 Springs, rear (progressive, -20% rate, pink) (2) 6864 Springs, rear (progressive, -20% rate, pink) (2) 6865 Springs, rear (progressive, -20% rate, pink) (2) 6866 Springs, rear (progressive, -20% rate, pink) (2) 6867 Springs, rear (progressive, -20% rate, orange) (2) 6868 Springs, rear (progressive, -20% rate, orange) (2) 6869 Springs, rear (progressive, -20% rate, orange) (2) 6860 Springs, rear (progressive, -20% rate, orange) (2) 6861 Springs, rear (progressive, -20% rate, orange) (2) 6862 Springs, rear (progressive, -20% rate, orange) (2) 6863 Springs, rear (progressive, -20% rate, orange) (2) 6864 Springs, rear (progressive, -20% rate, orange) (2) 6865 Springs, rear (progressive, -20% rate, orange) (2) 6866 Springs, rear (progressive, -20% rate, orange) (2) 6867 Springs, rear (progressive, -20% rate, orange) (2) 6868 Springs, rear (progressive, -20% rate, orange) (2) 6869 Springs, rear (progressive, -20% rate, orange) (2) 6860 Springs, rear (progressive, -20%	rive) (6)
Silicone shock oil (30 wt) Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, +20% rate, blue) (2) Springs, front (progressive, +20% rate, blue) (2) Springs, front (progressive, -10% rate, green) (2) Springs, front (white) (progressive, -20% rate, blue) (2) Springs, front (white) (progressive, +10% rate, pink) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, +20% rate, pink) (2) Springs, rear (progressive, -20% rate, blue) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (white) (progressive rate) (2) Springs, rear (brodressive, -10% rate, pink) (2) Springs, rear (progressive, -20% rate, prem) (2) Springs, rear (progressive, -10% rate, prem) (2) Springs, front (progressive, -10% rate, prem) (2) Springs, front (white) (progressive, -10% rate, prem) (2) Springs, front (white) (progressive, -10% rate, prem)	, , ,
Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) 6863 Springs, front (progressive, +10% rate, pink) (2) 6864 Springs, front (progressive, +20% rate, blue) (2) 6862 Springs, front (progressive, -10% rate, green) (2) 6861 Springs, front (progressive, -20% rate, orange) (2) 6867 Springs, front (white) (progressive rate) (2) 6868 Springs, rear (progressive, +10% rate, pink) (2) 6868 Springs, rear (progressive, +20% rate, blue) (2) 6869 Springs, rear (progressive, +20% rate, pink) (2) 6860 Springs, rear (progressive, -10% rate, green) (2) 6861 Springs, rear (progressive, -20% rate, orange) (2) 6862 Springs, rear (progressive, -20% rate, orange) (2) 6863 Springs, rear (progressive, -20% rate, orange) (2) 6864 Springs, rear (white) (progressive rate) (2) 6865 Springs, rear (white) (progressive rate) (2) 6866 Springs, rear (white) (progressive rate) (2) 6867 Springs, rear (progressive, -20% rate, orange) (2) 6868 Springs, rear (progressive, -20% rate, orange) (2) 6869 Springs, rear (progressive, -20% rate, orange) (2) 6870 Springs, rear (white) (progressive rate) (2) 6870 Springs, rear (white) (progressive rate) (2) 6871 Silper pressure plate and hub (alloy) 68842 Spur gear, 50-tooth (0.8 metric pitch, compatiin (for center differential) 68842 Spur gear, 50-tooth (0.8 metric pitch, compatiin (for center differential) 68843 Spur gear, 52-tooth (0.8 metric pitch, compatiin (for center differential) 68843 Spur gear, 52-tooth (0.8 metric pitch, compatiin (for center differential) 68843 Spur gear, 52-tooth (0.8 metric pitch, compatiin (for center differential) 68843 Spur gear, 52-tooth (0.8 metric pitch, compatiin (for center differential) 68844 Spur gear, 52-tooth (0.8 metric pitch, compatiin (for center differential) 68845 Spur gear, 52-tooth (0.8 metric pitch, compatiin (for center differential) 68845 Spur gear, 52-tooth (0.8 metric pitch, compatiin (for center differential) 68845 Spur gear, 52-tooth (0.8 metric pitch, compatiin (for center dif	loy)
1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks) 7477 Cover, gear/ wire retainer 6863 Springs, front (progressive, +10% rate, pink) (2) 6864 Springs, front (progressive, +20% rate, blue) (2) 6865 Springs, front (progressive, -10% rate, green) (2) 6866 Springs, front (progressive, -20% rate, orange) (2) 6867 Springs, rear (progressive, +10% rate, pink) (2) 6868 Springs, rear (progressive, +20% rate, blue) (2) 6869 Springs, rear (progressive, +20% rate, blue) (2) 6860 Springs, rear (progressive, +20% rate, blue) (2) 6861 Springs, rear (progressive, +20% rate, blue) (2) 6862 Springs, rear (progressive, +20% rate, blue) (2) 6863 Springs, rear (progressive, +20% rate, blue) (2) 6864 Springs, rear (progressive, +20% rate, blue) (2) 6865 Springs, rear (progressive, -20% rate, orange) (2) 6866 Springs, rear (progressive, -20% rate, orange) (2) 6867 Springs, rear (progressive, +20% rate, blue) (2) 6868 Springs, rear (progressive, -20% rate, orange) (2) 6869 Springs, rear (progressive, -20% rate, orange) (2) 6869 Springs, rear (progressive, -20% rate, orange) (2) 6860 Springs, rear (progressive, -20% rate, orange) (2) 6861 Springs, rear (progressive, -20% rate, blue) (2) 6862 Springs, rear (progressive, -20% rate, orange) (2) 6863 Springs, rear (progressive, -20% rate, orange) (2) 6864 Springs, rear (progressive, -20% rate, orange) (2) 6865 Springs, rear (progressive, -20% rate, orange) (2) 6866 Springs, rear (progressive, -20% rate, orange) (2) 6867 Springs, rear (progressive, -20% rate, orange) (2) 6868 Springs, rear (progressive, -20% rate, orange) (2) 6869 Springs, rear (progressive, -20% rate, orange) (2) 6869 Springs, rear (progressive, -20% rate, orange) (2) 6860 Springs, rear (progressive, -20% rate, orange) (2) 6861 Springs, rear (progressive, -20% rate, orange) (2) 6862 Springs, rear (progressive, -20% rate, orange) (2) 6865 Springs, rear (progressive, -20% rate, orange) (2) 6866 Springs, rear (progressive, -20% rate, orange) (2) 6867 Springs, rear (progressive, -20% rate, orange) (2) 6868 Sprin	
Shocks) Springs, front (progressive, +10% rate, pink) (2) 6864 Springs, front (progressive, +20% rate, blue) (2) 6862 Springs, front (progressive, -10% rate, green) (2) 6861 Springs, front (progressive, -20% rate, orange) (2) 6867 Springs, front (white) (progressive rate) (2) 6868 Springs, rear (progressive, +10% rate, pink) (2) 6868 Springs, rear (progressive, -10% rate, pink) (2) 6866 Springs, rear (progressive, -10% rate, pink) (2) 6865 Springs, rear (progressive, -10% rate, pink) (2) 6866 Springs, rear (progressive, -20% rate, blue) (2) 6858 Springs, rear (progressive, -20% rate, orange) (2) 6858 Springs, rear (progressive, -20% rate, orange) (2) 6859 Springs, rear (progressive, -20% rate, orange) (2) 6850 Springs, rear (progressive, -20% rate, orange) (2) 6851 Springs, rear (progressive, -20% rate, orange) (2) 6852 Springs, rear (progressive, -20% rate, orange) (2) 6853 Springs, rear (white) (progressive rate) (2) 6854 Springs, rear (progressive, -20% rate, orange) (2) 6856 Springs, rear (progressive, -20% rate, orange) (2) 6857 Springs, rear (progressive, -10% rate, pink) (2) 6868 Springs, rear (progressive, -10% rate, green) (2) 6869 Springs, rear (progressive, -20% rate, orange) (2) 6870 Springs, rear (progressive, -20% rate, pink) (2) 6870 Springs, rear (progressi	aare
Springs, front (progressive, +10% rate, pink) (2) Springs, front (progressive, +20% rate, blue) (2) Springs, front (progressive, -10% rate, green) (2) Springs, front (progressive, -10% rate, green) (2) Springs, front (white) (progressive rate) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, -10% rate, green) (2) Springs, rear (progressive, -20% rate, blue) (2) Springs, rear (white) (progressive rate) (2) Springs, rear (white) (progressive, -20% rate, prean) (2) Springs, rear (progressive, -10% rate, prean) (2) Springs, rear (progressive, -10% rate, prean) (2) Springs, rear (progressive, -10% rate, prean)	5a13
Springs, front (progressive, +20% rate, blue) (2) Springs, front (progressive, -10% rate, green) (2) Springs, front (progressive, -20% rate, orange) (2) Springs, front (progressive, -20% rate, orange) (2) Springs, front (white) (progressive rate) (2) Springs, front (white) (progressive rate) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, +20% rate, pink) (2) Springs, rear (progressive, +20% rate, pink) (2) Springs, rear (progressive, -10% rate, green) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (white) (progressive rate) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (progressive, -20% rate, orange) (2) Spur gear, 52-tooth (0.8 metric pitch, compatiin (for center differential) Spur gear, 52-tooth (0.8 metric pitch, compatiin (for center differential) Spur gear, 52-tooth (0.8 metric pitch, compatiin (for center differential) Spur gear, 52-tooth (0.8 metric pitch, compatiin (for center differential) Spur gear, 52-tooth (0.8 metric pitch, compatiin (for center differential) Spur gear, 52-tooth (0.8 metric pitch, compatiin (for center differential) Spur gear, 52-tooth (0.8 metric pitch, compatiin (for center differential) Spur gear, 52-tooth (0.8 metric pitch, compatiin (for center differential) Spur gear, 52-tooth (0.8 metric pitch, compatiin (for center differential) Spur gear, 52-tooth (0.8 metric pitch, compatiin (for center differential) Spur gear, 52-tooth (0.8 metric pitch, compatiin (for center differential) Spur gear, 52-tooth (0.8 metric pitch, compatiin (for center differential)	
Springs, front (progressive, -10% rate, green) (2) 6861 Springs, front (progressive, -20% rate, orange) (2) 6862 Springs, front (white) (progressive rate) (2) 6863 Springs, rear (progressive, +10% rate, pink) (2) 6864 Springs, rear (progressive, +20% rate, blue) (2) 6865 Springs, rear (progressive, -10% rate, green) (2) 6866 Springs, rear (progressive, -20% rate, orange) (2) 6865 Springs, rear (progressive, -20% rate, orange) (2) 6866 Springs, rear (progressive, -20% rate, orange) (2) 6867 Springs, rear (progressive, -20% rate, blue) (2) 6868 Springs, rear (progressive, -20% rate, orange) (2) 6869 Springs, rear (progressive, -20% rate, orange) (2) 6860 Springs, rear (white) (progressive rate) (2) 6860 Springs, rear (progressive, -20% rate, orange) (2) 6861 Springs, rear (progressive, -20% rate, orange) (2) 6862 Springs, rear (progressive, -20% rate, orange) (2) 6863 Springs, rear (progressive, -20% rate, orange) (2) 6865 Springs, rear (progressive, -20% rate, orange) (2) 6866 Springs, rear (progressive, -20% rate, orange) (2) 6867 Springs, rear (progressive, -20% rate, progressive, -20% rate, orange) (2) 6868 Springs, rear (progressive, -20% rate, orange) (2) 6869 Springs, rear (progressive, -20% rate, orange) (2) 6869 Springs, rear (progressive, -20% rate, orange) (2) 6860 Springs, rear (progressive, -20% rate, orange) (2) 6860 Springs, rear (progressive, -20% rate, orange) (2) 6861 Springs, rear (progressive, -20% rate, orange) (2) 6862 Springs, rear (progressive, -20% rate, orange) (2) 6863 Springs, rear (progressive, -20% rate, orange) (2) 6865 Springs, rear (progressive, -20% rate, orange) (2) 6866 Springs, fotal (0.8 metric pitch, compatible Spur gear, 52-tooth (0.8 metric pitch, compatible Spur gear, 54-tooth (0.8 metric pitch, co	
Springs, front (progressive, -20% rate, orange) (2) Springs, front (white) (progressive rate) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, -10% rate, green) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (white) (progressive rate) (2) Spur gear, 52-tooth (0.8 metric pitch, compatiin (for center differential) Spur gear, 52-tooth (0.8 metric pitch, compatiin (progressive with progressive spears, 54-tooth (0.8 metric pitch, compatiin (requires #6814 center differential) Spur gear, 52-tooth (0.8 metric pitch, compatiin (progressive with progressive spears, 54-tooth (0.8 metric pitch, compatiin (requires #6814 center differential) Spur gear, 52-tooth (0.8 metric pitch, compatiin (progressive with progressive with progr	mpatible with 32-pitch)
Springs, front (white) (progressive rate) (2) Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, -10% rate, green) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (white) (progressive rate) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (progressive, -20% rate, blue) (2) Springs, rear (progressive, -20% rate, blue) (2) Spur gear, 52-tooth (0.8 metric pitch, compatiin (for center differential) Spur gear, 54-tooth (0.8 metric pitch, compatiin (progressive, -20% rate, orange) (2) Spur gear, 54-tooth (0.8 metric pitch, compatiin (progressive, -20% rate, orange) (2) Spur gear, 54-tooth (0.8 metric pitch, compatiin (progressive, -20% rate, orange) (2) Spur gear, 54-tooth (0.8 metric pitch, compatiin (progressive, -20% rate, orange) (2) Spur gear, 54-tooth (0.8 metric pitch, compatiin (progressive, -20% rate, orange) (2) Spur gear, 54-tooth (0.8 metric pitch, compatiin (progressive, -20% rate, orange) (2) Spur gear, 54-tooth (0.8 metric pitch, compatiin (progressive, -20% rate, orange) (2) Spur gear, 54-tooth (0.8 metric pitch, compatiin (progressive, -20% rate, orange) (2) Spur gear, 54-tooth (0.8 metric pitch, compatiin (progressive, -20% rate, orange) (2) Spur gear, 54-tooth (0.8 metric pitch, compatiin (progressive, -20% rate, orange) (2) Spur gear, 54-tooth (0.8 metric pitch, compatiin (progressive, -20% rate	
Springs, rear (progressive, +10% rate, pink) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, -10% rate, green) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (white) (progressive rate) (2) Spur gear, 54-tooth (0.8 metric pitch, compatitive requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatitive requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatitive requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatitive requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatitive requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatitive requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatitive requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatitive requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatitive requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatitive requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatitive requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatitive requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatitive requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatitive requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatitive requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatitive requires #6814 center differential) Spur gear,	
Springs, rear (progressive, +20% rate, blue) (2) Springs, rear (progressive, -10% rate, green) (2) Springs, rear (progressive, -10% rate, green) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (white) (progressive rate) (2) Spur gear, 54-tooth (0.8 metric pitch, compatility (requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatility (requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatility (requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatility (requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatility (requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatility (requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatility (requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatility (requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatility (requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatility (requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatility (requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatility (requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatility (requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatility (requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatility (requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatility (requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compatility (requires #6814 center differential) S	mpatible with 32-pitch)
Springs, rear (progressive, -10% rate, green) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (white) (progressive rate) (2) Springs, rear (white) (progressive rate) (2) Springs, rear (white) (progressive rate) (2) Springs, rear (white) (progressive rate) (2) Springs, rear (white) (progressive rate) (2) Springs, rear (white) (progressive rate) (2) Springs, rear (white) (progressive rate) (2) Springs, rear (white) (progressive rate) (2) Springs, rear (progressive, -10% rate, green) (2) Springs, rear (progressive, -10% rate, green) (2) Springs, rear (progressive, -10% rate, green) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, fear (progressive, -20% rate, orange) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (white) (0.8 metric pitch, compation (requires #6814 center differential) Spur gear, 54-tooth (0.8 metric pitch, compation (progressive fate) (5 % spur gear, 54-tooth (0.8 metric pitch, compation (progressive fate) (5 % spur gear, 54-tooth (0.8 metric pitch, compation (progressive fate) (5 % spur gear, 54-tooth (0.8 metric pitch, compation (progressive fate) (5 % spur gear, 54-tooth (0.8 metric pitch, compation (progressive fate) (5 % spur gear, 54-tooth (0.8 metric pitch, compation (progressive fate) (5 % spur gear, 54-tooth (0.8 metric pitch, compation (progressive fate) (5 % spur gear, 54-tooth (0.8 metric pitch, compation (progressive fate) (5 % spur gear, 54-tooth (0.8 metric pitch, compation (progressive fate) (5 % sp	
Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (white) (progressive rate) (2) Springs, rear (progressive, -20% rate, orange) (2) Springs, s-toto (b.5 metric pitch, compand (progressive rate) (2) Spur gear, steel, 54-tooth (0.8 metric pitch, compitch) (requires #6814 center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compitch) (requires #6814 center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compitch) (requires #6780 center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compitch) (requires #6780 center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compitch) (requires #6814 center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compitch) (requires #6814 center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compitch) (requires #6814 center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compitch) (requires #6780 center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compitch) (requires #6780 center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compitch) (for pitch) (requires #6780 center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compitch) (for pitch) (fo	
Springs, rear (white) (progressive rate) (2) Singlis (Uira Singlis) 3642 Attachment screws, shock (3x12mm shoulder screws) (6) 3765A Body, Ultra Shock(s) (long) (grey) (2) 3766A Body, Ultra Shock(s) (XXL) (grey) (2) 2362 Rebuild kit, Ultra shocks (for 2 shocks) 1552 Screws, 3x8mm cap-head machine (hex drive) (6 wrench 2728 Ball bearings (5x8x2.5mm) (2) 1942 Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) 2742X Rod ends, short (6)/ hollow balls (6) 3767 Shock caps (2)/ shock bottoms (2) 3956X Spur gear, steel, 54-tooth (0.8 metric pitch, copitch) (requires #6780 center differential) 3956X Spur gear, steel, 54-tooth (0.8 metric pitch, copitch) (requires #6780 center differential) 3956X Spur gear, steel, 54-tooth (0.8 metric pitch, copitch) (requires #6780 center differential) 3956X Spur gear, steel, 54-tooth (0.8 metric pitch, copitch) (requires #6780 center differential) 3956X Spur gear, steel, 54-tooth (0.8 metric pitch, copitch) (requires #6780 center differential) 3956X Spur gear, steel, 54-tooth (0.8 metric pitch, copitch) (requires #6780 center differential) 3956X Spur gear, steel, 54-tooth (0.8 metric pitch, copitch) (requires #6780 center differential) 3956X Spur gear, steel, 54-tooth (0.8 metric pitch, copitch) (requires #6780 center differential) 3956X Spur gear, steel, 54-tooth (0.8 metric pitch, copitch) (requires #6780 center differential) 3956X Spur gear, steel, 54-tooth (0.8 metric pitch, copitch) (requires #6780 center differential) 3956X Spur gear, steel, 54-tooth (0.8 metric pitch, copitch) (requires #6780 center differential)	impatible with 32-pitch)
Singlis (Uitra Singlis) 3642 Attachment screws, shock (3x12mm shoulder screws) (6) 3765A Body, Ultra Shock(s) (long) (grey) (2) 3766A Body, Ultra Shock(s) (XXL) (grey) (2) 3766A Body, Ultra Shocks (for 2 shocks) 3767 Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) 2742X Rod ends, short (6)/ hollow balls (6) 3767 Shock caps (2)/ shock bottoms (2) Screws, (3x8mm cap-head machine (hex drive) (6 wrench 3768 Ball bearings (5x8x2.5mm) (2) Ball bearings, blue rubber sealed (5x8x2.5mm) (2) 6845A Drag link, machined 6061-T6 aluminum (blue-link) 5768 Ball bearings, blue rubber sealed (5x8x2.5mm) (2) 5769 Ball bearings, blue rubber sealed (5x8x2.5mm) (2) 5769 Ball bearings, blue rubber sealed (5x8x2.5mm) (2) 5769 Ball bearings, blue rubber sealed (5x8x2.5mm) (2) 5760 Ball bearings, blue rubber sealed (5x8x2.5mm) (2)	toh competible with 00
Attachment screws, shock (3x12mm shoulder screws) (6) 3765A Body, Ultra Shock(s) (long) (grey) (2) 3766A Body, Ultra Shock(s) (XXL) (grey) (2) 3766A Body, Ultra Shock(s) (XXL) (grey) (2) 3766A Rebuild kit, Ultra shocks (for 2 shocks) 1942 Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) 2742X Rod ends, short (6)/ hollow balls (6) 3767 Shock caps (2)/ shock bottoms (2) Attachment screws, shock (3x12mm shoulder screws) (6) 1552 Screws, 3x8mm cap-head machine (hex drive) (6 wrench 8 Ball bearings (5x8x2.5mm) (2) 6845A Drag link, machined 6061-T6 aluminum (green strength) 1552 Screws, 3x8mm cap-head machine (hex drive) (6 wrench 8 Ball bearings, blue rubber sealed (5x8x2.5mm) (2) 1552 Screws, 3x8mm cap-head machine (hex drive) (6 wrench 8 Body, Ultra Shock(s) (XXL) (grey) (2) 8 Ball bearings, blue rubber sealed (5x8x2.5mm) (2) 1552 Screws, 3x8mm cap-head machine (hex drive) (6 wrench 8 Ball bearings, blue rubber sealed (5x8x2.5mm) (2) 1552 Screws, 3x8mm cap-head machine (hex drive) (6 wrench 8 Ball bearings, blue rubber sealed (5x8x2.5mm) (2) 1552 Screws, 3x8mm cap-head machine (hex drive) (6 wrench 8 Ball bearings, blue rubber sealed (5x8x2.5mm) (2) 1552 Screws, 3x8mm cap-head machine (hex drive) (6 wrench 8 Ball bearings, blue rubber sealed (5x8x2.5mm) (2) 1552 Screws, 3x8mm cap-head machine (hex drive) (6 wrench 8 Ball bearings, blue rubber sealed (5x8x2.5mm) (2) 1552 Screws, 3x8mm cap-head machine (hex drive) (6 wrench 8 Ball bearings, blue rubber sealed (5x8x2.5mm) (2) 1552 Screws, 3x8mm cap-head machine (hex drive) (6 wrench 8 Ball bearings, blue rubber sealed (5x8x2.5mm) (2) 1552 Screws, 3x8mm cap-head machine (hex drive) (6 wrench 8 Ball bearings, blue rubber sealed (5x8x2.5mm) (2) 1552 Screws, 3x8mm cap-head machine (hex drive) (6 wrench 8 Ball bearings, blue rubber sealed (5x8x2.5mm) (2) 1552 Screws, 3x8mm cap-head machine (blue-like) (5x8x2.5mm) (2)	
3765A Body, Ultra Shock(s) (long) (grey) (2) 3766A Body, Ultra Shock(s) (XXL) (grey) (2) 3766A Body, Ultra Shock(s) (XXL) (grey) (2) 3766 Rebuild kit, Ultra shocks (for 2 shocks) 3762 Rebuild kit, Ultra shocks (for 2 shocks) 3763 Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) 3764 Rod ends, short (6)/ hollow balls (6) 3767 Shock caps (2)/ shock bottoms (2) 3765 Shock caps (2)/ shock bottoms (2) 3766 Rod ends, short (6)/ hollow balls (6) 3767 Shock caps (2)/ shock bottoms (2) 3768 Screws, 3x8mm cap-head machine (hex drive) (6 wrench 3768 Ball bearings (5x8x2.5mm) (2) 3768 Ball bearings, blue rubber sealed (5x8x2.5mm) (2) 3768 Drag link, machined 6061-T6 aluminum (green cap-head machine (hex drive) (6 wrench 3768 Ball bearings, blue rubber sealed (5x8x2.5mm) (2) 3768 Drag link, machined 6061-T6 aluminum (green cap-head machine (hex drive) (6 wrench 3768 Ball bearings, blue rubber sealed (5x8x2.5mm) (2) 3768 Drag link, machined 6061-T6 aluminum (green cap-head machine (hex drive) (6 wrench 3768 Ball bearings, blue rubber sealed (5x8x2.5mm) (2) 3768 Drag link, machined 6061-T6 aluminum (green cap-head machine (hex drive) (6	
3765A Body, Ultra Shock(s) (long) (grey) (2) 3766A Body, Ultra Shock(s) (XXL) (grey) (2) 3766A Body, Ultra Shock(s) (XXL) (grey) (2) 3766 Rebuild kit, Ultra shocks (for 2 shocks) 3762 Reduild kit, Ultra shocks (for 2 shocks) 3763 Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) 3764 Rod ends, short (6)/ hollow balls (6) 3767 Shock caps (2)/ shock bottoms (2) 3768 Ball bearings (5x8x2.5mm) (2) 3769 Ball bearings, blue rubber sealed (5x8x2.5mm) (2) 3760 Drag link, machined 6061-T6 aluminum (green control of the contr	S
3766A Body, Ultra Shock(s) (XXL) (grey) (2) Rebuild kit, Ultra shocks (for 2 shocks) Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) Rod ends, short (6)/ hollow balls (6) Rod ends, short (6)/ hollow balls (6) Shock caps (2)/ shock bottoms (2) Wrench Ball bearings (5x8x2.5mm) (2) Ball bearings, blue rubber sealed (5x8x2.5mm) (2) Ball bearings, blue rubber sealed (5x8x2.5mm) (2) Drag link, machined 6061-T6 aluminum (green ball) Drag link, machined 6061-T6 aluminum (orangen ball)	
2362 Rebuild kit, Ultra shocks (for 2 shocks) 1942 Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) 2742X Rod ends, short (6)/ hollow balls (6) 3767 Shock caps (2)/ shock bottoms (2) 278 Ball bearings (5x8x2.5mm) (2) 5114 Ball bearings, blue rubber sealed (5x8x2.5mm) (2) 6845A Drag link, machined 6061-T6 aluminum (green based) 6845G Drag link, machined 6061-T6 aluminum (green based) 6845T Drag link, machined 6061-T6 aluminum (orange)	, (· ,· · · · · · · · · · · · · · · · ·
1942 Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2) 2742X Rod ends, short (6)/ hollow balls (6) 3767 Shock caps (2)/ shock bottoms (2) Rod ends, short (6)/ hollow balls (6) 3767 Shock caps (2)/ shock bottoms (2) Ball bearings, blue rubber sealed (5x8x2.5mm) (2 Ball bearings, blue rubber sealed (5x8x2.5mm) (2 Drag link, machined 6061-T6 aluminum (green based) Drag link, machined 6061-T6 aluminum (orange)	
screws (2) 6845A Drag link, machined 6061-T6 aluminum (blue- 2742X Rod ends, short (6)/ hollow balls (6) 6845G Drag link, machined 6061-T6 aluminum (green 3767 Shock caps (2)/ shock bottoms (2) 6845T Drag link, machined 6061-T6 aluminum (orang	imm) (2)
2742X Rod ends, short (6)/ hollow balls (6) 6845G Drag link, machined 6061-T6 aluminum (green 3767 Shock caps (2)/ shock bottoms (2) 6845T Drag link, machined 6061-T6 aluminum (orang	, , ,
3767 Shock caps (2)/ shock bottoms (2) 6845T Drag link, machined 6061-T6 aluminum (orang	,
	,
3767G Shock caps, aluminum (green-anodized) (4) (fits all Ultra Shocks) 7438 Linkage, steering	,
2742 Rod ends, long (6)/ hollow ball connectors (6)	(6)
3767P Shock caps, aluminum (pink-anodized) (4) (fits all Ultra Shocks) 6845X Steering bellcranks/ servo saver/ servo saver spr	. ,
3767X Shock caps, aluminum (red-anodized) (4) (fits all Ultra Shocks) retainer/servo horn, steering	. s. spinig, serve spinig
1664T Shock shafts, hardened steel, titanium nitride coated (long) (2) 6742X Toe links (TUBES blue-anodized, 7075-T6 alur	T6 aluminum. stronger
2656T Shock shafts, hardened steel, titanium nitride coated (xx-long) than titanium) (87mm) (2)/ rod ends (4)/ alumin	
(2) 6742G Toe links (TUBES green-anodized, 7075-T6 alu	
1664 Shock shafts, steel, chrome finish (long) (2) than titanium) (87mm) (2)/ rod ends (4)/ alumir	
2656 Shock shafts, steel, chrome finish (xx-long) (2) 6742R Toe links (TUBES red-anodized, 7075-T6 alum	
1765 Silicone diaphragms (4) than titanium) (87mm) (2)/ rod ends (4)/ alumir	
1666 Silicone shock oil (30 wt) 2746 Washers, 3x6mm metal (12)	` '
3769 Spring pre-load spacers: 1mm (4)/ 2mm (2)/ 4mm (2)	

Page 5 Slash 4X4 Platinum: Low CG-Chassis (Model 6804R) Parts List

	Suspension Linkage	1654X	Wheel hubs, hex (blue-anodized, lightweight aluminum) (2)/ axle
3643X	Camber links, front (TUBES blue-anodized, 7075-T6 aluminum,	6856X	pins(4) Wheel hubs, splined, 17mm, short (4)/ wheel nuts, splined, 17mm
	stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)		(4) (blue-anodized)/ hub retainer MÀ X 0.7 (4)/ axle pin (4)/ wrench, 5mm
3643G	Camber links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum	5353	Wheel nuts, splined, 17mm (blue-anodized) (4)
	wrench (1) (#2579 3x15 BCS (4) required for installation)	5480X 5868	Wheel wrench, splined, 17mm Wheels, SCT chrome, red beadlock style, dual profile (2.2" outer,
3643R	Camber links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum		3.0" inner) (4WD front/rear, 2WD rear only) (2)
2044V	wrench (1) (#2579 3x15 BCS (4) required for installation)	5872	Wheels, SCT satin chrome, beadlock style, dual profile (2.2" outer, 3.0" inner) (4WD front/rear, 2WD rear only)
3644X	Camber links, rear (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum	5872X	Wheels, SCT satin chrome, black beadlock style SCT, dual profile (2.2" outer, 3.0" inner) (4WD front/rear, 2WD rear only) (2)
3644G	wrench (1) (#2579 3x15 BCS (4) required for installation) Camber links, rear (TUBES green-anodized 7075-T6 aluminum,	5872A	Wheels, SCT satin chrome, red beadlock style, dual profile (2.2"
30440	stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum	5884	outer, 3.0" inner) (4WD front/rear, 2WD rear only) (2) Wheels, SCT Split-Spoke, black, satin chrome beadlock style,
3644R	wrench (1) (#2579 3x15 BCS (4) required for installation) Camber links, rear (TUBES red-anodized, 7075-T6 aluminum,		dual profile (2.2" outer, 3.0" inner) (4WD f/r, 2WD rear) (2)
	stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)	6872X	Wheels, SCT Split-Spoke, chrome, green beadlock style, dual profile (2.2" outer, 3.0" inner) (4WD front/rear, 2WD rear) (2)
5525	Rod ends (12)/ hollow balls (12)	6872A	Wheels, SCT Split-Spoke, chrome, red beadlock style, dual
3739	Screw pin set (Rustler®/ Bandit/ Stampede®)	6872	profile (2.2" outer, 3.0" inner) (4WD front/rear, 2WD rear) (2) Wheels, SCT Split-Spoke, satin chrome, black beadlock style,
6834 2537	Suspension pin set, complete (front and rear) Threaded rods (20/25/44mm 1 ea.)/ (1) 12mm set screw		dual profile (2.2" outer, 3.0" inner) (4WD front/rear, 2WD rear
3644	Turnbuckles, camber link, 39mm (69mm center to center) (assembled		only) (2)
	with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on		Traxxas Tools
3643	Slash) Turnbuckles, camber link, 49mm (82mm center to center) (assembled	3433X	Body reamer (aluminum handle)
3043	with rod ends and hollow balls) (1 left, 1 right)	3433 3436	Body reamer (plastic handle)
5539	Turnbuckles, camber links, 58mm (assembled with rod ends and	3436 3432	Cap, body reamer Scissors, curved tip
	hollow balls) (2)	3431	Scissors, straight tip
	Team Traxxas Items	8712	Speed Bit Essentials Set, hex and nut driver, 7-piece, includes
2514	Decal sheet, racing sponsors		premium handle (medium), travel pouch, hex drivers (straight:
6160X	DVD, Maxx® Power! Full Throttle Action (sleeve)		1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm, and 8.0mm), 1/4" drive
9950	Official Team Traxxas® racing decal set (flag logo/ 6-color)	8721	Speed bit handle, medium (one piece)
9909	Traxxas® racing banner, red & black (3x7 feet)	8720	Speed bit handle, premium, large (rubber overmold)
	Tires & Wheels	8722	Speed bit handle, premium, medium (rubber overmold)
5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)	8710	Speed Bit Master Set, hex and nut driver, 13-piece, includes
5854	Hub retainer, 17mm hubs, M4 X 0.7 (4) (use with #5853X, #6856X,		premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm), (ball-end: 2.0mm, 2.5mm,
3647	#6469)		3.0mm), and nut drivers (4.00mm, 4.50mm, 5.00mm, 5.50mm,
1985	Nuts, 4mm flanged nylon locking (steel, serrated) (8) PTFE-coated washers, 5x8x0.5mm (20) (use with ball bearings)		7.00mm, 8.00mm),
1647	Silicone grease	8711	Speed Bit Master Set, hex driver, 7-piece straight and ball end,
2754	Stub axle pins (4)		includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm,
5880X	Tires & wheels, assembled, glued (SCT satin chrome, beadlock		2.5mm, 3.0mm), 1/4" drive
	style wheels, Kumho tires, foam inserts) (2) (4WD front/rear, 2WD rear only)	8719	Speed Bit Master Set, nut driver, 6-piece, includes premium
6873X	Tires & wheels, assembled, glued (S1 ultra-soft off-road racing		handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive
	compound) (SCT Split-Spoke satin chrome, black beadlock style	8716	Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4"
	wheels, BFG Mud-Terrain tires, foam inserts) (2) (4WD front/rear, 2WD rear only)		drive
6874R	Tires & wheels, assembled, glued (S1 ultra-soft off-road racing	8716X	Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm, 3.0mm), 1/4" drive
	compound) (SCT Split-Spoke satin chrome, black beadlock style wheels, Kumho tires, foam inserts) (2) (4WD front/rear, 2WD rear	8715	Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm,
	only)	8715X	2.5mm), 1/4" drive Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm,
6873R	Tires & wheels, assembled, glued (S1 ultra-soft, off-road racing compound) (SCT Split-Spoke chrome, red beadlock style wheels,	07 10%	2.5mm, 3.0mm), 1/4" drive
	BFGoodrich® Mud-Terrain™ T/A® KM2 tires, foam inserts) (2) (4WD	3415	Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/ 4mm, 5mm, 5.5mm, 7mm and 8mm nut
5867	f/r, 2WD rear) Tires & wheels, assembled, glued (SCT chrome, red beadlock		drivers/ 2mm, 4mm, and 5mm slotted screwdrivers/ #00 Phillips,
3007	style wheels, BFGoodrich® Mud-Terrain™ T/A® KM2 tires, foam		#0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrench/ driver handle
5050B	inserts) (2)(4WD front/rear, 2WD rear only)		
5873R	Tires & wheels, assembled, glued (SCT satin chrome red beadlock wheels, ultra-soft S1 compound off-road racing tires,	20.427	Turnbuckles & Threaded Rods
	inserts) (2) (2WD rear, 4WD f/r)	3643X	Camber links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum
5878	Tires & wheels, assembled, glued (SCT satin chrome, black		wrench (1) (#2579 3x15 BCS (4) required for installation)
	beadlock style wheels, BFGoodrich® Mud-Terrain™ T/A® KM2 tires, foam inserts) (2)(4WD front/rear, 2WD rear only)	3643G	Camber links, front (TUBES green-anodized, 7075-T6 aluminum,
5873X	Tires & wheels, assembled, glued (SCT satin chrome, black		stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
	beadlock style wheels, SCT off-road racing tires, foam inserts)	3643R	Camber links, front (TUBES red-anodized, 7075-T6 aluminum,
E004	(2) (4WD front/rear, 2WD rear only)		stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum
5891	Tires & wheels, assembled, glued (SCT Split-Spoke satin chrome, beadlock style wheels, paddle tires, foam inserts) (2)	2644V	wrench (1) (#2579 3x15 BCS (4) required for installation)
	(4WD front/rear, 2WD rear only) (TSM rated)	3644X	Camber links, rear (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum
5883	Tires & wheels, assembled, glued (SCT Split-Spoke, black, satin		wrench (1) (#2579 3x15 BCS (4) required for installation)
	chrome beadlock wheels, BFGoodrich® Mud-Terrain™ T/A® KM2 tire, foam inserts) (2) (4WD f/r, 2WD rear)	3644G	Camber links, rear (TUBES green-anodized 7075-T6 aluminum,
6871R	KM2 tire, foam inserts) (2) (4WD f/r, 2WD rear) Tires, BFGoodrich® Mud-Terrain T/A® KM2 , ultra-soft (S1 off-		stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum
	road racing compound) (dual profile 4.3x1.7- 2.2/3.0") (2)/ foam	3644R	wrench (1) (#2579 3x15 BCS (4) required for installation) Camber links, rear (TUBES red-anodized, 7075-T6 aluminum,
	inserts (2)	00-7-TIX	stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum
5871R	Tires, ultra-soft, S1 compound for off-road racing, SCT dual		wrench (1) (#2579 3x15 BCS (4) required for installation)
1654	profile 4.3x1.7- 2.2/3.0" (2)/ foam inserts (2) Wheel hubs, hex (rear) (2)/ stub axle pins (2)	5525	Rod ends (12)/ hollow balls (12)
1007			

Page 6 Slash 4X4 Platinum: Low CG-Chassis (Model 6804R) Parts List

6742X	Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1)
6742G	Toe links (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1)
6742R	Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1)
3644	Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash)
3643	Turnbuckles, camber link, 49mm (82mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right)
5539	Turnbuckles, camber links, 58mm (assembled with rod ends and hollow balls) (2)

If you have questions or need technical assistance, call Traxxas at:



For orders, calls outside the U.S., and other information, call 972-549-3000, or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com

TRAXXAS.COM