

Hoss™ 4X4 VXL (Model 90076-4) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

	Bearings & Bushings	5381	Carrier, differential, x-ring gaskets (2)/ ring gear gasket/ 6x10x0.5 TW
4607	Ball bearings (5x11x4mm) (8)	6780A 6780	Center differential, complete (fits Hoss™ 4X4 VXL) Differential kit, center (complete)
4612	Ball bearings (10x15x4mm) (2)	5136X	Differential oil kit (1 each: 10K, 30K, 50K weights)
2728 5110A	Ball bearings (5x8x2.5mm) (2)	6788	Differential, front (complete with pinion gear and differential
5119A 5119	Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2)		plastics) (fits 1/10-scale 4X4 Slash, Stampede®, Rustler®, Rally)
5120	Ball bearings, blue rubber sealed (10x10x411111) (2)	6789	Differential, rear (complete with pinion gear and differential
5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)	6783	plastics) (fits 1/10-scale 4X4 Slash, Stampede®, Rustler®, Rally) Gear set, center differential (output gears (2)/ spider gears (4)/ spider
5114	Ball bearings, blue rubber sealed (5x8x2.5mm) (2)	0700	gear shaft (2))
5117	Ball bearings, blue rubber sealed (6x12x4mm) (2)	6882X	Gear set, differential (output gears (2)/ spider gears (2)/ spider gear
5118	Ball bearings, blue rubber sealed (8x16x5mm) (2)	0704	shaft, carrier support)
1985	PTFE-coated washers, 5x8x0.5mm (20) (use with ball bearings)	6781	Housing, center differential (aluminum)/ x-ring gaskets (2)/ ring gear gasket/ bushings (2)/ 5x10x0.5mm PTFE-coated washers
	Body & Accessories		(2)/ 2.5x8 CCS (4)
1926	Antenna caps, vinyl (2)/ antenna spool	9081	Housing, center differential/ x-ring gaskets (2)/ 5x10x0.5 PTFE-
1726 9015	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) Body mounts, front & rear/ 3x12mm CS (4)/ 3x12mm shoulder screw	2004	coated washer (1)/ 2.5x8 CCS (4)
9013	(2)/ 3x10mm flat-head machine screw (6)/ 3x12mm BCS (1)	6881 6880	Housings, differential, front
9010	Body reinforcement set #9011	6782	Housings, differential, rear Output gears, center differential, hardened steel (2)
9013	Body support/ 3x12mm CS (4) / (fits #9011 body)	5379X	Ring gear, differential/ pinion gear, differential
9011	Body, Hoss™ 4X4 (clear, requires painting)/ window, grille, lights	5379R	Ring gear, differential/ pinion gear, differential (machined, spiral
00440	decal sheet		cut) (front)
9011G	Body, Hoss™ 4X4 VXL, green/ window, grille, lights decal sheet (assembled with front & rear body mounts and rear body support for	6879R	Ring gear, differential/ pinion gear, differential (machined, spiral
	clipless mounting)	6879	cut) (rear) Ring gear, differential/ pinion gear, differential (rear)
9011A	Body, Hoss™ 4X4 VXL, orange/ window, grille, lights decal sheet	3965	Screws, 2.5x8mm cap-head machine (6)
	(assembled with front & rear body mounts and rear body support for	1647	Silicone grease
00117	clipless mounting)		Driveline Components
9011X	Body, Hoss™ 4X4, ProGraphix® (Graphics are printed, requires paint & final color application)/ window, grille, lights decal sheet	E110A	Ball bearings, black rubber sealed (10x15x4mm) (2)
2514	Decal sheet, racing sponsors	5119A 5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)
9950	Official Team Traxxas® racing decal set (flag logo/ 6-color)	5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)
9017	Skid plate, roof (body) (black) (left & right)/ 3x8mm CS (4)	9059X	Cross pin (2)/ drive pin (2) (repairs 1 axle shaft)
9012	Tailgate protector/ 3x10mm flat-head screw (3)	6758	Differential output shaft (for steel constant-velocity driveshafts)
	Center Driveline	00557	(2)
5119A	Ball bearings, black rubber sealed (10x15x4mm) (2)	9057X 6828A	Differential output shafts, steel-splined constant-velocity (2) Differential output yoke assembly, extreme heavy duty (2) (left o
5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)	0020A	right, front or rear) (assembled with external-splined half shaft)
5120	Ball bearings, blue rubber sealed (12x18x4mm) (2)	6851A	Driveshaft assembly, front, extreme heavy duty (1) (left or right) (fully
5116 5117	Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2)		assembled, ready to install)/ screw pin (1)
9041	Cover, center driveshaft (clear)	6852A	Driveshaft assembly, rear, extreme heavy duty (1) (left or right) (fully
6877	Cover, gear/ motor wire hold-down clip	6765	assembled, ready to install)/ screw pin (1) Driveshaft, center, 6061-T6 aluminum (blue-anodized) (189mm)
7477	Cover, gear/ wire retainer	6765G	Driveshaft, center, 6061-T6 aluminum (green-anodized) (189mm)
6888	Drive hub, center, rear (1)/ 4x3 GS (1)	6765A	Driveshaft, center, 6061-T6 aluminum (orange-anodized)
6888X	Drive hub, front, hardened steel (1)/ screw pin (1)		(189mm)
9090 5148	Gear adapter, fixed Grease, white lithium	6765R	Driveshaft, center, 6061-T6 aluminum (red-anodized) (189mm)
6890	Plate, motor	6767 6851R	Driveshaft, center, plastic, (black)/ screw pin Driveshafts, front, steel-spline constant-velocity (complete
6890X	Plate, motor, 6061-T6 aluminum (blue-anodized)	005110	assembly) (2)
2575	Screws, 3x6mm button-head machine (hex drive) (6)	9051X	Driveshafts, front, steel-spline constant-velocity (complete
2554	Screws, 3x6mm cap-head machine (hex drive) (6)		assembly) (2)
3932	Screws, 3x6mm flat-head machine (hex drive) (6)	6852R	Driveshafts, rear, steel-spline constant-velocity (complete
1647	Silicone grease	9052X	assembly) (2) Driveshafts, rear, steel-spline constant-velocity (complete
	Chassis & Attachments	300 <u>2</u> X	assembly) (2)
9026	Battery hold-down (2)/ battery clip/ hold-down post/ screw pin/ pivot	9055X	Half shaft, external splined (steel-spline constant velocity) (1)
6724	post screw Box, receiver (sealed)/ foam pad/ 2.5x8mm CS (4)/ 3x10mm CS (2)	6750	Half shaft, external splined (steel-spline constant-velocity) (1)
9035	Bumper, front/ bumper support	9056X	Half shaft, internal splined (steel-spline constant velocity) (1)
9036	Bumper, rear/ bumper mount, rear/ bumper support, rear	6751 9058X	Half shaft, internal splined (steel-spline constant-velocity) (1) Rebuild kit, steel-splined constant-velocity driveshafts (includes
9022	Chassis	3030A	pins and hardware for one axle shaft)
9023	Nerf bars, chassis (2)	6757	Rebuild kit, steel-splined constant-velocity driveshafts (includes
9078	Wheelie bar (assembled)		pins, dustboots, lube, and hardware)
6777 3678	Wheelie bar mounts/ rear skidplate (black) Wheelie bar, assembled (black) (fits Slash, Bandit, Rustler®,	6854A	Stub axle assembly, front, outer, extreme heavy duty (1) (left or
30/0	Stampede® series)	COESA	right) (assembled with internal-splined half shaft)
3678X	Wheelie bar, assembled (blue) (fits Slash, Bandit, Rustler®,	6853A	Stub axle assembly, rear, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft)
	Stampede® series)	6754	Stub axle, front, 5mm (steel-splined constant-velocity
3678A	Wheelie bar, assembled (green) (fits Slash, Bandit, Rustler®,	-	driveshaft) (1)
00705	Stampede® series)	9054X	Stub axle, front, steel-splined constant velocity (1)
3678P	Wheelie bar, assembled (pink) (fits Slash, Bandit, Rustler®, Stampede® series)	6753	Stub axle, rear, 5mm (steel-splined constant-velocity driveshaft)
		9053X	(1) Stub axle, rear, steel-splined constant velocity (1)
			OLUD UNIC, ICAI, SICCI-SDIIIICU CUIISIAIII VCIUCIIV (I)
5440	Differential Components		
5119 5117	Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (6x12x4mm) (2)	1654 1654X	Wheel hubs, hex (2)/ stub axle pins (2) Wheel hubs, hex (blue-anodized, lightweight aluminum) (2)/ axle

Page 2	Hoss™ 4X4 VXL: TQi Traxxas Link Enabled 2.4GHz Radio & TSM (Model 90076-4) Parts List
--------	---

	Front Suspension & Steering	1589	Double-sided adhesive tape (25mm x 25mm) (2)
2728	Ball bearings (5x8x2.5mm) (2)	2586 2745	Screws, 3x15mm cap-head machine (hex drive) (6) Nuts, 3mm nylon locking (12)
5114	Ball bearings, blue rubber sealed (5x8x2.5mm) (2)	3647	Nuts, 4mm flanged nylon locking (steel, serrated) (8)
6823	Bulkhead tie bars, front & rear, aluminum (blue-anodized)	1747	Nuts, 4mm nylon locking (10)
6823G	Bulkhead tie bars, front & rear, aluminum (green-anodized)	1747A	Nuts, aluminum, flanged, serrated (4mm) (red-anodized) (4)
6823R	Bulkhead tie bars, front & rear, aluminum (red-anodized)	1985	PTFE-coated washers, 5x8x0.5mm (20) (use with ball bearings)
6830X	Bulkhead, front	5525	Rod ends (12)/ hollow balls (12)
6735	Bumper, front/ skidplate, front (black)	2742X	Rod ends, short (6)/ hollow balls (6)
3643X	Camber links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum	3347	Screws, 2.5x5mm button-head machine (hex drive) (6)
	wrench (1) (#2579 3x15 BCS (4) required for installation)	3215	Screws, 2.5x6mm cap-head machine (hex drive) (6)
3643G	Camber links, front (TUBES green-anodized, 7075-T6 aluminum,	3965	Screws, 2.5x8mm cap-head machine (6)
	stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum	2577	Screws, 3x10mm button-head machine (hex drive) (6)
	wrench (1) (#2579 3x15 BCS (4) required for installation)	2578	Screws, 3x12mm button-head machine (hex drive) (6)
3643R	Camber links, front (TUBES red-anodized, 7075-T6 aluminum,	2552	Screws, 3x12mm countersunk machine (6) (hex drive)
	stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum	2579	Screws, 3x15mm button-head machine (hex drive) (6)
	wrench (1) (#2579 3x15 BCS (4) required for installation)	3646	Screws, 3x15mm flat-head machine (hex drive) (6)
6832X	Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left &	2583 2580	Screws, 3x18mm button-head machine (hex drive) (6)
6832G	right Contar blocks (a bubs) 6064 T6 aluminum (green anadized) left	2591	Screws, 3x20mm button-head machine (hex drive) (6) Screws, 3x23mm button-head machine (hex drive) (6)
00320	Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right	2582	Screws, 3x30mm button-head machine (hex drive) (6)
6832A	Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized),	2592	Screws, 3x40mm button-head machine (hex drive) (6)
000271	left & right	2575	Screws, 3x6mm button-head machine (hex drive) (6)
6832R	Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left &	2534	Screws, 3x6mm countersunk machine (6) (hex drive)
	right	3932	Screws, 3x6mm flat-head machine (hex drive) (6)
6832	Caster blocks (c-hubs), left & right	2576	Screws, 3x8mm button-head machine (hex drive) (6)
6845A	Drag link, machined 6061-T6 aluminum (blue-anodized)	3931	Screws, 3x8mm flat-head machine (hex drive) (6)
6845G	Drag link, machined 6061-T6 aluminum (green-anodized)	3936	Screws, 4x10mm button-head machine (hex drive) (6)
6845T	Drag link, machined 6061-T6 aluminum (orange-anodized)	3937	Screws, 4x12mm button-head machine (hex drive) (6)
6845R	Drag link, machined 6061-T6 aluminum (red-anodized)	2542	Screws, 4x12mm countersunk machine (hex drive) (6)
6851A	Driveshaft assembly, front, extreme heavy duty (1) (left or right) (fully	3938	Screws, 4x14mm button-head machine (hex drive) (6)
	assembled, ready to install)/ screw pin (1)	2546	Screws, 4x15mm countersunk machine (hex drive) (6)
6851R	Driveshafts, front, steel-spline constant-velocity (complete	2743	Set (grub) screws, 3mm hardened (12)
7400	assembly) (2)	3642X	Shoulder screws, Ultra Shocks (3x12 hex drive) (6)
7438	Linkage, steering	2754	Stub axle pins (4)
6739	Shock tower, front	2748X	Tool set (includes 1.5mm & 2.5mm hex wrenches/ 4-way wrench/
6739X	Shock tower, front, 7075-T6 aluminum (blue-anodized) (1)/ body		4mm and 8mm wrench/ U-joint wrench)
6739G	mount bracket (1) Shock tower, front, 7075-T6 aluminum (green-anodized) (1)/ body	2746	Washers, 3x6mm metal (12)
07330	mount bracket (1)		Motors & Electronics
6739R	Shock tower, front, 7075-T6 aluminum (red-anodized) (1)/ body	1726	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)
	mount bracket (1)	2260	BEC assembly (complete)
6845X	Steering bellcranks/ servo saver/ servo saver spring/ servo spring	3456	Cooling fan kit (with shroud) (fits #3351R and #3461 motors)
	retainer/servo horn, steering		(requires #3458 heat sink to mount)
6837X	Steering blocks, 6061-T6 aluminum (blue-anodized), left & right	3340	Cooling fan, Velineon® VXL-3s ESC
6837G	Steering blocks, 6061-T6 aluminum (green-anodized), left & right	9090	Gear adapter, fixed
6837A	Steering blocks, 6061-T6 aluminum (orange-anodized), left &	2072A	Gear set (for 2070, 2075 servos)
C007D	right	2072X	Gear set, metal (for 2070, 2075 servos)
6837R 6837	Steering blocks, 6061-T6 aluminum (red-anodized), left & right	2252	Gear set, metal (for 2250, 2255 servos)
6854A	Steering blocks, left & right Stub axle assembly, front, outer, extreme heavy duty (1) (left or	2072R	Gear set, metal, high speed (for 2070, 2075 servos)
00077	right) (assembled with internal-splined half shaft)	3458	Heat sink (fits #3351R and #3461 motors)
6754	Stub axle, front, 5mm (steel-splined constant-velocity	6860A	Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm
	driveshaft) (1)	6860R	NL (1) Motor mount, 6061-T6 aluminum (blue-anodized)
3655P	Suspension arms, blue, front/rear (left & right), heavy duty (2)	3461	Motor, Velineon® 540XL, 2400Kv 70mm, brushless (assembled with
3655R	Suspension arms, front/rear (left & right), heavy duty (2)	3401	6.5mm gold-plated bullet connectors) (for Maxx®/Hoss™) (not for use
3655G	Suspension arms, green, front/rear (left & right), heavy duty (2)		in marine models)
3655T	Suspension arms, orange, front/rear (left & right), heavy duty (2)	6890	Plate, motor
3655L	Suspension arms, red, front/rear (left & right), heavy duty (2)	6890X	Plate, motor, 6061-T6 aluminum (blue-anodized)
3655A	Suspension arms, white, front/rear (left & right), heavy duty (2)	3347	Screws, 2.5x5mm button-head machine (hex drive) (6)
6834	Suspension pin set, complete (front and rear)	3932	Screws, 3x6mm flat-head machine (hex drive) (6)
6898	Sway bar kit (front and rear) (includes front and rear sway bars	2254	Servo case, aluminum (blue-anodized) (middle) (for 2250 servo)
	and adjustable linkage)	2253	Servo case, aluminum (red-anodized) (middle) (for 2255 servo)
6742X	Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger	2251	Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for
07/05	than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1)		2250, 2255 servos)
6742G	Toe links (TUBES green-anodized, 7075-T6 aluminum, stronger	2074	Servo case/gaskets (for 2056 and 2075 waterproof servos)
67465	than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1)	2075R	Servo, digital high-speed, metal gear (ball bearing), waterproof
6742R	Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger	2075	Servo, digital high-torque (ball bearing), waterproof
3643	than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Turnbuckles, camber link, 49mm (82mm center to center) (assembled	2250	Servo, digital high-torque 330 coreless, metal gear (ball bearing),
JU -1 J	with rod ends and hollow balls) (1 left, 1 right)		waterproof
5539	Turnbuckles, camber links, 58mm (assembled with rod ends and	2255	Servo, digital high-torque 400 brushless, metal gear (ball
3000	hollow balls) (2)	2075	bearing), waterproof
	Hardware	2075X	Servo, digital high-torque, metal gear (ball bearing), waterproof
1000			Radio System, Batteries & Chargers
1926	Antenna caps, vinyl (2)/ antenna spool	2849X	4000mAh 11.1v 3-Cell 25C LiPo Battery
	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)	2872X	5000mAh 11.1v 3-Cell 25C LiPo Battery
1726			
	Screws, 3x8mm cap-head machine (hex drive) (6)/washers (6)/	2843X	5800mAh 7.4v 2-Cell 25C LiPo Battery
1726 1552	Screws, 3x8mm cap-head machine (hex drive) (6)/washers (6)/ wrench	2869X	5800mAh 7.4v 2-Cell 25C LiPo Battery 7600mAh 7.4v 2-Cell 25C LiPo Battery
1726 1552 3935	Screws, 3x8mm cap-head machine (hex drive) (6)/washers (6)/ wrench Body clip (mounting clip), angled, 90-degrees (10)	2869X 2976	7600mAh 7.4v 2-Cell 25C LiPo Battery AC to DC converter, 40W
1726 1552	Screws, 3x8mm cap-head machine (hex drive) (6)/washers (6)/ wrench	2869X	7600mAh 7.4v 2-Cell 25C LiPo Battery

Page 3	Hoss™ 4X4 VXL	.: TQi Traxxas Link Enabled	I 2.4GHz Radio & TSM	(Model 90076-4) Parts List
--------	---------------	-----------------------------	----------------------	----------------------------

2943 6548	Battery charge indicators (green (4), blue (4), grey (4)) Battery door, transmitter (replacement for #6516, 6517, 6528, 6529,	6823	Rear Suspension Bulkhead tie bars, front & rear, aluminum (blue-anodized)
2044	6530 transmitters)	6823G	Bulkhead tie bars, front & rear, aluminum (blue-anodized) Bulkhead tie bars, front & rear, aluminum (green-anodized)
2914 2923X	Battery, Power Cell AA Alkaline (4)	6823R	Bulkhead tie bars, front & rear, aluminum (red-anodized)
923A 940X	Battery, Power Cell, 3000mAh (NiMH, 7-C flat, 8.4V) Battery, Series 3 Power Cell, 3300mAh (NiMH, 7-C flat, 8.4V)	6829	Bulkhead, rear
950X 960X	Battery, Series 4 Power Cell, 4200mAh (NiMH, 7-C flat, 8.4V) Battery, Series 5 Power Cell, 5000mAh (NiMH, 7-C flat, 8.4V)	3644X	Camber links, rear (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum
983	Battery/charger completer pack (includes #2969 2-amp NiMH peak detecting AC charger (1), #2923X 3000mAh 8.4V 7-cell NiMH	3644G	wrench (1) (#2579 3x15 BCS (4) required for installation) Camber links, rear (TUBES green-anodized 7075-T6 aluminum, stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum
992	battery (1)) Battery/charger completer pack (includes #2970 iD® charger (1),	3644R	wrench (1) (#2579 3x15 BCS (4) required for installation) Camber links, rear (TUBES red-anodized, 7075-T6 aluminum,
994	#2843X 5800mAh 7.4V 2-cell 25C LiPo battery (1)) Battery/charger completer pack (includes #2970 iD® charger (1), #2849X 4000mAh 11.1v 3-Cell 25C LiPo Battery (1))		stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
260	BEC assembly (complete)	1952X	Carriers, stub axle (blue-anodized 6061-T6 aluminum) (rear) (2)
975	Charger, DC, 4 amp (6 - 7 cell, 7.2 - 8.4 volt, NiMH)	1952G	Carriers, stub axle (green-anodized 6061-T6 aluminum) (rear) (2
972	Charger, EZ-Peak® Dual, 100W, NiMH/LiPo with iD® Auto Battery Identification	1952T 1952	Carriers, stub axle (orange-anodized 6061-T6 aluminum) (rear) (2) Carriers, stub axle (rear) (2)
973	Charger, EZ-Peak® Live Dual, 200W, NiMH/LiPo with iD® Auto	1952A	Carriers, stub axle (red-anodized 6061-T6 aluminum) (rear) (2)
971	Battery Identification Charger, EZ-Peak® Live, 100W, NiMH/LiPo with iD® Auto Battery Identification	6852A	Driveshaft assembly, rear, extreme heavy duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1)
970	Charger, EZ-Peak® Plus, 4 amp, NiMH/LiPo with iD® Auto Battery Identification	6852R	Driveshafts, rear, steel-spline constant-velocity (complete assembly) (2)
525	Communication link, telemetry expander	6738	Shock tower, rear
978	Fuse, charger, 5A (2) (for #2974, 2975, 2977)	6738X	Shock tower, rear, 7075-T6 aluminum (blue-anodized) (1)/ body
072A	Gear set (for 2070, 2075 servos)	6738G	mount bracket (1) Shock tower, rear, 7075-T6 aluminum (green-anodized) (1)/ body
072X	Gear set, metal (for 2070, 2075 servos)	01300	mount bracket (1)
252 072B	Gear set, metal (for 2250, 2255 servos)	6738R	Shock tower, rear, 7075-T6 aluminum (red-anodized) (1)/ body
072R 968X	Gear set, metal, high speed (for 2070, 2075 servos) LiPo cell voltage checker/balancer (includes #2938X adapter for Traxxas® iD® batteries)	6853A	mount bracket (1) Stub axle assembly, rear, outer, extreme heavy duty (1) (left or
968	LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® batteries)	3655P	right) (assembled with internal-splined half shaft) Suspension arms, blue, front/rear (left & right), heavy duty (2)
535	Mount, temperature sensor (electric motors)/ wire tie/ thermal	3655R 3655G	Suspension arms, front/rear (left & right), heavy duty (2)
	pad	3655T	Suspension arms, green, front/rear (left & right), heavy duty (2) Suspension arms, orange, front/rear (left & right), heavy duty (2)
533	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel)	3655L	Suspension arms, red, front/rear (left & right), heavy duty (2)
932	Screws, 3x6mm flat-head machine (hex drive) (6)	3655A	Suspension arms, white, front/rear (left & right), heavy duty (2)
552	Seal kit, expander box (includes o-ring, seals, and silicone grease)	6834	Suspension pin set, complete (front and rear)
526	Sensor, auto-detectable, temperature	6898	Sway bar kit (front and rear) (includes front and rear sway bars
527	Sensor, auto-detectable, voltage	0044	and adjustable linkage)
521	Sensor, temperature and voltage (long)	3644	Turnbuckles, camber link, 39mm (69mm center to center) (assemble with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on
254	Servo case, aluminum (blue-anodized) (middle) (for 2250 servo)		Slash, rear on Slash 4X4)
253	Servo case, aluminum (red-anodized) (middle) (for 2255 servo)		Shock Oil
251	Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for	E024	
074	2250, 2255 servos) Servo case/gaskets (for 2056 and 2075 waterproof servos)	5031 5032	Oil, shock (20 wt, 200 cSt, 60cc) (silicone) Oil, shock (30 wt, 350 cSt, 60cc) (silicone)
075R	Servo, digital high-speed, metal gear (ball bearing), waterproof	5032	Oil, shock (40 wt, 500 cSt, 60cc) (silicone)
075	Servo, digital high-torque (ball bearing), waterproof	5034	Oil, shock (50 wt, 600 cSt, 60cc) (silicone)
250	Servo, digital high-torque 330 coreless, metal gear (ball bearing),	5035	Oil, shock (60 wt, 700 cSt, 60cc) (silicone)
	waterproof	5036	Oil, shock (70 wt, 900 cSt, 60cc) (silicone)
255	Servo, digital high-torque 400 brushless, metal gear (ball	5037	Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone)
075X	bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof	5029	Shock oil bottle (60cc) (for mixing shock oil)
553X	Telemetry expander 2.0 and GPS module 2.0, TQi radio system	5038X	Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, 8 80 wt premium shock oils with spinning carousel rack)
550X	Telemetry expander 2.0, TQi radio system (for use only with	1667	Silicone shock oil (30 wt), 60cc
	#6551X GPS module)	5038	Spinning carousel rack
551X	Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander)		Shocks (GTR)
509R	TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver)	7466X 7466	Body, GTR long (hard-anodized, PTFE-coated aluminum) (1) Body, GTR long shock, aluminum (blue-anodized) (PTFE-coated
507R	TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver)	7466G	bodies) (1) Body, GTR long shock, aluminum (green-anodized) (PTFE- coated bodies) (1)
528	Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2- channel (transmitter only)	7466A	Body, GTR long shock, aluminum (orange-anodized) (PTFE- coated bodies) (1)
529	Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3-channel (transmitter only)	7467X 7467	Body, GTR xx-long (hard-anodized, PTFE-coated aluminum) (1) Body, GTR xx-long shock, aluminum (blue-anodized) (PTFE-
530	Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4-channel (transmitter only)	7467G	coated bodies) (1) Body, GTR xx-long shock, aluminum (green-anodized) (PTFE-
511	Traxxas Link™ Wireless Module Ready-To-Race Model	7467A	coated bodies) (1) Body, GTR xx-long shock, aluminum (orange-anodized) (PTFE-
90076-4	Hoss™ 4X4 VXL: 1/10 Scale Monster Truck with TQi Traxxas Link™ Enabled 2.4GHz Radio System & Traxxas Stability Management	7468	coated bodies) (1) Caps and spring retainers, GTR long/xx-long shock (upper cap (2)/ hollow balls (4)/ bottom cap (2)/ upper retainer (2)/ lower
	(TSM)®	7400	retainer (2))
		7463	Rebuild kit, GTR long/xx-long shocks (x-rings, bladders, piston piston nuts, shock rod ends, hollow balls) (renews 2 shocks)

5 4	Harath AVA NVI TO: To an I de Facilia de AOII	D. J. C	7 TOM (M. 1-1 00070 4) P. 4- 17-4
Page 4	Hoss™ 4X4 VXL: TQi Traxxas Link Enabled 2.4GHz	Radio 8	k TSM (Model 90076-4) Parts List
5469	Rod ends (GTR shocks) (6)	3769	Spring pre-load spacers: 1mm (4)/ 2mm (2)/ 4mm (2)/ 8mm (2)
7464T 7465T	Shaft, GTR long, TiN-coated (2) Shaft, GTR xx-long, TiN-coated (2)	3768	Spring retainers, upper & lower (2)/ piston head set (2-hole (2)/ 3-hole (2))
7461	Shocks, GTR long blue-anodized, PTFE-coated bodies with TiN	3758	Springs, front (black) (2)
	shafts (fully assembled, without springs) (2)	3758T	Springs, front (blue) (2)
7461G	Shocks, GTR long green-anodized, PTFE-coated bodies with TiN	3758A	Springs, front (green) (2)
7461X	shafts (fully assembled, without springs) (2) Shocks, GTR long hard-anodized, PTFE-coated bodies with TiN	3758P 6863	Springs, front (pink) (2) Springs, front (progressive, +10% rate, pink) (2)
	shafts (assembled) (2) (without springs)	6864	Springs, front (progressive, +20% rate, blue) (2)
7462	Shocks, GTR xx-long blue-anodized, PTFE-coated bodies with	6862	Springs, front (progressive, -10% rate, green) (2)
7462G	TiN shafts (fully assembled, without springs) (2) Shocks, GTR xx-long green-anodized, PTFE-coated bodies with	6861	Springs, front (progressive, -20% rate, orange) (2)
	TiN shafts (fully assembled, without springs) (2)	3758X 6857	Springs, front (white) (2) Springs, front (white) (progressive rate) (2)
7462X	Shocks, GTR xx-long hard-anodized, PTFE-coated bodies with	3757	Springs, rear (black) (2)
7440	TiN shafts (assembled) (2) (without springs) Spring, shock, white (GTR long) (0.623 rate orange) (1 pair)	3757T	Springs, rear (blue) (2)
7441	Spring, shock, white (GTR long) (0.653 rate green) (1 pair)	3757A 3757P	Springs, rear (green) (2) Springs, rear (pink) (2)
7444	Spring, shock, white (GTR long) (0.767 rate black) (1 pair)	6867	Springs, rear (pink) (2) Springs, rear (progressive, +10% rate, pink) (2)
7445	Spring, shock, white (GTR long) (0.810 rate pink) (1 pair)	6868	Springs, rear (progressive, +20% rate, blue) (2)
7448 7442	Spring, shock, white (GTR long) (0.892 rate blue) (1 pair) Spring, shock, white (GTR xx-long) (0.711 rate orange) (1 pair)	6866	Springs, rear (progressive, -10% rate, green) (2)
7443	Spring, shock, white (GTR xx-long) (0.762 rate green) (1 pair)	6865 3757X	Springs, rear (progressive, -20% rate, orange) (2) Springs, rear (white) (2)
7446	Spring, shock, white (GTR xx-long) (0.874 rate black) (1 pair)	6858	Springs, rear (white) (progressive rate) (2)
7447 7449	Spring, shock, white (GTR xx-long) (0.884 rate pink) (1 pair) Spring, shock, white (GTR xx-long) (1.004 rate blue) (1 pair)	3760	Ultra Shocks (black) (long) (complete w/ spring pre-load spacers
7445		2700	& springs) (front) (2)
0004	Shocks (Pro-level Aluminum)	3762	Ultra Shocks (black) (xx-long) (complete w/ spring pre-load spacers & springs) (rear) (2)
2664 2666	Big Bore shock cylinder (long) (1) Big Bore shock cylinder (XX-long) (1)	3760A	Ultra Shocks (grey) (long) (complete w/ spring pre-load spacers &
5862	Big Bore shocks (hard-anodized & PTFE-coated T6 aluminum)	07004	springs) (2)
	(assembled with TiN shafts and springs) (front & rear) (4)	3762A	Ultra Shocks (grey) (xx-long) (complete w/ spring pre-load spacers & springs) (rear) (2)
2660	Big Bore shocks (long) (hard-anodized & PTFE-coated T6 aluminum) (assembled with TiN shafts) w/o springs (front) (2)		Spur Gears & Pinion Gears
2662	Big Bore shocks (XX-long) (hard-anodized & PTFE-coated T6	6877	Cover, gear/ motor wire hold-down clip
	aluminum) (assembled with TiN shafts) w/o springs (rear) (2)	9090	Gear adapter, fixed
2669	Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushings & washers (2) (Big Bore Shocks)	5641	Gear, 11-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits
2362	Rebuild kit, Ultra shocks (for 2 shocks)	5642	5mm shaft)/ set screw Gear, 13-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits
1942	Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws	3042	5mm shaft)/ set screw
2742V	(2) Red and a short (6)/ hellow hello (6)	5640	Gear, 14-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits
2742X 2667	Rod ends, short (6)/ hollow balls (6) Shock caps, aluminum (Big Bore Shocks) (2)	EC 42	5mm shaft)/ set screw
1664T	Shock shafts, hardened steel, titanium nitride coated (long) (2)	5643	Gear, 17-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw
2656T	Shock shafts, hardened steel, titanium nitride coated (xx-long)	5644	Gear, 18-T pinion (0.8 metric pitch, compatible with 32-pitch)
1664	(2) Shock shafts, steel, chrome finish (long) (2)	5646	(hardened steel) (fits 5mm shaft)/ set screw
2656	Shock shafts, steel, chrome finish (xx-long) (2)	3040	Gear, 20-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits 5mm shaft)/ set screw
1765	Silicone diaphragms (4)	6842X	Spur gear, steel, 50-tooth (0.8 metric pitch, compatible with 32-
2668	Spring retainers, upper & lower (2)/ spring pre-load spacers: 1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore	3956X	pitch) (for center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compatible with 32-pitch)
	Shocks)	39307	(requires #6780 center differential)
6863	Springs, front (progressive, +10% rate, pink) (2)		Steering Components
6864	Springs, front (progressive, +20% rate, blue) (2)	1552	Screws, 3x8mm cap-head machine (hex drive) (6)/washers (6)/
6862 6861	Springs, front (progressive, -10% rate, green) (2) Springs, front (progressive, -20% rate, orange) (2)		wrench
6857	Springs, front (white) (progressive rate) (2)	2728	Ball bearings (5x8x2.5mm) (2)
6867	Springs, rear (progressive, +10% rate, pink) (2)	5114 6845A	Ball bearings, blue rubber sealed (5x8x2.5mm) (2)
6868	Springs, rear (progressive, +20% rate, blue) (2)	6845G	Drag link, machined 6061-T6 aluminum (blue-anodized) Drag link, machined 6061-T6 aluminum (green-anodized)
6866 6865	Springs, rear (progressive, -10% rate, green) (2) Springs, rear (progressive, -20% rate, orange) (2)	6845T	Drag link, machined 6061-T6 aluminum (orange-anodized)
6858	Springs, rear (white) (progressive rate) (2)	6845R	Drag link, machined 6061-T6 aluminum (red-anodized)
	Shocks (Ultra Shocks)	7438 2742X	Linkage, steering
3642	Attachment screws, shock (3x12mm shoulder screws) (6)	6845X	Rod ends, short (6)/ hollow balls (6) Steering bellcranks/ servo saver/ servo saver spring/ servo spring
3765A	Body, Ultra Shock(s) (long) (grey) (2)		retainer/servo horn, steering
3766A	Body, Ultra Shock(s) (XXL) (grey) (2)	6742	Toe link, front & rear (molded composite) (2)/ hollow balls (4)
5475 2362	Multi-tool (plastic) Rebuild kit, Ultra shocks (for 2 shocks)	6742X	(87mm center to center) Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger
1942	Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball		than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1)
	screws (2)	6742G	Toe links (TUBES green-anodized, 7075-T6 aluminum, stronger
2742X	Rod ends, short (6)/ hollow balls (6)	6742R	than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger
3767 8361	Shock caps (2)/ shock bottoms (2) Shock caps (black) (4) (assembled with hollow balls)	÷. →=/\	than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1)
3767A	Shock caps, aluminum (blue-anodized) (4) (fits all Ultra Shocks)	2746	Washers, 3x6mm metal (12)
3767G	Shock caps, aluminum (green-anodized) (4) (fits all Ultra Shocks)		Suspension Linkage
3767P	Shock caps, aluminum (pink-anodized) (4) (fits all Ultra Shocks)	3643X	Camber links, front (TUBES blue-anodized, 7075-T6 aluminum,
3767X 1664T	Shock caps, aluminum (red-anodized) (4) (fits all Ultra Shocks) Shock shafts, hardened steel, titanium nitride coated (long) (2)		stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum
2656T	Shock shafts, hardened steel, titanium nitride coated (long) (2)	3643G	wrench (1) (#2579 3x15 BCS (4) required for installation) Camber links, front (TUBES green-anodized, 7075-T6 aluminum,
400:	(2)		stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum
1664 2656	Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2)		wrench (1) (#2579 3x15 BCS (4) required for installation)
1765	Silicone diaphragms (4)		

Page 5	Hoss™ 4X4 VXL: TQi Traxxas Link Enabled 2.4GHz	Radio &	TSM (Model 90076-4) Parts List
3643R	Camber links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)	8710	Speed Bit Master Set, hex and nut driver, 13-piece, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm), (ball-end: 2.0mm, 2.5mm,
3644X	Camber links, rear (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)	8711	3.0mm), and nut drivers (4.00mm, 4.50mm, 5.00mm, 5.50mm, 7.00mm, 8.00mm), Speed Bit Master Set, hex driver, 7-piece straight and ball end,
3644G	Camber links, rear (TUBES green-anodized 7075-T6 aluminum, stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)	0, 11	includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm, 2.5mm, 3.0mm), 1/4" drive
3644R	Camber links, rear (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)	8719	Speed Bit Master Set, nut driver, 6-piece, includes premium handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive
5525	Rod ends (12)/ hollow balls (12)	8716	Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4" drive
3739 6834	Screw pin set (Rustler®/ Bandit/ Stampede®) Suspension pin set, complete (front and rear)	8716X	Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm,
2537	Threaded rods (20/25/44mm 1 ea.)/ (1) 12mm set screw		3.0mm), 1/4" drive
6742X	Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1)	8715	Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm, 2.5mm), 1/4" drive
6742G	Toe links (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1)	8715X	Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm, 2.5mm, 3.0mm), 1/4" drive
6742R	Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1)	3415	Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/ 4mm, 5mm, 5.5mm, 7mm and 8mm nut
3644	Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash)		drivers/ 2mm, 4mm, and 5mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrench/ driver handle
3643	Turnbuckles, camber link, 49mm (82mm center to center) (assembled		Turnbuckles & Threaded Rods
5539	with rod ends and hollow balls) (1 left, 1 right) Turnbuckles, camber links, 58mm (assembled with rod ends and hollow balls) (2)	3643X	Camber links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
	Team Traxxas Items	3643G	Camber links, front (TUBES green-anodized, 7075-T6 aluminum,
2514	Decal sheet, racing sponsors		stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
6160X	DVD, Maxx® Power! Full Throttle Action (sleeve)	3643R	Camber links, front (TUBES red-anodized, 7075-T6 aluminum,
9950 9909	Official Team Traxxas® racing decal set (flag logo/ 6-color) Traxxas® racing banner, red & black (3x7 feet)		stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum
	Tires & Wheels	3644X	wrench (1) (#2579 3x15 BCS (4) required for installation) Camber links, rear (TUBES blue-anodized, 7075-T6 aluminum,
5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)		stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum
3647	Nuts, 4mm flanged nylon locking (steel, serrated) (8)	3644G	wrench (1) (#2579 3x15 BCS (4) required for installation) Camber links, rear (TUBES green-anodized 7075-T6 aluminum,
1747R 1985	Nuts, aluminum, flanged, serrated (4mm) (blue-anodized) (4)	00440	stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum
1965	PTFE-coated washers, 5x8x0.5mm (20) (use with ball bearings) Silicone grease		wrench (1) (#2579 3x15 BCS (4) required for installation)
2754	Stub axle pins (4)	3644R	Camber links, rear (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum
4175	Tires & wheels, assembled, glued (2.8") (All-Star black chrome wheels, paddle tires, foam inserts) (nitro rear/ 4WD electric front/rear) (2) (TSM rated)	5525	wrench (1) (#2579 3x15 BCS (4) required for installation) Rod ends (12)/ hollow balls (12)
3669A	Tires & wheels, assembled, glued (2.8") (All-Star black chrome	6742	Toe link, front & rear (molded composite) (2)/ hollow balls (4) (87mm center to center)
3669	wheels, Talon tires, foam inserts) (nitro rear/ electric front) (2) (TSM rated) Tires & wheels, assembled, glued (2.8") (All-Star chrome wheels,	6742X	Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1)
6792	Talon tires, foam inserts) (nitro rear/ electric front) (2) Tires & wheels, assembled, glued (black 2.8" wheels,	6742G	Toe links (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1)
9072	Sledgehammer™ tires, foam inserts) (2) (TSM® rated) Tires & wheels, assembled, glued (black chrome 2.8" wheels,	6742R	Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4)/ aluminum wrench (1)
3665X	Sledgehammer [™] tires, foam inserts) (2) (TSM® rated) Tires & wheels, assembled, glued (chrome wheels, Terra Groove	3644	Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on
3665	dual profile tires, foam inserts) (nitro rear/ electric front) (2) Tires & wheels, assembled, glued (satin chrome wheels, Terra	3643	Slash) Turnbuckles, camber link, 49mm (82mm center to center) (assembled
	Groove dual profile tires, foam inserts) (nitro rear/ electric front) (2)	5539	with rod ends and hollow balls) (1 left, 1 right) Turnbuckles, camber links, 58mm (assembled with rod ends and hollow balls) (2)
6771	Tires and wheels, assembled, glued 2.8" (All-Star chrome wheels, Maxx® tires, foam inserts) (2)		······································
6769	Tires, Talon EXT 2.8" (2)/ foam inserts (2)		
1654 1654X	Wheel hubs, hex (rear) (2)/ stub axle pins (2) Wheel hubs, hex (blue-anodized, lightweight aluminum) (2)/ axle pins(4)		
6856X	Wheel hubs, splined, 17mm, short (4)/ wheel nuts, splined, 17mm (4) (blue-anodized)/ hub retainer M4 X 0.7 (4)/ axle pin (4)/ wrench, 5mm		If you have questions or need technical assistance, call Traxxas at: 1-888-TRAXXAS
6772	Wheels, RXT 2.8" (black) (2)		(1-888-872-9927) (U.S. residents only)
	Traxxas Tools		For orders, calls outside the U.S., and other information, call 972-549-3000, or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com
3433X	Body reamer (aluminum handle)		TRAXXAS.COM
3433 3436	Body reamer (plastic handle) Cap, body reamer		
3432	Scissors, curved tip		
3431	Scissors, straight tip		
8712	Speed Bit Essentials Set, hex and nut driver, 7-piece, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm, and 8.0mm), 1/4" drive		
8721	Speed bit handle, medium (one piece)		
8720 8722	Speed bit handle, premium, large (rubber overmold)		
8722	Speed bit handle, premium, medium (rubber overmold)		